

Authorization Control Profile (ACP)

Bluetooth® Implementation Conformance Statement (ICS) Proforma

- **Revision:** ACP.ICS.p1
- **Revision Date:** 2025-07-08
- **Prepared By:** Medical Devices Working Group
- **Published during TCRL:** TCRL.pkg100



This document, regardless of its title or content, is not a Bluetooth Specification as defined in the Bluetooth Patent/Copyright License Agreement (“PCLA”) and Bluetooth Trademark License Agreement. Use of this document by members of Bluetooth SIG is governed by the membership and other related agreements between Bluetooth SIG Inc. (“Bluetooth SIG”) and its members, including the PCLA and other agreements posted on Bluetooth SIG’s website located at www.bluetooth.com.

THIS DOCUMENT IS PROVIDED “AS IS” AND BLUETOOTH SIG, ITS MEMBERS, AND THEIR AFFILIATES MAKE NO REPRESENTATIONS OR WARRANTIES AND DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, TITLE, NON-INFRINGEMENT, FITNESS FOR ANY PARTICULAR PURPOSE, THAT THE CONTENT OF THIS DOCUMENT IS FREE OF ERRORS.

TO THE EXTENT NOT PROHIBITED BY LAW, BLUETOOTH SIG, ITS MEMBERS, AND THEIR AFFILIATES DISCLAIM ALL LIABILITY ARISING OUT OF OR RELATING TO USE OF THIS DOCUMENT AND ANY INFORMATION CONTAINED IN THIS DOCUMENT, INCLUDING LOST REVENUE, PROFITS, DATA OR PROGRAMS, OR BUSINESS INTERRUPTION, OR FOR SPECIAL, INDIRECT, CONSEQUENTIAL, INCIDENTAL OR PUNITIVE DAMAGES, HOWEVER CAUSED AND REGARDLESS OF THE THEORY OF LIABILITY, AND EVEN IF BLUETOOTH SIG, ITS MEMBERS, OR THEIR AFFILIATES HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

This document is proprietary to Bluetooth SIG. This document may contain or cover subject matter that is intellectual property of Bluetooth SIG and its members. The furnishing of this document does not grant any license to any intellectual property of Bluetooth SIG or its members.

This document is subject to change without notice.

Copyright © 2022–2025 by Bluetooth SIG, Inc. The Bluetooth word mark and logos are owned by Bluetooth SIG, Inc. Other third-party brands and names are the property of their respective owners.

Contents

1	General principles	4
1.1	Implementation Under Test (IUT) identification	4
1.2	Enforcement of inter-layer dependencies	4
2	ICS declarations.....	5
2.1	Roles	5
2.2	Transports.....	5
2.3	Authorization Control Server role.....	5
2.3.1	Versions.....	5
2.3.2	Service and Features requirements	5
2.4	Authorization Control Client role	6
2.4.1	Versions.....	6
2.4.2	Services and Characteristics	6
2.4.3	GATT requirements	8
2.4.4	GAP requirements	9
3	References	10
4	Revision history and acknowledgments.....	11

1 General principles

1.1 Implementation Under Test (IUT) identification

Using the Bluetooth SIG qualification tool, the implementer is expected to declare details about what will be implemented.

1.2 Enforcement of inter-layer dependencies

This ICS includes one or more tables with inter-layer dependencies (ILDs). ILDs are used for specification requirements that are dependent on other supporting specifications. ILDs can refer to an individual ICS item in a separate layer (individual ILD), or it can refer to the full layer (full-layer ILD).

ILDs residing in an X2Core layer will be enforced from the Bluetooth SIG qualification tool in the following conditions, depending on where the referred ILD is residing:

Referred ILD resides in	Individual ILD	Full-layer ILD
Controller layer	Core-Complete configuration, or Referred layer is supported	N/A
Lower HCI layer	HCI is supported	N/A
Upper HCI layer	Core-Host configuration, or UHCI is supported	N/A
Host layer	Core-Host configuration, or Core-Complete configuration, or Referred layer is supported	N/A
X2Core layer	Core-Host configuration, or Core-Complete configuration, or Referred layer is supported	Core-Host configuration, or Core-Complete configuration

Table 1.1: Enforcement of an ILD within the Bluetooth SIG qualification tool

2 ICS declarations

2.1 Roles

Table 1: Role Requirements

Item	Role	Reference	Status
1	AC Server	[1] 2.1	C.1
2	AC Client	[1] 2.1	C.1

C.1: Mandatory to support at least one.

2.2 Transports

Table 2: Transport Requirements

Item	Transport	Reference	Status
1	Profile supported over BR/EDR	[1] 2.5	C.1, C.3
2	Profile supported over LE	[1] 2.5	C.2, C.3

C.1: Excluded for this Profile IF CORE 41/2 “LE Core Configuration”.

C.2: Excluded for this Profile IF CORE 41/1 “BR/EDR Core Configuration”.

C.3: Mandatory to support at least one.

2.3 Authorization Control Server role

2.3.1 Versions

Table 3: X.Y Versions

Prerequisite: ACP 1/1 “AC Server”

Item	Version	Reference	Status
1	ACP v1.0	[1]	M

Table 4: X.Y.Z Versions

Table number reserved but not yet in use.

2.3.2 Service and Features requirements

Table 5: Service and Features Requirement

Prerequisite: ACP 1/1 “AC Server”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Authorization Control Service	[1] 4	M	[4] ACS
2	Elliptic Curve Diffie Hellman (ECDH) key agreement scheme with Curve P-256 and key derivation function HKDF SHA-256 128-bit	[1] 4.1.1.1	C.1	N/A

Item	Capability	Reference	Status	Inter-Layer Dependency
3	Authentication encryption using Galois/Counter Mode (GCM)	[1] 4.1.1.2	C.2	N/A
4	Authentication messaging using Galois/Counter Mode Message Authentication Code (GMAC)	[1] 4.1.1.2	C.3	N/A

C.1: Mandatory IF ACS 3/7 “ECDH Key Exchange”, otherwise Optional.

C.2: Mandatory IF ACS 4/1 “Confidentiality” AND ACS 4/2 “Integrity” AND ACS 4/3 “Authentication”, otherwise Optional.

C.3: Mandatory IF ACS 4/2 “Integrity” AND ACS 4/3 “Authentication” AND NOT ACS 4/1 “Confidentiality”, otherwise Optional.

Table 6: No longer used

2.4 Authorization Control Client role

2.4.1 Versions

Table 7: X.Y Versions

Prerequisite: ACP 1/2 “AC Client”

Item	Version	Reference	Status
1	ACP v1.0	[1]	M

Table 8: X.Y.Z Versions

Table number reserved but not yet in use.

2.4.2 Services and Characteristics

Table 9: Discovery of Services and Characteristics Requirements

Prerequisite: ACP 1/2 “AC Client”

Item	Capability	Reference	Status
1	No longer used	N/A	N/A
2	Discover Authorization Control Service	[1] 5.2	M
3	Discover ACS Status characteristic and Client Characteristic Configuration Descriptor	[1] 5.3, 5.3.1	M
4	Discover ACS Data In characteristic	[1] 5.3, 5.3.2	M
5	Discover ACS Data Out Notify characteristic and Client Characteristic Configuration Descriptor	[1] 5.3, 5.3.3	M
6	Discover ACS Data Out Indicate characteristic and Client Characteristic Configuration Descriptor	[1] 5.3, 5.3.4	M

Item	Capability	Reference	Status
7	Discover ACS Control Point characteristic and Client Characteristic Configuration Descriptor	[1] 5.3, 5.3.5	M

Table 10: Features*Prerequisite: ACP 1/2 “AC Client”*

Item	Capability	Reference	Status
1	ECDH key agreement scheme	[1] 5.4.1	M
2	ECDH key agreement scheme with Curve P-256 and key derivation function HKDF SHA-256 128-bit	[1] 5.4.1.1	M
3	Galois/Counter Mode (GCM)	[1] 5.4.2	M
4	Galois/Counter Mode Message Authentication Code (GMAC)	[1] 5.4.2	M
5	Read ACS Status	[1] 5.5.2	O
6	Configure ACS Status characteristic for indication	[1] 5.5.2	O
7	Write to ACS Data In characteristic	[1] 5.5.3	M
8	Read ACS Data In characteristic	[1] 5.5.3	M
9	Configure ACS Data Out Notify characteristic for notifications	[1] 5.5.3	M
10	Configure ACS Data Out Indicate characteristic for indications	[1] 5.5.3	M
11	Configure ACS Control Point characteristic for indications	[1] 5.5.4	M
12	Write to ACS Control Point characteristic	[1] 5.5.4	O
13	Multiple Restriction Maps	[1] 5.5.4.1.7	O
14	Key Exchange	[1] 5.5.4.1.7	O
15	Set Security Controls Switch	[1] 5.5.4.1.7	O
16	OOB Key Exchange	[1] 5.5.4.1.7	O
17	Key URI	[1] 5.5.4.1.7	O

Table 11: ACS Control Point Procedures*Prerequisite: ACP 1/2 “AC Client”*

Item	Capability	Reference	Status
1	Get All Active Descriptors	[1] 5.5.4.2	M
2	Get Restriction Map Descriptor	[1] 5.5.4.3	M
3	Get Restriction Map ID List	[1] 5.5.4.4	M
4	Activate Restriction Map	[1] 5.5.4.5	C.1
5	Get Resource Handle To UUID Map	[1] 5.5.4.6	M
6	Get Service And Characteristic UUIDs For Characteristic Resource Handle	[1] 5.5.4.7	M
7	Get Information Security Configuration Descriptor	[1] 5.5.4.8	M
8	Get Key Descriptor	[1] 5.5.4.9	M
9	Get Current Key List	[1] 5.5.4.10	C.2
10	Start Key Exchange	[1] 5.5.4.11	C.2

Item	Capability	Reference	Status
11	Invalidate All Established Security	[1] 5.5.4.12	O
12	Invalidate Key	[1] 5.5.4.13	C.2
13	Abort	[1] 5.5.4.14	M
14	Set Security Controls Switch	[1] 5.5.4.15	C.3
15	Get Key URI	[1] 5.5.4.16	C.4
16	Get ACS Feature	[1] 5.5.4.17	M
17	Key Exchange ECDH	[1] 5.5.4.18.1.1	C.2
18	Key Exchange ECDH Confirmation Code	[1] 5.5.4.18.1.2	C.2
19	Key Exchange ECDH Confirmation Random Number	[1] 5.5.4.18.1.3	C.2
20	Key Exchange KDF	[1] 5.5.4.18.2.1	C.2
21	Set AC Client Nonce Fixed	[1] 5.5.4.19	C.2
22	Get ATT_MTU	[1] 5.5.4.20	O
23	Initiate Pairing	[1] 5.5.4.21	O

C.1: Mandatory IF ACP 10/13 “Multiple Restriction Maps”, otherwise Excluded.

C.2: Mandatory IF ACP 10/14 “Key Exchange”, otherwise Excluded.

C.3: Mandatory IF ACP 10/15 “Set Security Controls Switch”, otherwise Excluded.

C.4: Mandatory IF ACP 10/16 “OOB Key Exchange” AND ACP 10/17 “Key URI”, otherwise Excluded.

2.4.3 GATT requirements

Table 12: GATT Requirements

Prerequisite: ACP 1/2 “AC Client”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	No longer used	N/A	N/A	N/A
1a	GATT Client over BR/EDR	[1] 2.1	C.3	[2] GATT 1a/2
1b	GATT Client over LE	[1] 2.1	C.4	[2] GATT 1a/1
2	Discover All Primary Services	[1] 5.1, 5.2	C.1	[2] GATT 3/2
3	Discover Primary Services by Service UUID	[1] 5.1, 5.2	C.1	[2] GATT 3/3
4	Discover All Characteristics of a Service	[1] 5.1, 5.3	C.2	[2] GATT 3/5
5	Discover Characteristics by UUID	[1] 5.1, 5.3	C.2	[2] GATT 3/6
6	Discover All Characteristic Descriptors	[1] 5.1, 5.3	M	[2] GATT 3/7
7	Single Notification	[1] 5.1	M	[2] GATT 3/17
8	Indications	[1] 5.1	M	[2] GATT 3/18
9	Read Characteristic Value	[1] 5.1	M	[2] GATT 3/8
10	Write Characteristic Value	[1] 5.1	M	[2] GATT 3/14
11	Write Long Characteristic Values	[1] 5.1	O	[2] GATT 3/15
12	Read Characteristic Descriptors	[1] 5.1	M	[2] GATT 3/19
13	Write Characteristic Descriptors	[1] 5.1	M	[2] GATT 3/21

C.1: Mandatory to support at least one.



- C.2: Mandatory to support at least one.
- C.3: Mandatory IF ACP 2/1 “Profile supported over BR/EDR”, otherwise not defined.
- C.4: Mandatory IF ACP 2/2 “Profile supported over LE”, otherwise not defined.

2.4.4 GAP requirements

Table 13: GAP Requirements

Prerequisite: ACP 1/2 “AC Client”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Central	[1] 6	M	[3] GAP 5/4 OR GAP 38/4
2	Bondable mode	[1] 7.2	C.1	[3] GAP 34/2
3	LE security mode 1	[1] 7.2	C.2	[3] GAP 35/1

- C.1: Optional IF ACP 2/2 “Profile supported over LE”, otherwise not defined.
- C.2: Mandatory IF ACP 2/2 “Profile supported over LE”, otherwise not defined.

3 References

- [1] Authorization Control Profile (ACP) Specification, Version 1.0
- [2] ICS Proforma for Generic Attribute Profile (GATT)
- [3] ICS Proforma for Generic Access Profile (GAP)
- [4] ICS Proforma for Authorization Control Service (ACS)

4 Revision history and acknowledgments

Revision History

Publication Number	Revision Number	Date	Comments
0	p0	2022-09-20	Approved by BTI on 2022-08-31. ACP v1.0 adopted by the BoD on 2022-09-13. Prepared for initial publication.
	p1r00–r01	2025-02-04 – 2025-02-18	TSE 27101 (rating 2): Updated Table 1 conditional C.1. Updated Table 2 Status values and C.1, and added C.2 and C.3. Marked Table 6, 9/1, and 12/1 as no longer used, and added 12/1a and 12/1b. Updated 12/7. Updated C.1 and C.2 and added C.3 and C.4 for Table 12. Updated formatting for the Inter-Layer Dependency value for 13/1.
1	p1	2025-07-08	Approved by BTI on 2025-05-30. Prepared for TCRL pkg100 publication.

Acknowledgments

Name	Company
Jörg Brakensiek	Bluetooth SIG, Inc.
Ismail Mohamud	Bluetooth SIG, Inc.
Christoph Fischer	F. Hoffmann-La Roche AG
Nathaniel Hamming	HMT Consulting