

# Automation IO Service (AIOS)

## **Bluetooth®** Implementation Conformance Statement (ICS) Proforma

---

- **Revision:** AIOS.ICS.p3
- **Revision Date:** 2026-02-17
- **Prepared By:** BTI
- **Published during TCRL:** TCRL.pkg102



This document, regardless of its title or content, is not a Bluetooth Specification as defined in the Bluetooth Patent/Copyright License Agreement (“PCLA”) and Bluetooth Trademark License Agreement. Use of this document by members of Bluetooth SIG is governed by the membership and other related agreements between Bluetooth SIG Inc. (“Bluetooth SIG”) and its members, including the PCLA and other agreements posted on Bluetooth SIG’s website located at [www.bluetooth.com](http://www.bluetooth.com).

THIS DOCUMENT IS PROVIDED “AS IS” AND BLUETOOTH SIG, ITS MEMBERS, AND THEIR AFFILIATES MAKE NO REPRESENTATIONS OR WARRANTIES AND DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, TITLE, NON-INFRINGEMENT, FITNESS FOR ANY PARTICULAR PURPOSE, THAT THE CONTENT OF THIS DOCUMENT IS FREE OF ERRORS.

TO THE EXTENT NOT PROHIBITED BY LAW, BLUETOOTH SIG, ITS MEMBERS, AND THEIR AFFILIATES DISCLAIM ALL LIABILITY ARISING OUT OF OR RELATING TO USE OF THIS DOCUMENT AND ANY INFORMATION CONTAINED IN THIS DOCUMENT, INCLUDING LOST REVENUE, PROFITS, DATA OR PROGRAMS, OR BUSINESS INTERRUPTION, OR FOR SPECIAL, INDIRECT, CONSEQUENTIAL, INCIDENTAL OR PUNITIVE DAMAGES, HOWEVER CAUSED AND REGARDLESS OF THE THEORY OF LIABILITY, AND EVEN IF BLUETOOTH SIG, ITS MEMBERS, OR THEIR AFFILIATES HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

This document is proprietary to Bluetooth SIG. This document may contain or cover subject matter that is intellectual property of Bluetooth SIG and its members. The furnishing of this document does not grant any license to any intellectual property of Bluetooth SIG or its members.

This document is subject to change without notice.

Copyright © 2012–2026 by Bluetooth SIG, Inc. The Bluetooth word mark and logos are owned by Bluetooth SIG, Inc. Other third-party brands and names are the property of their respective owners.



# Contents

- 1 General principles ..... 4**
  - 1.1 Implementation Under Test (IUT) identification ..... 4
  - 1.2 Enforcement of inter-layer dependencies ..... 4
- 2 ICS declarations..... 5**
  - 2.1 Versions ..... 5
  - 2.2 Transports ..... 5
  - 2.3 Service requirements ..... 5
  - 2.4 GATT requirements ..... 6
  - 2.5 SDP requirements..... 7
- 3 References ..... 8**
- 4 Revision history and acknowledgments ..... 9**



# 1 General principles

## 1.1 Implementation Under Test (IUT) identification

Using the Bluetooth SIG qualification tool, the implementer is expected to declare details about what will be implemented.

## 1.2 Enforcement of inter-layer dependencies

This ICS includes one or more tables with inter-layer dependencies (ILDs). ILDs are used for specification requirements that are dependent on other supporting specifications. ILDs can refer to an individual ICS item in a separate layer (individual ILD), or it can refer to the full layer (full-layer ILD).

ILDs residing in an X2Core layer will be enforced from the Bluetooth SIG qualification tool in the following conditions, depending on where the referred ILD is residing:

Referred ILD resides in	Individual ILD	Full-layer ILD
Controller layer	Core-Complete configuration, or Referred layer is supported	N/A
Lower HCI layer	HCI is supported	N/A
Upper HCI layer	Core-Host configuration, or UHCI is supported	N/A
Host layer	Core-Host configuration, or Core-Complete configuration, or Referred layer is supported	N/A
X2Core layer	Core-Host configuration, or Core-Complete configuration, or Referred layer is supported	Core-Host configuration, or Core-Complete configuration

Table 1.1: Enforcement of an ILD within the Bluetooth SIG qualification tool

## 2 ICS declarations

### 2.1 Versions

Table 0: X.Y Versions

Item	Version	Reference	Status
1	AIOS v1.0	[1]	M

### 2.2 Transports

Table 1: Transport Requirements

Item	Transport	Reference	Status
1	Service supported over BR/EDR	[1] 1.3	C.1, C.3
2	Service supported over LE	[1] 1.3	C.2, C.3

C.1: Excluded for this Service IF CORE 41/2 “LE Core Configuration” OR CORE 40/1 “Core-Controller”.

C.2: Excluded for this Service IF CORE 41/1 “BR/EDR Core Configuration” OR CORE 40/1 “Core-Controller”.

C.3: Mandatory to support at least one.

### 2.3 Service requirements

Table 2: Service Requirements

Item	Feature	Reference	Status
1	Automation IO Service	[1] 2	M
2	Digital characteristic	[1] 3	C.1
3	Digital characteristic: Multiple instances	[1] 3	C.8
4	Digital characteristic: Readable	[1] 3.1	O
5	Digital characteristic: Writable	[1] 3.1	O
6	Digital characteristic: Notifications	[1] 3.1.1	C.2
7	Digital characteristic: Indications	[1] 3.1.1	C.2
8	Digital characteristic: Number of Digitals Descriptor	[1] 3.1.2	C.6
9	Digital characteristic: Value Trigger Settings Descriptor	[1] 3.1.1, 3.5	O
10	Digital characteristic: Time Trigger Settings Descriptor	[1] 3.1.1, 3.5	O
11	Digital characteristic: Presentation Format Descriptor	[1] 3.1.2	C.9
12	Digital characteristic: Characteristic Extended Properties Descriptor	[1] 3.1.2	O
13	Digital characteristic: User Description Descriptor	[1] 3.1.2	O
14	Digital characteristic: Writable User Description Descriptor	[1] 3.1.2	O
15	Digital characteristic: Write Without Response	[1] 3	O
16	Analog characteristic	[1] 3	C.1
17	Analog characteristic: Multiple instances	[1] 3	C.7
18	Analog characteristic: Readable	[1] 3.2	O



Item	Feature	Reference	Status
19	Analog characteristic: Writable	[1] 3.2	O
20	Analog characteristic: Notifications	[1] 3.2.1	C.3
21	Analog characteristic: Indications	[1] 3.2.1	C.3
22	Analog characteristic: Value Trigger Settings Descriptor	[1] 3.2.1, 3.5	O
23	Analog characteristic: Time Trigger Settings Descriptor	[1] 3.2.1, 3.5	O
24	Analog characteristic: Presentation Format Descriptor	[1] 3.2.2	C.5
25	Analog characteristic: Characteristic Extended Properties Descriptor	[1] 3.2.2	O
26	Analog characteristic: User Description Descriptor	[1] 3.2.2	O
27	Analog characteristic: Writable User Description Descriptor	[1] 3.2.2	O
28	Analog characteristic: Valid Range Descriptor	[1] 3.2.2	O
29	Analog characteristic: Write Without Response	[1] 3	O
30	Aggregate characteristic	[1] 3	O
31	Aggregate characteristic: Notifications	[1] 3.3.1	C.4
32	Aggregate characteristic: Indications	[1] 3.3.1	C.4
33	Aggregate characteristic: Triggered by Trigger Settings Descriptor in the included Digital or Analog	[1] 3.3.1, 3.5	O

- C.1: Mandatory to support at least one.
- C.2: Optional to support one and only one IF AIOS 2/2 “Digital characteristic” otherwise Excluded IF AIOS 2/31 “Aggregate characteristic: Notifications” OR AIOS 2/32 “Aggregate characteristic: Indications”, otherwise Optional.
- C.3: Optional to support one and only one IF AIOS 2/16 “Analog characteristic”, otherwise Excluded IF AIOS 2/31 “Aggregate characteristic: Notifications” OR AIOS 2/32 “Aggregate characteristic: Indications”, otherwise Optional.
- C.4: Excluded IF AIOS 2/6 “Digital characteristic: Notifications” OR AIOS 2/7 “Digital characteristic: Indications” OR AIOS 2/20 “Analog characteristic: Notifications” OR AIOS 2/21 “Analog characteristic: Indications”, otherwise Optional.
- C.5: Mandatory IF AIOS 2/17 “Analog characteristic: Multiple instances”, otherwise Optional.
- C.6: Mandatory IF AIOS 2/2 “Digital characteristic”, otherwise Excluded.
- C.7: Optional IF AIOS 2/16 “Analog characteristic”, otherwise Excluded.
- C.8: Optional IF AIOS 2/2 “Digital characteristic”, otherwise Excluded.
- C.9: Mandatory IF AIOS 2/3 “Digital characteristic: Multiple instances”, otherwise Optional.

## 2.4 GATT requirements

**Table 3: GATT Requirements**

Item	Feature	Reference	Status	Inter-Layer Dependency
1	No longer used	N/A	N/A	N/A
2	GATT Server over BR/EDR	[1] 1.4	C.7	[2] GATT 1a/4
3	GATT Server over LE	[1] 1.4	C.8	[2] GATT 1a/3
4	Write Characteristic Value	[1] 1.4	C.1	[2] GATT 4/14
5	Write Without Response	[1] 1.4	C.2	[2] GATT 4/12
6	Single Notification	[1] 1.4	C.3	[2] GATT 4/17



Item	Feature	Reference	Status	Inter-Layer Dependency
7	Indication	[1] 1.4	C.4	[2] GATT 4/18
8	Write Characteristic Descriptor	[1] 1.4	C.6	[2] GATT 4/21
9	Read Characteristic Descriptor	[1] 1.4	C.5	[2] GATT 4/19

- C.1: Mandatory IF AIOS 2/5 “Digital characteristic: Writable” OR AIOS 2/19 “Analog characteristic: Writable” OR AIOS 2/3 “Digital characteristic: Multiple instances” OR AIOS 2/17 “Analog characteristic: Multiple instances”, otherwise Optional.
- C.2: Mandatory IF AIOS 2/15 “Digital characteristic: Write Without Response” OR AIOS 2/29 “Analog characteristic: Write Without Response”, otherwise Optional.
- C.3: Mandatory IF AIOS 2/6 “Digital characteristic: Notifications” OR AIOS 2/20 “Analog characteristic: Notifications” OR AIOS 2/31 “Aggregate characteristic: Notifications”, otherwise Optional.
- C.4: Mandatory IF AIOS 2/7 “Digital characteristic: Indications” OR AIOS 2/21 “Analog characteristic: Indications” OR AIOS 2/32 “Aggregate characteristic: Indications”, otherwise Optional.
- C.5: Mandatory IF AIOS 2/2 “Digital characteristic” OR AIOS 2/20 “Analog characteristic: Notifications” OR AIOS 2/21 “Analog characteristic: Indications” OR AIOS 2/22 “Analog characteristic: Value Trigger Settings Descriptor” OR AIOS 2/23 “Analog characteristic: Time Trigger Settings Descriptor” OR AIOS 2/24 “Analog characteristic: Presentation Format Descriptor” OR AIOS 2/25 “Analog characteristic: Characteristic Extended Properties Descriptor” OR AIOS 2/26 “Analog characteristic: User Description Descriptor” OR AIOS 2/28 “Analog characteristic: Valid Range Descriptor” OR AIOS 2/31 “Aggregate characteristic: Notifications” OR AIOS 2/32 “Aggregate characteristic: Indications”, otherwise Optional.
- C.6: Mandatory IF AIOS 2/6 “Digital characteristic: Notifications” OR AIOS 2/7 “Digital characteristic: Indications” OR AIOS 2/9 “Digital characteristic: Value Trigger Settings Descriptor” OR AIOS 2/10 “Digital characteristic: Time Trigger Settings Descriptor” OR AIOS 2/14 “Digital characteristic: Writable User Description Descriptor” OR AIOS 2/20 “Analog characteristic: Notifications” OR AIOS 2/21 “Analog characteristic: Indications” OR AIOS 2/22 “Analog characteristic: Value Trigger Settings Descriptor” OR AIOS 2/23 “Analog characteristic: Time Trigger Settings Descriptor” OR AIOS 2/27 “Analog characteristic: Writable User Description Descriptor” OR AIOS 2/31 “Aggregate characteristic: Notifications” OR AIOS 2/32 “Aggregate characteristic: Indications”, otherwise not defined.
- C.7: Mandatory IF AIOS 1/1 “Service supported over BR/EDR”, otherwise not defined.
- C.8: Mandatory IF AIOS 1/2 “Service supported over LE”, otherwise not defined.

## 2.5 SDP requirements

**Table 4: SDP Requirements**

*Prerequisite: AIOS 1/1 “Service supported over BR/EDR”*

Item	Feature	Reference	Status
1	SDP record present for AIOS	[1] 4	M

## 3 References

---

- [1] Automation IO Service Specification, Version 1.0
- [2] ICS Proforma for Generic Attribute Profile (GATT)



## 4 Revision history and acknowledgments

### Revision History

Publication Number	Revision Number	Date	Comments
0	1.0.0	2015-07-21	Prepared for publication.
	1.0.0 edition 2r00	2018-11-20	Editorial changes only. Template updated. Revision History and contributors moved to the end of the document.
	1.0.0 edition 2	2019-11-11	Updated copyright page and confidentiality markings to support new Documentation Marking Requirements, performed minor formatting updates, and accepted all tracked changes to prepare for edition 2 publication.
	p1r00–r01	2022-07-20 – 2022-10-13	TSE 19175 (rating 1): Updated to align with current ICS conventions/template. Removed Support columns and added Inter-Layer Dependency columns. Revised document numbering convention, setting last release publication of 1.0.0 as p0; added Publication Number column to Revision History.
1	p1	2023-02-07	Approved by BTI on 2022-12-28. Prepared for TCRL 2022-2 publication.
	p2r00–r01	2025-04-21 – 2025-04-24	TSE 27311 (rating 1): Updated the Status value for AIOS 1/1 and AIOS 1/2. In Table 1, added conditions C.1 and C.2 and renumbered C.1 as C.3. Updated C.3 in Table 1 and C.1–C.3 in Table 2. Updated the feature name for AIOS 3/6. Incorporated editorials to align the document with the latest ICS template, including updates to Section 1 and the addition of a section heading for the ICS declarations section.
2	p2	2025-07-08	Approved by BTI on 2025-06-15. Prepared for TCRL pkg100 publication.
	p3r00–r01	2025-12-04 – 2025-12-29	TSE 28169 (rating 1): Updated the conditions in the transport table to make sure the layer is excluded when the design is an implementation of the Core-Controller Configuration by adding "OR CORE 40/1 "Core-Controller"" to an already excluded transport based on Core Configuration support. Deleted draft revision history comments prior to p0.
3	p3	2026-02-17	Approved by BTI on 2026-01-21. Prepared for TCRL pkg102 publication.

### Acknowledgments

Name	Company
Alicia Courtney	Broadcom
Victor Zhodzishsky	Broadcom
Chris Church	CSR
Magnus Sommansson	CSR



---

Name	Company
David Edwin	Nordic Semiconductor
Miles Smith	Nordic Semiconductor
Mats Andersson	u-blox