

Asset Tracking Profile (ATP)

Bluetooth® Implementation Conformance Statement (ICS) Proforma

- **Revision:** ATP.ICS.p5 edition 2
- **Revision Date:** 2026-06-23
- **Prepared By:** DFWG
- **Published during TCRL:** TCRL.pkg104



This document, regardless of its title or content, is not a Bluetooth Specification as defined in the Bluetooth Patent/Copyright License Agreement (“PCLA”) and Bluetooth Trademark License Agreement. Use of this document by members of Bluetooth SIG is governed by the membership and other related agreements between Bluetooth SIG Inc. (“Bluetooth SIG”) and its members, including the PCLA and other agreements posted on Bluetooth SIG’s website located at www.bluetooth.com.

THIS DOCUMENT IS PROVIDED “AS IS” AND BLUETOOTH SIG, ITS MEMBERS, AND THEIR AFFILIATES MAKE NO REPRESENTATIONS OR WARRANTIES AND DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, TITLE, NON-INFRINGEMENT, FITNESS FOR ANY PARTICULAR PURPOSE, THAT THE CONTENT OF THIS DOCUMENT IS FREE OF ERRORS.

TO THE EXTENT NOT PROHIBITED BY LAW, BLUETOOTH SIG, ITS MEMBERS, AND THEIR AFFILIATES DISCLAIM ALL LIABILITY ARISING OUT OF OR RELATING TO USE OF THIS DOCUMENT AND ANY INFORMATION CONTAINED IN THIS DOCUMENT, INCLUDING LOST REVENUE, PROFITS, DATA OR PROGRAMS, OR BUSINESS INTERRUPTION, OR FOR SPECIAL, INDIRECT, CONSEQUENTIAL, INCIDENTAL OR PUNITIVE DAMAGES, HOWEVER CAUSED AND REGARDLESS OF THE THEORY OF LIABILITY, AND EVEN IF BLUETOOTH SIG, ITS MEMBERS, OR THEIR AFFILIATES HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

This document is proprietary to Bluetooth SIG. This document may contain or cover subject matter that is intellectual property of Bluetooth SIG and its members. The furnishing of this document does not grant any license to any intellectual property of Bluetooth SIG or its members.

This document is subject to change without notice.

Copyright © 2021–2026 by Bluetooth SIG, Inc. The Bluetooth word mark and logos are owned by Bluetooth SIG, Inc. Other third-party brands and names are the property of their respective owners.



Contents

1	General principles	4
1.1	Implementation Under Test (IUT) identification	4
1.2	Enforcement of inter-layer dependencies	4
2	ICS declarations.....	5
2.1	Roles	5
2.2	Transports.....	5
2.3	Asset Tag role	5
2.3.1	Versions.....	5
2.3.2	Services (Asset Tag).....	5
2.3.3	GAP requirements (Asset Tag)	6
2.3.4	LL requirements (Asset Tag)	7
2.4	Locator role	7
2.4.1	Versions.....	7
2.4.2	Service Support (Locator)	7
2.4.3	Discover Services and Characteristics (Locator)	7
2.4.4	Features (Locator)	8
2.4.5	GATT requirements (Locator)	8
2.4.6	GAP requirements (Locator)	8
2.4.7	LL requirements (Locator).....	9
3	References	10
4	Revision history and acknowledgments	11

1 General principles

1.1 Implementation Under Test (IUT) identification

Using the Bluetooth SIG qualification tool, the implementer is expected to declare details about what will be implemented.

1.2 Enforcement of inter-layer dependencies

This ICS includes one or more tables with inter-layer dependencies (ILDs). ILDs are used for specification requirements that are dependent on other supporting specifications. ILDs can refer to an individual ICS item in a separate layer (individual ILD), or it can refer to the full layer (full-layer ILD).

ILDs residing in an X2Core layer will be enforced from the Bluetooth SIG qualification tool in the following conditions, depending on where the referred ILD is residing:

Referred ILD resides in	Individual ILD	Full-layer ILD
Controller layer	Core-Complete configuration, or Referred layer is supported	N/A
Lower HCI layer	HCI is supported	N/A
Upper HCI layer	Core-Host configuration, or UHCI is supported	N/A
Host layer	Core-Host configuration, or Core-Complete configuration, or Referred layer is supported	N/A
X2Core layer	Core-Host configuration, or Core-Complete configuration, or Referred layer is supported	Core-Host configuration, or Core-Complete configuration

Table 1.1: Enforcement of an ILD within the Bluetooth SIG qualification tool

2 ICS declarations

2.1 Roles

Table 1: Role Requirements

Item	Role	Reference	Status
1	Asset Tag	[1] 2.1	C.1
2	Locator	[1] 2.1	C.1

C.1: Mandatory to support at least one.

2.2 Transports

Table 2: Transport Requirements

Item	Transport	Reference	Status
1	Profile supported over BR/EDR	[1] 1.5	C.1
2	Profile supported over LE	[1] 1.5	C.2, C.3

C.1: Excluded for this Profile.

C.2: Excluded for this Profile IF CORE 41/1 “BR/EDR Core Configuration” OR CORE 40/1 “Core-Controller”.

C.3: Mandatory for this Profile.

2.3 Asset Tag role

2.3.1 Versions

Table 3: X.Y Versions

Prerequisite: ATP 1/1 “Asset Tag”

Item	Version	Reference	Status
1	ATP v1.0	[1]	M

Table 4: X.Y.Z Versions

Prerequisite: ATP 1/1 “Asset Tag”

Item	Version	Reference	Status
1	ATP v1.0.1	[6]	C.1

C.1: Optional IF ATP 3/1 “ATP v1.0”, otherwise Excluded.

2.3.2 Services (Asset Tag)

Table 5: Service Requirements (Asset Tag)

Prerequisite: ATP 1/1 “Asset Tag”

Item	Feature	Reference	Status	Inter-Layer Dependency
1	Constant Tone Extension Service	[1] 3	M	[5] CTES

Item	Feature	Reference	Status	Inter-Layer Dependency
2	Include Constant Tone Extension Service UUID in AD in GAP Discoverable Mode	[1] 3.1.1	O	N/A
3	Include Local Name in AD or Scan Response	[1] 3.1.2	O	N/A
4	Writable Device Name	[1] 3.1.3	O	[3] GAP 27/6
5	Include Appearance in AD or Scan Response	[1] 3.1.4	O	N/A

2.3.3 GAP requirements (Asset Tag)

Table 6: GAP Requirements (Asset Tag)

Prerequisite: ATP 1/1 “Asset Tag”

Item	Feature	Reference	Status	Inter-Layer Dependency
1	Peripheral	[1] 2.4	M	[3] GAP 5/3
2	Central	[1] 2.4	O	[3] GAP 5/4
Peripheral Features				
3	Bondable mode	[1] 6.1	O	[3] GAP 24/2
4	Multiple Bonds	[1] 3	C.1	[3] GAP 24/4
5	LE security mode 1	[1] 6.1	O	[3] GAP 25/1
6	Authenticated Pairing (LE security mode 1 level 3)	[1] 6.1	C.2	[3] GAP 25/7
7	Unauthenticated Pairing (LE security mode 1 level 2)	[1] 6.1	C.2	[3] GAP 25/8
8	LE security mode 1 level 4	[1] 6.1	C.2	[3] GAP 25/9
9	Privacy feature	[1] 6.1	O	[3] GAP 26/1
Central Features				
10	Bondable mode	[1] 6.1	C.3	[3] GAP 34/2
11	LE security mode 1	[1] 6.1	C.3	[3] GAP 35/1
12	Unauthenticated Pairing (LE security mode 1 level 2)	[1] 6.1	C.4	[3] GAP 35/8
13	Authenticated Pairing (LE security mode 1 level 3)	[1] 6.1	C.4	[3] GAP 35/7
14	LE security mode 1 level 4	[1] 6.1	C.4	[3] GAP 35/9
15	Privacy feature	[1] 6.1	C.3	[3] GAP 36/1

- C.1: Optional IF ATP 6/3 “Bondable mode”, otherwise not defined.
C.2: Optional IF ATP 6/5 “LE security mode 1”, otherwise not defined.
C.3: Optional IF ATP 6/2 “Central”, otherwise not defined.
C.4: Optional IF ATP 6/11 “LE security mode 1”, otherwise not defined.

Table 7: No longer used

2.3.4 LL requirements (Asset Tag)

Table 8: LL Requirements (Asset Tag)

Prerequisite: ATP 1/1 “Asset Tag”

Item	Feature	Reference	Status	Inter-Layer Dependency
1	Connection CTE Response	[1] 2.5	M	[4] LL 9/15
2	No Antenna Switching During Constant Tone Extension Transmission (AoA)	[1] 2.5	M	[4] LL 9/19

2.4 Locator role

2.4.1 Versions

Table 0a: X.Y Versions

Prerequisite: ATP 1/2 “Locator”

Item	Version	Reference	Status
1	ATP v1.0	[1]	M

Table 0b: X.Y.Z Versions

Prerequisite: ATP 1/2 “Locator”

Item	Version	Reference	Status
1	ATP v1.0.1	[6]	C.1

C.1: Optional IF ATP 0a/1 “ATP v1.0”, otherwise Excluded.

2.4.2 Service Support (Locator)

Table 9: Service Support (Locator)

Prerequisite: ATP 1/2 “Locator”

Item	Feature	Reference	Status
1	Constant Tone Extension Service	[1] 4	M

2.4.3 Discover Services and Characteristics (Locator)

Table 10: Discover Services and Characteristics (Locator)

Prerequisite: ATP 1/2 “Locator”

Item	Feature	Reference	Status
1	Discover Constant Tone Extension Service	[1] 4	M
2	Discover Constant Tone Extension Enable Characteristic	[1] 4.3.1	M
3	Discover Device Name Characteristic	[1] 3.1.1.3	O

2.4.4 Features (Locator)

Table 11: Features (Locator)

Prerequisite: ATP 1/2 "Locator"

Item	Feature	Reference	Status
1	Write Constant Tone Extension Enable Characteristic	[1] 4.4.1	M
2	Read Device Name Characteristic	[1] 4, 3.1.1.3	O
3	Write Device Name Characteristic	[1] 4, 3.1.1.3	O
4	Connection Constant Tone Extension Request	[1] 4.4.1	M
5	Verify Bond Status on Reconnection	[1] 6.2	C.1

C.1: Mandatory IF ATP 13/10 "Bondable mode", otherwise Excluded.

2.4.5 GATT requirements (Locator)

Table 12: GATT Requirements (Locator)

Prerequisite: ATP 1/2 "Locator"

Item	Feature	Reference	Status	Inter-Layer Dependency
1	No longer used	N/A	N/A	N/A
2	GATT Client over LE	[1] 2.5	M	[2] GATT 1a/1
3	Discover All Primary Services	[1] 4.1	C.1	[2] GATT 3/2
4	Discover Primary Service by Service UUID	[1] 4.1	C.1	[2] GATT 3/3
5	Discover All Characteristics of a Service	[1] 4.1	C.2	[2] GATT 3/5
6	Discover Characteristics by UUID	[1] 4.1	C.2	[2] GATT 3/6
7	Read Characteristic Value	[1] 4.1	M	[2] GATT 3/8
8	Write Characteristic Value	[1] 4.1	M	[2] GATT 3/14

C.1: Mandatory to support at least one.

C.2: Mandatory to support at least one.

2.4.6 GAP requirements (Locator)

Table 13: GAP Requirements (Locator)

Prerequisite: ATP 1/2 "Locator"

Item	Feature	Reference	Status	Inter-Layer Dependency
1	Peripheral	[1] 2.4	O	[3] GAP 5/3
2	Central	[1] 2.4	M	[3] GAP 5/4
Peripheral Features				
3	Bondable mode	[1] 6.2	C.1	[3] GAP 24/2
4	Multiple Bonds	[1] 3	C.2	[3] GAP 24/4
5	LE security mode 1	[1] 6.2	C.1	[3] GAP 25/1
6	Authenticated Pairing (LE security mode 1 level 3)	[1] 6.2	C.3	[3] GAP 25/7



Item	Feature	Reference	Status	Inter-Layer Dependency
7	Unauthenticated Pairing (LE security mode 1 level 2)	[1] 6.2	C.3	[3] GAP 25/8
8	LE security mode 1 level 4	[1] 6.2	C.3	[3] GAP 25/9
9	Privacy feature	[1] 6.2	C.1	[3] GAP 26/1
Central Features				
10	Bondable mode	[1] 6.2	O	[3] GAP 34/2
11	LE security mode 1	[1] 6.2	O	[3] GAP 35/1
12	Unauthenticated Pairing (LE security mode 1 level 2)	[1] 6.2	C.4	[3] GAP 35/8
13	Authenticated Pairing (LE security mode 1 level 3)	[1] 6.2	C.4	[3] GAP 35/7
14	LE security mode 1 level 4	[1] 6.2	C.4	[3] GAP 35/9
15	Privacy feature	[1] 6.2	O	[3] GAP 36/1

C.1: Optional IF ATP 13/1 “Peripheral”, otherwise not defined.

C.2: Optional IF ATP 13/3 “Bondable mode”, otherwise not defined.

C.3: Optional IF ATP 13/5 “LE security mode 1”, otherwise not defined.

C.4: Optional IF ATP 13/11 “LE security mode 1”, otherwise not defined.

Table 14: No longer used

2.4.7 LL requirements (Locator)

Table 15: LL Requirements (Locator)

Prerequisite: ATP 1/2 “Locator”

Item	Feature	Reference	Status	Inter-Layer Dependency
1	Connection CTE Request	[1] 2.5	M	[4] LL 9/14
2	2 μ s Antenna Switching and Sampling During Constant Tone Extension Reception (AoA)	[1] 2.5	M	[4] LL 9/21

3 References

- [1] Asset Tracking Profile Specification, Version 1.0 or later
- [2] ICS Proforma for Generic Attribute Profile (GATT)
- [3] ICS Proforma for Generic Access Profile (GAP)
- [4] ICS Proforma for Link Layer (LL)
- [5] ICS Proforma for Constant Tone Extension Service (CTES)
- [6] Asset Tracking Profile Specification, Version 1.0.1

4 Revision history and acknowledgments

Revision History

Publication Number	Revision Number	Date	Comments
0	p0	2021-01-19	Approved by BTI on 2020-12-06. ATP v1.0 adopted by BoD on 2021-01-12. Prepared for publication.
	p1r00–r02	2023-09-08 – 2023-12-11	TSE 23346 (rating 2): Resolved GAP and SM inter-layer dependencies: Marked Tables 7 and 14 as no longer used. In Table 12, marked Item 1 as no longer used and updated the Feature and ILD values for Item 2. Updated the copyright page to align with v2 of the DNMD. Updated the references. Made editorial edits to align the document with the latest ICS template. Deleted draft revision history comments prior to p0.
1	p1	2024-07-01	Approved by BTI on 2024-04-21. Prepared for TCRL 2024-1 publication.
	p2r00–r03	2025-02-26 – 2025-05-13	TSE 27346 (rating 1): Updated the Status value for ATP 2/2 and added conditions C.2 and C.3. Incorporated editorials to align the document with the latest ICS template: Updated Section 1 and added a section heading for the ICS declarations section.
2	p2	2025-07-08	Approved by BTI on 2025-06-15. Prepared for TCRL pkg100 publication.
	p3r00	2025-07-16	TSE 27531 (rating 1): Updated ILD in ATP 6/1, ATP 6/2, ATP 13/1, and ATP 13/2.
3	p3	2025-11-04	Approved by BTI on 2025-10-02. Prepared for TCRL pkg101 publication.
	p4r00–r01	2025-12-04 – 2025-12-29	TSE 28169 (rating 1): Updated the conditions in the transport table to make sure the layer is excluded when the design is an implementation of the Core-Controller Configuration by adding "OR CORE 40/1 "Core-Controller"" to an already excluded transport based on Core Configuration support. Incorporated editorials to align the document with the current template.
4	p4	2026-02-17	Approved by BTI on 2026-01-21. Prepared for TCRL pkg102 publication.
	p5r00	2026-03-12	TSE 27157 (rating 2): In support of E27026, added new Item 2, "No Antenna Switching During Constant Tone Extension Transmission (AoA)" feature, as new row (8/2) in LL (Table 8).
5	p5	2026-06-23	Approved by BTI on 2026-05-28. Prepared for TCRL pkg104 publication.
	p5ed2r00	2026-06-15	TSE 29437 (rating 1): In support of E27026, updated Tables 0b and 4 and the references list to add ATP v1.0.1.
	p5 edition 2	2026-06-23	Approved by BTI on 2026-06-22. Prepared for edition 2 publication.

Acknowledgments

Name	Company
Alexandru Andreescu	Bluetooth SIG, Inc.
Christopher Badder	Bluetooth SIG, Inc.
Jim Harper	Bluetooth SIG, Inc.