

Running Out of Bits

Bluetooth® Validation Specification

- **Version:** VSr00_PR
- **Version Date:** 2025-11-19
- **Prepared By:** Core Specification Working Group
- **Feedback Email:** core-main@bluetooth.org

This CR proposes changes to the following specification (“Source Specification”):

- Bluetooth Core Specification, Version 6.1

This document is a working draft of a potential Bluetooth specification. It is subject to change and Bluetooth SIG is not required to finalize or adopt it. Although the Bluetooth SIG Board of Directors has decided to publicly release this working draft, other draft specifications, including prior or subsequent versions of this document, are Bluetooth SIG Confidential Information, unless they have been approved for public release by the Bluetooth SIG Board of Directors. Bluetooth SIG Members must comply with the Bluetooth SIG Confidentiality Policy and not disclose any document that is Bluetooth SIG confidential to anyone that is not a member of the Bluetooth SIG.

Abstract:

This document specifies the changes to the Core Specification required to increase the number of supported Host Controller Interface (HCI) commands and events beyond the current respective limits of 512 and 60.

Use of this specification is your acknowledgement that you agree to and will comply with the following notices and disclaimers. You are advised to seek appropriate legal, engineering, and other professional advice regarding the use, interpretation, and effect of this specification.

Use of Bluetooth specifications by members of Bluetooth SIG is governed by the membership and other related agreements between Bluetooth SIG and its members, including those agreements posted on Bluetooth SIG's website located at www.bluetooth.com. Any use of this specification by a member that is not in compliance with the applicable membership and other related agreements is prohibited and, among other things, may result in (i) termination of the applicable agreements and (ii) liability for infringement of the intellectual property rights of Bluetooth SIG and its members. This specification may provide options, because, for example, some products do not implement every portion of the specification. All content within the specification, including notes, appendices, figures, tables, message sequence charts, examples, sample data, and each option identified is intended to be within the bounds of the Scope as defined in the Bluetooth Patent/Copyright License Agreement ("PCLA"). Also, the identification of options for implementing a portion of the specification is intended to provide design flexibility without establishing, for purposes of the PCLA, that any of these options is a "technically reasonable non-infringing alternative."

Use of this specification by anyone who is not a member of Bluetooth SIG is prohibited and is an infringement of the intellectual property rights of Bluetooth SIG and its members. The furnishing of this specification does not grant any license to any intellectual property of Bluetooth SIG or its members. THIS SPECIFICATION IS PROVIDED "AS IS" AND BLUETOOTH SIG, ITS MEMBERS AND THEIR AFFILIATES MAKE NO REPRESENTATIONS OR WARRANTIES AND DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTIES OF MERCHANTABILITY, TITLE, NON-INFRINGEMENT, FITNESS FOR ANY PARTICULAR PURPOSE, OR THAT THE CONTENT OF THIS SPECIFICATION IS FREE OF ERRORS. For the avoidance of doubt, Bluetooth SIG has not made any search or investigation as to third parties that may claim rights in or to any specifications or any intellectual property that may be required to implement any specifications and it disclaims any obligation or duty to do so.

TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, BLUETOOTH SIG, ITS MEMBERS AND THEIR AFFILIATES DISCLAIM ALL LIABILITY ARISING OUT OF OR RELATING TO USE OF THIS SPECIFICATION AND ANY INFORMATION CONTAINED IN THIS SPECIFICATION, INCLUDING LOST REVENUE, PROFITS, DATA OR PROGRAMS, OR BUSINESS INTERRUPTION, OR FOR SPECIAL, INDIRECT, CONSEQUENTIAL, INCIDENTAL OR PUNITIVE DAMAGES, HOWEVER CAUSED AND REGARDLESS OF THE THEORY OF LIABILITY, AND EVEN IF BLUETOOTH SIG, ITS MEMBERS OR THEIR AFFILIATES HAVE BEEN ADVISED OF THE POSSIBILITY OF THE DAMAGES.

Products equipped with Bluetooth wireless technology ("Bluetooth Products") and their combination, operation, use, implementation, and distribution may be subject to regulatory controls under the laws and regulations of numerous countries that regulate products that use wireless non-licensed spectrum. Examples include airline regulations, telecommunications regulations, technology transfer controls, and health and safety regulations. You are solely responsible for complying with all applicable laws and regulations and for obtaining any and all required authorizations, permits, or licenses in connection with your use of this specification and development, manufacture, and distribution of Bluetooth Products. Nothing in this specification provides any information or assistance in connection with complying with applicable laws or regulations or obtaining required authorizations, permits, or licenses.

Bluetooth SIG is not required to adopt any specification or portion thereof. If this specification is not the final version adopted by Bluetooth SIG's Board of Directors, it may not be adopted. Any specification adopted by Bluetooth SIG's Board of Directors may be withdrawn, replaced, or modified at any time. Bluetooth SIG reserves the right to change or alter final specifications in accordance with its membership and operating agreements.

Copyright © 2025. All copyrights in the Bluetooth Specifications themselves are owned by Apple Inc., Ericsson AB, Intel Corporation, Google LLC, Lenovo (Singapore) Pte. Ltd., Microsoft Corporation, Nokia Corporation, and Toshiba Corporation. The Bluetooth word mark and logos are owned by Bluetooth SIG, Inc. Other third-party brands and names are the property of their respective owners.

Contents

1	Language	4
1.1	Language conventions.....	4
2	Conventions used in this specification	5
3	Changes to Source Specification	6
3.1	Changes to Volume 4, Part E, Host Controller Interface Functional Specification .	6
3.1.1	[Modified Section] 3 Overview of commands and events	6
3.1.2	[Modified Section] 6.27 Supported commands.....	6
3.1.3	[Modified Section] 7.4.2 Read Local Supported Commands command	7
3.1.4	[Modified Section] 7.8.1 LE Set Event Mask command	7
Appendix A	References	9

1 Language

1.1 Language conventions

Refer to and follow any terminology, language conventions, and interpretation sections of the Source Specification.

2 Conventions used in this specification

The formatting and color conventions described in Table 2.1 below are used in the CR to describe the specific changes and additions that are proposed to the Source Specification(s) identified on the cover page.

Text Color	Description
black	Text that is unmodified from the Source Specification. Note: The text of the Source Specification may not be black and may contain tracked changes or other colored text that are reflected as black text in this document.
red	Text that is added to the Source Specification.
red strikethrough	Text that is deleted from the Source Specification.
[green bracketed text]	Comments that explain the changes made to the Source Specification.
[...]	Indicates the section of the Source Specification that includes additional text that is not included in black text.
blue	Default color used for section numbers and headings of this document.

Table 2.1: Color key for headings, captions, and body text

3 Changes to Source Specification

This Section sets forth the specific changes and additions, using the formatting and color conventions described in Section 2, that are proposed to the Source Specification.

3.1 Changes to Volume 4, Part E, Host Controller Interface Functional Specification

3.1.1 [Modified Section] 3 Overview of commands and events

[Modify rows of this table as shown.]

Name	Vers.	Summary Description	BR/EDR	LE
LE Set Event Mask command	4.0 TBD	The HCI_LE_Set_Event_Mask command is used to control which events are generated by the HCI for the Host.	E	[v1] M [v2] C.X+0
Read Local Supported Commands command	1.2 TBD	The HCI_Read_Local_Supported_Commands command requests a list of the supported HCI commands for the local device.	[v1] M [v2] C.X+1	[v1] M [v2] C.X+1

[Add the following conditions to the list underneath the table, in position of assigned number.]

C.X+0: Mandatory if any event assigned a bit number of 64 or above is supported, otherwise optional.

C.X+1: Mandatory if any command listed in octet 64 or above is supported, otherwise optional.

3.1.2 [Modified Section] 6.27 Supported commands

[Modify this section as shown.]

The Supported_Commands configuration parameter lists which HCI commands the local Controller supports.

The Supported_Commands is a ~~64~~251 octet bit field. If a bit is set to 1, then this command is supported.

Supported_Commands:

Size: ~~64~~251 octets

[Amend or add rows of the table, in assigned order of octet and bit, as shown. Leave the rest of the table unchanged.]

Octet	Bit	Command Supported
25	0	HCI_LE_Set_Event_Mask [v1]

TBD	TBD	HCI_LE_Set_Event_Mask [v2]
TBD	TBD	HCI_Read_Local_Supported_Commands [v2]

[Note to reviewers: HCI_Read_Local_Supported_Commands [v1] does not appear in the table because the table is only accessible if the command is supported. In any case, the command is mandatory to support.]

3.1.3 [Modified Section] 7.4.2 Read Local Supported Commands command

[Modify the introductory table as shown.]

Command	OCF	Command Parameters	Return Parameters
HCI_Read_Local_Supported_Commands [v2]	TBD	<i>none</i>	Status, Supported_Commands
HCI_Read_Local_Supported_Commands [v1]	0x0002	<i>none</i>	Status, Supported_Commands

[Modify the Supported_Commands parameter of the Return parameters subsection as shown.]

Supported_Commands [v1]: Size: 64 octets

Supported_Commands [v2]: Size: 251 octets

[Table is unchanged.]

The [v1] command returns octets 0 to 63 of the supported commands; the [v2] command returns all octets.

3.1.4 [Modified Section] 7.8.1 LE Set Event Mask command

[Modify the introductory table as shown.]

Command	OCF	Command Parameters	Return Parameters
HCI_LE_Set_Event_Mask [v2]	TBD	LE_Event_Mask	Status
HCI_LE_Set_Event_Mask [v1]	0x0001	LE_Event_Mask	Status

[Modify the Command parameters subsection as shown.]

Command parameters:

LE_Event_Mask [v1]: Size: 8 octets

LE_Event_Mask [v2]:

Size: 255 octets

[Table is unchanged.]

The value with all bits set to 0 indicates that no events are specified. The default is for just bits 0 to 4 (the value ~~0x0000-0000-0000-001F~~) to be set.

All bits not listed in this table are reserved for future use.

The [v1] command sets bits 0 to 63 of the event mask and leaves bits 64 and above unchanged. The [v2] command sets all the bits of the event mask.

Appendix A References

No references.