

# Emergency Profile (EMP)

## **Bluetooth®** Implementation Conformance Statement (ICS) Proforma

---

- **Revision:** EMP.ICS.p4
- **Revision Date:** 2026-02-17
- **Prepared By:** PUID WG
- **Published during TCRL:** TCRL.pkg102



This document, regardless of its title or content, is not a Bluetooth Specification as defined in the Bluetooth Patent/Copyright License Agreement (“PCLA”) and Bluetooth Trademark License Agreement. Use of this document by members of Bluetooth SIG is governed by the membership and other related agreements between Bluetooth SIG Inc. (“Bluetooth SIG”) and its members, including the PCLA and other agreements posted on Bluetooth SIG’s website located at [www.bluetooth.com](http://www.bluetooth.com).

THIS DOCUMENT IS PROVIDED “AS IS” AND BLUETOOTH SIG, ITS MEMBERS, AND THEIR AFFILIATES MAKE NO REPRESENTATIONS OR WARRANTIES AND DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, TITLE, NON-INFRINGEMENT, FITNESS FOR ANY PARTICULAR PURPOSE, THAT THE CONTENT OF THIS DOCUMENT IS FREE OF ERRORS.

TO THE EXTENT NOT PROHIBITED BY LAW, BLUETOOTH SIG, ITS MEMBERS, AND THEIR AFFILIATES DISCLAIM ALL LIABILITY ARISING OUT OF OR RELATING TO USE OF THIS DOCUMENT AND ANY INFORMATION CONTAINED IN THIS DOCUMENT, INCLUDING LOST REVENUE, PROFITS, DATA OR PROGRAMS, OR BUSINESS INTERRUPTION, OR FOR SPECIAL, INDIRECT, CONSEQUENTIAL, INCIDENTAL OR PUNITIVE DAMAGES, HOWEVER CAUSED AND REGARDLESS OF THE THEORY OF LIABILITY, AND EVEN IF BLUETOOTH SIG, ITS MEMBERS, OR THEIR AFFILIATES HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

This document is proprietary to Bluetooth SIG. This document may contain or cover subject matter that is intellectual property of Bluetooth SIG and its members. The furnishing of this document does not grant any license to any intellectual property of Bluetooth SIG or its members.

This document is subject to change without notice.

Copyright © 2018–2026 by Bluetooth SIG, Inc. The Bluetooth word mark and logos are owned by Bluetooth SIG, Inc. Other third-party brands and names are the property of their respective owners.



# Contents

- 1 General principles ..... 4**
  - 1.1 Implementation Under Test (IUT) identification ..... 4
  - 1.2 Enforcement of inter-layer dependencies ..... 4
- 2 ICS declarations..... 5**
  - 2.1 Versions ..... 5
  - 2.2 Roles ..... 5
  - 2.3 Transports..... 5
  - 2.4 Emergency Emitter role ..... 5
    - 2.4.1 Services (Emergency Emitter) ..... 5
    - 2.4.2 GAP requirements (Emergency Emitter)..... 6
  - 2.5 Emergency Inhibitor role..... 6
    - 2.5.1 GAP requirements (Emergency Inhibitor) ..... 6
  - 2.6 Emergency Locator role..... 7
    - 2.6.1 Services (Emergency Locator)..... 7
    - 2.6.2 GAP requirements (Emergency Locator) ..... 7
- 3 References ..... 8**
- 4 Revision history and acknowledgments ..... 9**



# 1 General principles

## 1.1 Implementation Under Test (IUT) identification

Using the Bluetooth SIG qualification tool, the implementer is expected to declare details about what will be implemented.

## 1.2 Enforcement of inter-layer dependencies

This ICS includes one or more tables with inter-layer dependencies (ILDs). ILDs are used for specification requirements that are dependent on other supporting specifications. ILDs can refer to an individual ICS item in a separate layer (individual ILD), or it can refer to the full layer (full-layer ILD).

ILDs residing in an X2Core layer will be enforced from the Bluetooth SIG qualification tool in the following conditions, depending on where the referred ILD is residing:

Referred ILD resides in	Individual ILD	Full-layer ILD
Controller layer	Core-Complete configuration, or Referred layer is supported	N/A
Lower HCI layer	HCI is supported	N/A
Upper HCI layer	Core-Host configuration, or UHCI is supported	N/A
Host layer	Core-Host configuration, or Core-Complete configuration, or Referred layer is supported	N/A
X2Core layer	Core-Host configuration, or Core-Complete configuration, or Referred layer is supported	Core-Host configuration, or Core-Complete configuration

Table 1.1: Enforcement of an ILD within the Bluetooth SIG qualification tool

## 2 ICS declarations

### 2.1 Versions

Table 0: X.Y Versions

Item	Version	Reference	Status
1	EMP v1.0	[1]	M

### 2.2 Roles

Table 1: Role Requirements

Item	Role	Reference	Status
1	Emergency Emitter	[1] 2.1	C.1
2	Emergency Inhibitor	[1] 2.1	C.1
3	Emergency Locator	[1] 2.1	C.1

C.1: Mandatory to support at least one.

### 2.3 Transports

Table 2: Transport Requirements

Item	Transport	Reference	Status
1	Profile supported over BR/EDR	[1] 2.5	C.1
2	Profile supported over LE	[1] 2.5	C.2, C.3

C.1: Excluded for this Profile.

C.2: Excluded for this Profile IF CORE 41/1 "BR/EDR Core Configuration" OR CORE 40/1 "Core-Controller".

C.3: Mandatory for this Profile.

### 2.4 Emergency Emitter role

#### 2.4.1 Services (Emergency Emitter)

Table 3: Services (Emergency Emitter)

Prerequisite: EMP 1/1 "Emergency Emitter"

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Emergency Configuration Service	[1] 3	M	[2] EMCS 3/1
2	Emergency Advertising Data	[1] 3.1	M	N/A
3	Reconnecting to Inhibitor before alerting	[1] 3.1	M	N/A
4	Reconnecting to Inhibitor during alerting	[1] 3.1	C.1	N/A



Item	Capability	Reference	Status	Inter-Layer Dependency
5	Emitter not allowing reconnection during alerting	[1] 3.1	C.1	N/A

C.1: Mandatory to support one and only one.

## 2.4.2 GAP requirements (Emergency Emitter)

**Table 4: GAP Requirements (Emergency Emitter)**

*Prerequisite: EMP 1/1 "Emergency Emitter" AND EMP 2/2 "Profile supported over LE"*

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Broadcaster	[1] 2.1	M	[3] GAP 5/1
2	Peripheral	[1] 2.4	M	[3] GAP 5/3
3	Unauthenticated Pairing (LE security mode 1 level 2)	[1] 7	C.1	[3] GAP 25/8
4	Authenticated Pairing (LE security mode 1 level 3)	[1] 7	C.1	[3] GAP 25/7
5	LE security mode 1	[1] 7	M	[3] GAP 25/1
6	Service Data	[1] 3.1.1	M	[3] GAP 20a/10
7	Service UUID	[1] 3.1.2	M	[3] GAP 20a/1

C.1: Mandatory to support at least one.

## 2.5 Emergency Inhibitor role

### 2.5.1 GAP requirements (Emergency Inhibitor)

**Table 5: GAP Requirements (Emergency Inhibitor)**

*Prerequisite: EMP 1/2 "Emergency Inhibitor"*

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Central	[1] 2.4	M	[3] GAP 5/4
2	Unauthenticated Pairing (LE security mode 1 level 2)	[1] 7	M	[3] GAP 35/8
3	Authenticated Pairing (LE security mode 1 level 3)	[1] 7	M	[3] GAP 35/7
4	LE security mode 1	[1] 7	M	[3] GAP 35/1



## 2.6 Emergency Locator role

### 2.6.1 Services (Emergency Locator)

**Table 6: Services (Emergency Locator)**

*Prerequisite: EMP 1/3 "Emergency Locator"*

Item	Capability	Reference	Status
1	Scanning for Emergency ID	[1] 5	M

### 2.6.2 GAP requirements (Emergency Locator)

**Table 7: GAP Requirements (Emergency Locator)**

*Prerequisite: EMP 1/3 "Emergency Locator"*

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Observer	[1] 2.4	M	[3] GAP 5/2

## 3 References

---

- [1] Emergency Profile Specification
- [2] ICS Proforma for Emergency Configuration Service (EMCS)
- [3] ICS Proforma for Generic Access Profile (GAP)

## 4 Revision history and acknowledgments

### Revision History

Publication Number	Revision Number	Date	Comments
0	1.0.0	2019-07-02	Emergency Profile adopted by the Board of Directors. Prepared for publication.
	p1r00-r01	2022-10-14 – 2022-11-04	TSE 19292 (rating 3): Corrected GAP table references. Added missing GAP ILD to LE security mode 1. Added missing GAP ILD for Service Data and Service UUID. Updated to align with current ICS conventions/template. Removed Support columns. Updated references. Added a Publication Number column to the Revision History. Revised the document numbering convention, setting the last release publication of 1.0.0 as p0. Performed additional template-related formatting fixes. Replaced the Bluetooth logo in the footer and updated the copyright page to align with v2 of the DNMD.
1	p1	2023-02-07	Approved by BTI on 2022-12-28. Prepared for TCRL 2022-2 publication.
	p2r00-r01	2025-05-01 – 2025-05-06	TSE 27350 (rating 1): In Table 2, updated the Status value for EMP 2/2 and added conditions C.2 and C.3. Deleted draft revision history comments prior to p0. Incorporated editorials to align the document with the latest ICS template, including updates to Section 1 and the addition of a section heading for the ICS declarations section.
2	p2	2025-07-08	Approved by BTI on 2025-06-15. Prepared for TCRL pkg100 publication.
	p3r00	2025-08-22	TSE 28077 (rating 1): Updated the ILD column for Items 4/1, 4/2, 5/1, and 7/1 to delete references to GAP Table 38.
3	p3	2025-11-04	Approved by BTI on 2025-10-02. Prepared for TCRL pkg101 publication.
	p4r00	2025-12-04 – 2025-12-12	TSE 28169 (rating 1): Updated the conditions in the transport table to make sure the layer is excluded when the design is an implementation of the Core-Controller Configuration by adding "OR CORE 40/1 "Core-Controller"" to an already excluded transport based on Core Configuration support.
4	p4	2026-02-17	Approved by BTI on 2026-01-21. Prepared for TCRL pkg102 publication.

### Acknowledgments

Name	Company
David Chapman	Bluetooth SIG, Inc.
Alan Ewing	Bluetooth SIG, Inc.
Frank Berntsen	Nordic Semiconductor

