

Generic Access Profile (GAP)

Bluetooth® Implementation Conformance Statement (ICS) Proforma

- **Revision:** GAP.ICS.p46
- **Revision Date:** 2026-05-05
- **Prepared By:** BTI
- **Published during TCRL:** TCRL.pkg103



This document, regardless of its title or content, is not a Bluetooth Specification as defined in the Bluetooth Patent/Copyright License Agreement (“PCLA”) and Bluetooth Trademark License Agreement. Use of this document by members of Bluetooth SIG is governed by the membership and other related agreements between Bluetooth SIG Inc. (“Bluetooth SIG”) and its members, including the PCLA and other agreements posted on Bluetooth SIG’s website located at www.bluetooth.com.

THIS DOCUMENT IS PROVIDED “AS IS” AND BLUETOOTH SIG, ITS MEMBERS, AND THEIR AFFILIATES MAKE NO REPRESENTATIONS OR WARRANTIES AND DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, TITLE, NON-INFRINGEMENT, FITNESS FOR ANY PARTICULAR PURPOSE, THAT THE CONTENT OF THIS DOCUMENT IS FREE OF ERRORS.

TO THE EXTENT NOT PROHIBITED BY LAW, BLUETOOTH SIG, ITS MEMBERS, AND THEIR AFFILIATES DISCLAIM ALL LIABILITY ARISING OUT OF OR RELATING TO USE OF THIS DOCUMENT AND ANY INFORMATION CONTAINED IN THIS DOCUMENT, INCLUDING LOST REVENUE, PROFITS, DATA OR PROGRAMS, OR BUSINESS INTERRUPTION, OR FOR SPECIAL, INDIRECT, CONSEQUENTIAL, INCIDENTAL OR PUNITIVE DAMAGES, HOWEVER CAUSED AND REGARDLESS OF THE THEORY OF LIABILITY, AND EVEN IF BLUETOOTH SIG, ITS MEMBERS, OR THEIR AFFILIATES HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

This document is proprietary to Bluetooth SIG. This document may contain or cover subject matter that is intellectual property of Bluetooth SIG and its members. The furnishing of this document does not grant any license to any intellectual property of Bluetooth SIG or its members.

This document is subject to change without notice.

Copyright © 2004–2026 by Bluetooth SIG, Inc. The Bluetooth word mark and logos are owned by Bluetooth SIG, Inc. Other third-party brands and names are the property of their respective owners.

Contents

1	General principles	5
1.1	Implementation Under Test (IUT) identification	5
1.2	Auto-fill tables	5
1.3	Enforcement of inter-layer dependencies	5
2	ICS declarations.....	6
2.1	Host configuration	6
2.2	BR/EDR Capability Statement	6
2.2.1	Modes	6
2.2.2	Security Aspects	7
2.2.3	Idle Mode Procedures	8
2.2.4	Establishment Procedures	9
2.2.5	L2CAP requirements.....	9
2.2.6	Generic Access Profile Characteristics	9
2.2.7	LMP requirements.....	10
2.2.8	BB requirements	10
2.3	LE Capability Statement	11
2.3.1	Broadcaster	11
2.3.1.1	Physical Layer	11
2.3.1.2	Link Layer Features	11
2.3.1.3	Connection Modes and Procedures	12
2.3.1.4	Broadcasting and Observing	13
2.3.1.5	Privacy Feature	13
2.3.1.6	Periodic Advertising Modes and Procedures	14
2.3.1.7	Security Aspects	14
2.3.2	Observer	15
2.3.2.1	Physical Layer	15
2.3.2.2	Link Layer Features	15
2.3.2.3	Connection Modes and Procedures	16
2.3.2.4	Broadcasting and Observing	17
2.3.2.5	Privacy Feature	17
2.3.2.6	Periodic Advertising Modes and Procedures	18
2.3.2.7	Security Aspects	18
2.3.3	Peripheral	19
2.3.3.1	Physical Layer	19
2.3.3.2	Link Layer Features	19
2.3.3.3	Discovery Modes and Procedures	21
2.3.3.4	Connection Modes and Procedures	22
2.3.3.5	Bonding Modes and Procedures	22
2.3.3.6	Security Aspects	23
2.3.3.7	Privacy Feature	25
2.3.3.8	Generic Access Profile Characteristics.....	25
2.3.3.9	Periodic Advertising Modes and Procedures	26
2.3.3.10	SM requirements	27
2.3.3.11	L2CAP requirements	28
2.3.4	Central	28
2.3.4.1	Physical Layer	28

2.3.4.2	Link Layer Features	28
2.3.4.3	Control Procedures	30
2.3.4.4	Discovery Modes and Procedures	30
2.3.4.5	Connection Modes and Procedures	31
2.3.4.6	Bonding Modes and Procedures	32
2.3.4.7	Security Aspects	32
2.3.4.8	Privacy Feature	34
2.3.4.9	Generic Access Profile Characteristics	35
2.3.4.10	Periodic Advertising Modes and Procedures	35
2.3.4.11	SM requirements	36
2.3.4.12	L2CAP requirements	37
2.4	BR/EDR/LE Capability Statement	37
2.4.1	Central	37
2.4.1.1	Security Aspects	37
2.4.1.2	Simultaneous Transports	38
2.4.2	Peripheral	38
2.4.2.1	Security Aspects	38
2.4.2.2	Simultaneous Transports	38
3	Bridge mapping (informational)	39
4	References	41
5	Revision history and acknowledgments	42

1 General principles

1.1 Implementation Under Test (IUT) identification

Using the Bluetooth SIG qualification tool, the implementer is expected to declare details about what will be implemented.

1.2 Auto-fill tables

This ICS includes one or more tables that are defined as auto-fill tables. Auto-fill tables are defined to allow for less-complex conditions within other tables. Auto-fill tables are distinguished from regular ICS tables by the addition of “(auto-fill)” after the Table number, prior to the colon “:”.

An auto-fill table is automatically populated based on selected capabilities elsewhere in the ICS. The populated settings in the auto-fill table are not user editable.

1.3 Enforcement of inter-layer dependencies

This ICS includes one or more tables with inter-layer dependencies (ILDs). ILDs are used for specification requirements that are dependent on other supporting specifications. ILDs can refer to an individual ICS item in a separate layer (individual ILD), or it can refer to the full layer (full-layer ILD).

ILDs residing in an X2Core layer will be enforced from the Bluetooth SIG qualification tool in the following conditions, depending on where the referred ILD is residing:

Referred ILD resides in	Individual ILD	Full-layer ILD
Controller layer	Core-Complete configuration, or Referred layer is supported	N/A
Lower HCI layer	HCI is supported	N/A
Upper HCI layer	Core-Host configuration, or UHCI is supported	N/A
Host layer	Core-Host configuration, or Core-Complete configuration, or Referred layer is supported	N/A
X2Core layer	Core-Host configuration, or Core-Complete configuration, or Referred layer is supported	Core-Host configuration, or Core-Complete configuration

Table 1.1: Enforcement of an ILD within the Bluetooth SIG qualification tool

2 ICS declarations

2.1 Host configuration

Table 0: No longer used

Table 0a: No longer used

Table 0b: GAP Host Configuration

Item	Capability	Reference	Status
1	GAP BR/EDR Host	[1] 1.1	C.1, C.3
2	GAP LE Host	[2] 1.1	C.2, C.3

C.1: Mandatory IF CORE 20/2 “BR/EDR Host Layers”, otherwise Optional.

C.2: Mandatory IF CORE 20/4 “LE Host Layers”, otherwise Optional.

C.3: Mandatory to support at least one.

Note: A GAP BR/EDR/LE Host will need to select GAP 0b/1 and GAP 0b/2.

2.2 BR/EDR Capability Statement

2.2.1 Modes

Table 1: Modes

Prerequisite: GAP 0b/1 “GAP BR/EDR Host”

Item	Capability	Reference	Status
1	Non-discoverable mode	[1] 4.1.1	C.1
2	Limited discoverable mode	[1] 4.1.2	O
3	General discoverable mode	[1] 4.1.3	O
4	Non-connectable mode	[1] 4.2.1	O
5	Connectable mode	[1] 4.2.2	M
6	Non-bondable mode	[1] 4.3.1	C.4
7	Bondable mode	[1] 4.3.2	C.2
8	No longer used	N/A	N/A
9	Synchronizable mode	[4] 4.4.2	O

C.1: Mandatory IF GAP 1/2 “Limited discoverable mode” OR NOT GAP 1/3 “General discoverable mode”, otherwise Optional.

C.2: Mandatory IF GAP 3/5 “Initiation of general bonding”, otherwise Optional.

C.3: No longer used.

C.4: Optional IF GAP 1/7 “Bondable mode”, otherwise Mandatory.

2.2.2 Security Aspects

Table 2: Security Aspects

Prerequisite: GAP 0b/1 “GAP BR/EDR Host”

Item	Capability	Reference	Status
1	Authentication procedure	[1] 5.1	C.1
2	Support of LMP-Authentication	[1] 5.1	M
3	Initiate LMP-Authentication	[1] 5.1	C.5
4	Security mode 1	[1] 5.2.1.1	C.7
5	Security mode 2	[1] 5.2.1.2	O
6	Security mode 3	[1] 5.2.1.3	C.7
7	Security mode 4	[1] 5.2.2	M
7a	Security mode 4, level 4	[4] 5.2.2.8	C.9
7b	Security mode 4, level 3	[4] 5.2.2.8	C.9
7c	Security mode 4, level 2	[4] 5.2.2.8	C.9
7d	Security mode 4, level 1	[4] 5.2.2.8	C.9
8	Authenticated link key	[1] 5.2.2	C.6
9	Unauthenticated link key	[1] 5.2.2	C.6
10	Security Optional	[1] 5.2.2	C.6
11	Secure Connections Only Mode	[12] 5.2.2, 14.3	C.8
12	56-bit minimum encryption key size	[9] 5.2.2.8	C.10
13	128-bit encryption key size capable	[4] 5.2.2.8	C.11
13a	128-bit encryption key size capable, Security mode 4, level 4	[4] 5.2.2.8	C.12
13b	128-bit encryption key size capable, Security mode 4, level 3	[4] 5.2.2.8	C.13
13c	128-bit encryption key size capable, Security mode 4, level 2	[4] 5.2.2.8	C.14
13d	128-bit encryption key size capable, Security mode 4, level 1	[4] 5.2.2.8	C.15
14	Out-of-Band	[4] 5.2.2.7	O

C.1: Mandatory IF GAP 2/5 “Security mode 2” OR GAP 2/6 “Security mode 3”, otherwise Optional.

C.2–C.4: No longer used.

C.5: Mandatory IF GAP 2/5 “Security mode 2” OR GAP 2/6 “Security mode 3” OR GAP 2/7 “Security mode 4”, otherwise Optional.

C.6: Mandatory to support at least one IF GAP 2/7 “Security mode 4”, otherwise Excluded.

C.7: Excluded. See Note 2.

C.8: Mandatory IF GAP 25/10 “Secure Connections Only mode” OR GAP 35/10 “Secure Connections Only mode”, otherwise Optional IF GAP 2/7a “Security mode 4, level 4”, otherwise Excluded.

C.9: Optional IF GAP 2/7 “Security mode 4”, otherwise Excluded.

C.10: Optional IF GAP 2/7d “Security mode 4, level 1” OR GAP 2/7c “Security mode 4, level 2” OR GAP 2/7b “Security mode 4, level 3”, otherwise Excluded.

- C.11: Mandatory IF GAP 2/13a “128-bit encryption key size capable, Security mode 4, level 4” OR GAP 2/13b “128-bit encryption key size capable, Security mode 4, level 3” OR GAP 2/13c “128-bit encryption key size capable, Security mode 4, level 2” OR GAP 2/13d “128-bit encryption key size capable, Security mode 4, level 1”, otherwise Excluded.
- C.12: Mandatory IF GAP 2/7a “Security mode 4, level 4”, otherwise Excluded.
- C.13: Optional IF GAP 2/7b “Security mode 4, level 3”, otherwise Excluded.
- C.14: Optional IF GAP 2/7c “Security mode 4, level 2”, otherwise Excluded.
- C.15: Optional IF GAP 2/7d “Security mode 4, level 1”, otherwise Excluded.

Note 1: The “Authentication Procedure” in item GAP 2/1 is the one described in Fig. 5.1 in the GAP Specification and not the LMP-Authentication.

Note 2: A Core 2.1 or later device is required to support security mode 4. Security mode 2 is used only for backward compatibility purposes with Core 2.0 and earlier devices. Security mode 1 and security mode 3 are excluded for Core 2.1 or later devices.

Table 2a (auto-fill): Security Levels Satisfaction

Prerequisite: GAP 0b/1 “GAP BR/EDR Host”

Item	Capability	Reference	Status
1	Satisfies Security mode 4, level 1	[4] 5.2.2.8	C.1
2	Satisfies Security mode 4, level 2	[4] 5.2.2.8	C.2
3	Satisfies Security mode 4, level 3	[4] 5.2.2.8	C.3
4	Satisfies Security mode 4, level 4	[4] 5.2.2.8	C.4

- C.1: Mandatory IF GAP 2/7a “Security mode 4, level 4” OR GAP 2/7b “Security mode 4, level 3” OR GAP 2/7c “Security mode 4, level 2” OR GAP 2/7d “Security mode 4, level 1”, otherwise Excluded.
- C.2: Mandatory IF GAP 2/7a “Security mode 4, level 4” OR GAP 2/7b “Security mode 4, level 3” OR GAP 2/7c “Security mode 4, level 2”, otherwise Excluded.
- C.3: Mandatory IF GAP 2/7a “Security mode 4, level 4” OR GAP 2/7b “Security mode 4, level 3”, otherwise Excluded.
- C.4: Mandatory IF GAP 2/7a “Security mode 4, level 4”, otherwise Excluded.

2.2.3 Idle Mode Procedures

Table 3: Idle Mode Procedures

Prerequisite: GAP 0b/1 “GAP BR/EDR Host”

Item	Capability	Reference	Status
1	Initiation of general inquiry	[1] 6.1	C.1
2	Initiation of limited inquiry	[1] 6.2	C.1
3	Initiation of name discovery	[1] 6.3	O
4	Initiation of device discovery	[1] 6.4	O
5	Initiation of general bonding	[1] 6.5	O
6	Initiation of dedicated bonding	[1] 6.5	O

- C.1: Mandatory to support at least one IF GAP 3/5 “Initiation of general bonding”, otherwise Optional.

2.2.4 Establishment Procedures

Table 4: Establishment Procedures

Prerequisite: GAP 0b/1 “GAP BR/EDR Host”

Item	Capability	Reference	Status
1	Link Establishment as initiator	[1] 7.1	M
2	Link Establishment as acceptor	[1] 7.1	M
3	Channel Establishment as initiator	[1] 7.2	O
4	Channel Establishment as acceptor	[1] 7.2	M
5	Connection Establishment as initiator	[1] 7.3	O
6	Connection Establishment as acceptor	[1] 7.3	O
7	Synchronization Establishment as receiver	[4] 7.5	O

Table 4c: Procedures

Prerequisite: GAP 0b/1 “GAP BR/EDR Host”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Synchronization Train	[1] 7.5	C.1	[18] LMP 30/130

C.1: Mandatory IF GAP 1/9 “Synchronizable mode”, otherwise not defined.

2.2.5 L2CAP requirements

Table 4a (auto-fill): L2CAP Requirements

Prerequisite: GAP 0b/1 “GAP BR/EDR Host”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Detect insufficient authentication	[1] 5.1	C.1	[14] L2CAP 5/1

C.1: Mandatory IF GAP 2/1 “Authentication procedure”, otherwise not defined.

2.2.6 Generic Access Profile Characteristics

Table 4b: GAP Characteristics

Prerequisite: GATT 1a/4 “GATT Server over BR/EDR”

Item	Capability	Reference	Status
1	Device Name	[2] 12.1	M
2	Appearance	[2] 12.2	M
3	Peripheral Preferred Connection Parameters	[2] 12.3	C.4
4	Central Address Resolution	[5] 12.4	C.5
5	Resolvable Private Address Only	[2] 12.5	C.6
6	Encrypted Data Key Material	[12] 12.6	C.7
7	Encrypted Data Key Material Indications	[12] 12.6	C.1

Item	Capability	Reference	Status
8	Writable Device Name	[2] 12.1	C.2
9	Writable Appearance	[2] 12.2	C.3

- C.1: Mandatory IF GAP 27/10a “Encrypted Data Key Material Indications”, otherwise Optional IF GAP 4b/6 “Encrypted Data Key Material”, otherwise Excluded.
- C.2: Mandatory IF GAP 27/6 “Writable Device Name” OR GAP 37/6 “Writable Device Name”, otherwise Optional.
- C.3: Mandatory IF GAP 27/7 “Writable Appearance” OR GAP 37/7 “Writable Appearance”, otherwise Optional.
- C.4: Mandatory IF GAP 27/5 “Peripheral Preferred Connection Parameters”, otherwise Optional.
- C.5: Mandatory IF GAP 27/9 “Central Address Resolution” OR GAP 37/3 “Central Address Resolution”, otherwise Optional.
- C.6: Mandatory IF GAP 27/12 “Resolvable Private Address Only” OR GAP 37/5 “Resolvable Private Address Only”, otherwise Optional.
- C.7: Mandatory IF GAP 27/10 “Encrypted Data Key Material”, otherwise Optional.

2.2.7 LMP requirements

Table 4d (auto-fill): LMP Requirements

Prerequisite: GAP 0b/1 “GAP BR/EDR Host”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Secure Connections	[12] 5.2.2, 14.3	C.1	[18] LMP 2/26

- C.1: Mandatory IF GAP 2/11 “Secure Connections Only Mode”, otherwise not defined.

2.2.8 BB requirements

Table 4e (auto-fill): BB Requirements

Prerequisite: GAP 0b/1 “GAP BR/EDR Host”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Connectionless Peripheral Broadcast Transmitter	[4] 4.4.1, 4.4.2	C.1	[19] BB 3a/1
2	Connectionless Peripheral Broadcast Receiver	[4] 7.5	C.2	[19] BB 3a/2
3	Extended Inquiry Response	[1] 4.1.3	C.3	[19] BB 10/7

- C.1: Mandatory IF GAP 1/9 “Synchronizable mode”, otherwise not defined.
- C.2: Mandatory IF GAP 4/7 “Synchronization Establishment as receiver”, otherwise not defined.
- C.3: Mandatory IF GAP 1/3 “General discoverable mode”, otherwise not defined.

2.3 LE Capability Statement

Table 5: LE Roles

Prerequisite: GAP 0b/2 “GAP LE Host”

Item	Capability	Reference	Status
1	Broadcaster	[2] 2.2.2	C.1
2	Observer	[2] 2.2.2	C.1
3	Peripheral	[2] 2.2.2	C.1
4	Central	[2] 2.2.2	C.1

C.1: Mandatory to support at least one.

2.3.1 Broadcaster

2.3.1.1 Physical Layer

Table 6: Broadcaster Physical Layer

Prerequisite: GAP 5/1 “Broadcaster”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	LE Transmitter	[2] 2.2.2	M	[20] RFPHY 0/1
2	LE Receiver	[2] 2.2.2	O	[20] RFPHY 0/2
3	LE 2M PHY	[2] 2.2.2	O	[20] RFPHY 1/4

2.3.1.2 Link Layer Features

2.3.1.2.1 Link Layer States

Table 7: Broadcaster Link Layer States

Prerequisite: GAP 5/1 “Broadcaster”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Standby State	[2] 2.2.2, 2.2.2.1	M	N/A
2	Advertising State	[2] 2.2.2, 2.2.2.1	M	[15] LL 1/1
3	Isochronous Broadcasting State	[10] 2.2.2, 2.2.2.1	C.1	[15] LL 1/6
3a	Isochronous Broadcaster	[10] 2.2.2, 2.2.2.1	C.2	[15] LL 9/33
3b	Encrypted Broadcast Isochronous Stream	[10] 2.2.2, 2.2.2.1	C.3	[15] LL 12/1
3c	Unencrypted Broadcast Isochronous Stream	[10] 2.2.2, 2.2.2.1	C.4	[15] LL 12/2

C.1: Optional IF CORE 2a/52 “Host Core v5.2 or later”, otherwise not defined.

C.2: Optional IF GAP 7/3 “Isochronous Broadcasting State”, otherwise not defined.

C.3: Mandatory IF GAP 7/3a “Isochronous Broadcaster” AND GAP 8b/1 “LE Encryption”, otherwise not defined.

C.4: Mandatory IF GAP 7/3a “Isochronous Broadcaster”, otherwise not defined.



2.3.1.2.2 Advertising Event Types

Table 8: Broadcaster Link Layer Advertising Event Types

Prerequisite: GAP 5/1 “Broadcaster”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Non-connectable and non-scannable undirected events	[2] 2.2.2	M	[15] LL 3/1
2	Scannable undirected events	[2] 2.2.2	O	[15] LL 3/5
3	Non-connectable and non-scannable directed events	[7] 2.2.2	C.1	[15] LL 3/1a
4	Scannable directed events	[7] 2.2.2	C.1	[15] LL 3/5a
5	LE Extended Advertising	[7] 2.2.2	O	[15] LL 9/41
6	LE Periodic Advertising	[7] 2.2.2	C.1	[15] LL 9/42

C.1: Optional IF GAP 8/5 “LE Extended Advertising”, otherwise not defined.

2.3.1.2.3 Control Procedures

Table 8b: Broadcaster Link Layer Control Procedures

Prerequisite: GAP 5/1 “Broadcaster”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	LE Encryption	[4] 2.2.2	O	[15] LL 9/1

2.3.1.3 Connection Modes and Procedures

Table 8a: Broadcaster Link Layer Advertising Data Types

Prerequisite: GAP 5/1 “Broadcaster”

Item	Capability	Reference	Status
1	Service UUID	[3] 1.1	O
2	Local Name	[3] 1.2	O
3	Flags	[3] 1.3	O
4	Manufacturer Specific Data	[3] 1.4	O
5	TX Power Level	[3] 1.5	O
6	Security Manager OOB	[3] 1.7	O
7	Security Manager TK Value	[3] 1.8	O
8	Peripheral Connection Interval Range	[3] 1.9	O
9	Service Solicitation	[3] 1.10	O
10	Service Data	[3] 1.11	O
11	Appearance	[3] 1.12	O
12	Public Target Address	[3] 1.13	O
13	Random Target Address	[3] 1.14	O
14	Advertising Interval	[3] 1.15	O
14a	Advertising Interval – Long	[3] 1.15	O

Item	Capability	Reference	Status
15	LE Bluetooth Device Address	[3] 1.16	O
16	LE Role	[3] 1.17	O
17	Uniform Resource Identifier	[3] 1.18	O
18	LE Supported features	[3] 1.19	O
19	Encrypted Data	[3] 1.23	O
20	Periodic Advertising Response Timing	[3] 1.24	O

Table 9: Broadcaster Connection Modes and Procedures*Prerequisite: GAP 5/1 “Broadcaster”*

Item	Capability	Reference	Status
1	Non-connectable mode	[2] 9.3.2	M

2.3.1.4 Broadcasting and Observing

Table 10: Broadcaster Broadcasting and Observing Features*Prerequisite: GAP 5/1 “Broadcaster”*

Item	Capability	Reference	Status
1	Broadcast mode	[2] 9.1.1	M
2	Broadcast Isochronous Synchronizability mode	[10] 9.6.1	C.1
3	Broadcast Isochronous Broadcasting mode	[10] 9.6.2	C.2
4	Broadcast Isochronous Terminate procedure	[10] 9.6.5	C.1
5	Broadcast Isochronous Channel Map Update procedure	[10] 9.6.4	C.1

C.1: Mandatory IF GAP 10/3 “Broadcast Isochronous Broadcasting mode”, otherwise Excluded.

C.2: Optional IF CORE 2a/52 “Host Core v5.2 or later”, otherwise Excluded.

2.3.1.5 Privacy Feature

Table 11: Broadcaster Privacy Feature*Prerequisite: GAP 5/1 “Broadcaster”*

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Privacy feature	[5] 10.7	O	N/A
2	Resolvable private address generation procedure	[5] 10.8.2.2 [6] 1.3.2.2	C.1	N/A
3	Non-resolvable private address generation procedure	[5] 10.8.2.1 [6] 1.3.2.2	C.2	N/A
4	Resolvable private address resolution procedure	[5] 10.8.2.3 [6] 1.3.2.2	O	N/A

Item	Capability	Reference	Status	Inter-Layer Dependency
5	Controller-based privacy	[5] 10.7	O	N/A
6	LL Privacy	[5] 10.7 [6] 6	C.3	[15] LL 9/13

C.1: Mandatory IF GAP 11/1 “Privacy feature” AND NOT GAP 11/3 “Non-resolvable private address generation procedure”, otherwise Optional.

C.2: Mandatory IF GAP 11/1 “Privacy feature” AND NOT GAP 11/2 “Resolvable private address generation procedure”, otherwise Optional.

C.3: Mandatory IF GAP 11/1 “Privacy feature”, otherwise not defined.

2.3.1.6 Periodic Advertising Modes and Procedures

Table 11a: Periodic Advertising Modes and Procedures

Prerequisite: GAP 5/1 “Broadcaster”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Periodic Advertising Synchronizability mode	[7] 9.5.1	C.1	N/A
2	Periodic Advertising	[7] 9.5.2	O	[15] LL 3/10
3	Periodic Advertising with Responses	[7] 9.5.2.1	O	[15] LL 3/10a
4	No longer used	N/A	N/A	N/A

C.1: Optional IF GAP 11a/2 “Periodic Advertising”, otherwise Excluded.

2.3.1.7 Security Aspects

Table 11b: Broadcaster Security Aspects Features

Prerequisite: GAP 5/1 “Broadcaster”

Item	Capability	Reference	Status
1	LE security mode 3	[10] 10.2.5	C.1
2	LE security mode 3 level 1	[10] 10.2.5	C.2
3	LE security mode 3 level 2	[10] 10.2.5	C.2
4	LE security mode 3 level 3	[10] 10.2.5	C.2

C.1: Mandatory IF GAP 10/2 “Broadcast Isochronous Synchronizability mode”, otherwise Excluded.

C.2: Mandatory to support at least one IF GAP 11b/1 “LE security mode 3”, otherwise Excluded.

Table 11c: SM Requirements

Prerequisite: GAP 5/1 “Broadcaster”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Out of Band	N/A	C.1	[13] SM 4a/3 OR SM 4b/3

C.1: Mandatory IF GAP 8a/6 “Security Manager OOB”, otherwise not defined.

2.3.2 Observer

2.3.2.1 Physical Layer

Table 12: Observer Physical Layer

Prerequisite: GAP 5/2 “Observer”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	LE Receiver	[2] 2.2.2	M	[20] RFPHY 0/2
2	LE Transmitter	[2] 2.2.2	O	[20] RFPHY 0/1
3	LE 2M PHY	[2] 2.2.2	O	[20] RFPHY 1/4

2.3.2.2 Link Layer Features

2.3.2.2.1 Link Layer States

Table 13: Observer Link Layer States

Prerequisite: GAP 5/2 “Observer”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Standby State	[2] 2.2.2	M	N/A
2	Scanning State	[2] 2.2.2	M	[15] LL 1/2
3	Synchronization State	[2] 2.2.2	C.1	[15] LL 1/3a
3a	Synchronized Receiver	[2] 2.2.2	C.2	[15] LL 9/34

C.1: Optional IF CORE 1a/51 “Controller Core v5.1 or later”, otherwise not defined.

C.2: Optional IF GAP 13/3 “Synchronization State”, otherwise not defined.

2.3.2.2.2 Scanning Types

Table 14: Observer Link Layer Scanning Types

Prerequisite: GAP 5/2 “Observer”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Passive Scanning	[2] 2.2.2	M	[15] LL 4/1
2	Active Scanning	[2] 2.2.2	O	[15] LL 4/3

Table 14a: Observer Link Layer Scanning Data Types

Prerequisite: GAP 5/2 “Observer”

Item	Capability	Reference	Status
1	Service UUID	[3] 1.1	O
2	Local Name	[3] 1.2	O
3	Flags	[3] 1.3	O

Item	Capability	Reference	Status
4	Manufacturer Specific Data	[3] 1.4	O
5	TX Power Level	[3] 1.5	O
6	Security Manager OOB	[3] 1.7	O
7	Security Manager TK Value	[3] 1.8	O
8	Peripheral Connection Interval Range	[3] 1.9	O
9	Service Solicitation	[3] 1.10	O
10	Service Data	[3] 1.11	O
11	Appearance	[3] 1.12	O
12	Public Target Address	[3] 1.13	O
13	Random Target Address	[3] 1.14	O
14	Advertising Interval	[3] 1.15	O
14a	Advertising Interval – Long	[3] 1.15	O
15	LE Bluetooth Device Address	[3] 1.16	O
16	LE Role	[3] 1.17	O
17	Uniform Resource Identifier	[3] 1.18	O
18	LE Supported features	[3] 1.19	O
19	Encrypted Data	[3] 1.23	O
20	Periodic Advertising Response Timing	[3] 1.24	O

2.3.2.2.3 Control Procedures

Table 14b: Observer Link Layer Control Procedures

Prerequisite: GAP 5/2 “Observer”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	LE Encryption	[4] 2.2.2	O	[15] LL 9/1

2.3.2.3 Connection Modes and Procedures

Table 15: Observer Connection Modes and Procedures

Prerequisite: GAP 5/2 “Observer”

Item	Capability	Reference	Status
1	Non-connectable mode	[2] 9.3.2	M

2.3.2.4 Broadcasting and Observing

Table 16: Observer Broadcasting and Observing Features

Prerequisite: GAP 5/2 “Observer”

Item	Capability	Reference	Status
1	Observation procedure	[2] 9.1.2	M
2	Broadcast Isochronous Synchronization Establishment procedure	[10] 9.6.3	C.1
3	Broadcast Isochronous Termination procedure	[10] 9.6.5	C.2
4	Broadcast Isochronous Channel Map Update procedure	[10] 9.6.4	C.2

C.1: Optional IF CORE 2a/52 “Host Core v5.2 or later”, otherwise Excluded.

C.2: Mandatory IF GAP 16/2 “Broadcast Isochronous Synchronization Establishment procedure”, otherwise Excluded.

2.3.2.5 Privacy Feature

Table 17: Observer Privacy Feature

Prerequisite: GAP 5/2 “Observer”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Privacy feature	[5] 10.7	O	N/A
2	Non-resolvable private address generation procedure	[5] 10.8.2.1 [6] 1.3.2.2	C.1	N/A
3	Resolvable private address resolution procedure	[5] 10.8.2.3 [6] 1.3.2.2	O	N/A
4	Resolvable private address generation procedure	[5] 10.8.2.2 [6] 1.3.2.3	C.2	N/A
5	Controller-based privacy	[5] 10.7	O	N/A
6	LL Privacy	[5] 10.7 [6] 6	C.3	[15] LL 9/13

C.1: Mandatory IF GAP 17/1 “Privacy feature” AND GAP 14/2 “Active Scanning” AND NOT GAP 17/4 “Resolvable private address generation procedure”, otherwise Optional.

C.2: Mandatory IF GAP 17/1 “Privacy feature” AND GAP 14/2 “Active Scanning” AND NOT GAP 17/2 “Non-resolvable private address generation procedure”, otherwise Optional.

C.3: Mandatory IF GAP 17/1 “Privacy feature”, otherwise not defined.

2.3.2.6 Periodic Advertising Modes and Procedures

Table 17a: Periodic Advertising Modes and Procedures

Prerequisite: GAP 5/2 "Observer"

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Periodic Advertising Synchronization Establishment procedure without listening for periodic advertising	[7] 9.5.3	O	N/A
2	Periodic Advertising Synchronization Establishment procedure with listening for periodic advertising	[7] 9.5.3	O	N/A
3	No longer used	N/A	N/A	N/A
4	Scanning for Periodic Advertising	[7] 9.5.3	C.1	[15] LL 4/8
5	Synchronizing to Periodic Advertising	[7] 9.5.3	C.2	[15] LL 11/1
6	Scanning for Periodic Advertising with Responses	[12] 9.3.17	C.3	[15] LL 4/8a

C.1: Mandatory IF GAP 17a/1 "Periodic Advertising Synchronization Establishment procedure without listening for periodic advertising", otherwise not defined.

C.2: Mandatory IF GAP 17a/2 "Periodic Advertising Synchronization Establishment procedure with listening for periodic advertising", otherwise not defined.

C.3: Mandatory IF GAP 33/10 "Periodic Advertising Connection procedure", otherwise not defined.

2.3.2.7 Security Aspects

Table 17b: Observer Security Aspects Features

Prerequisite: GAP 5/2 "Observer"

Item	Capability	Reference	Status
1	LE security mode 3	[10] 10.2.5	C.1
2	LE security mode 3 level 1	[10] 10.2.5	C.2
3	LE security mode 3 level 2	[10] 10.2.5	C.2
4	LE security mode 3 level 3	[10] 10.2.5	C.2

C.1: Mandatory IF GAP 16/2 "Broadcast Isochronous Synchronization Establishment procedure", otherwise Excluded.

C.2: Mandatory to support at least one IF GAP 17b/1 "LE security mode 3", otherwise Excluded.

2.3.3 Peripheral

2.3.3.1 Physical Layer

Table 18: Peripheral Physical Layer

Prerequisite: GAP 5/3 “Peripheral”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	LE Transmitter	[2] 2.2.2	M	[20] RFPHY 0/1
2	LE Receiver	[2] 2.2.2	M	[20] RFPHY 0/2
3	LE 2M PHY	[2] 2.2.2	O	[20] RFPHY 1/4

2.3.3.2 Link Layer Features

2.3.3.2.1 Link Layer States

Table 19: Peripheral Link Layer States

Prerequisite: GAP 5/3 “Peripheral”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Standby State	[2] 2.2.2	M	N/A
2	Advertising State	[2] 2.2.2	M	[15] LL 1/1
3	Connection State (Peripheral Role)	[4] 2.2.2	M	[15] LL 1/4

2.3.3.2.2 Advertising Event Types

Table 20: Peripheral Link Layer Advertising Event Types

Prerequisite: GAP 5/3 “Peripheral”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Connectable and scannable undirected events	[4] 2.2.2	M	[15] LL 3/2
2	Connectable directed events	[4] 2.2.2	O	[15] LL 3/4
2a	No longer used	N/A	N/A	N/A
3	Non-connectable and non-scannable undirected events	[4] 2.2.2, 9.3.2.2, 9.3.11.2	O	[15] LL 3/1
4	Scannable undirected events	[4] 2.2.2, 9.3.4.2	O	[15] LL 3/5
5	Connectable undirected events	[7] 2.2.2	C.1	[15] LL 3/4b
6	Non-connectable and non-scannable directed events	[7] 2.2.2	C.1	[15] LL 3/1a
7	Scannable directed events	[7] 2.2.2	C.1	[15] LL 3/5a

Item	Capability	Reference	Status	Inter-Layer Dependency
8	LE Extended Advertising	[7] 2.2.2	O	[15] LL 9/41
9	LE Periodic Advertising	[7] 2.2.2	C.1	[15] LL 9/42

C.1: Optional IF GAP 20/8 “LE Extended Advertising”, otherwise not defined.

2.3.3.2.3 Advertising Data Types

Table 20a: Peripheral Link Layer Advertising Data Types

Prerequisite: GAP 5/3 “Peripheral”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Service UUID	[3] 1.1	C.1	N/A
2	Local Name	[3] 1.2	C.1	N/A
3	Flags	[3] 1.3	C.2	N/A
4	Manufacturer Specific Data	[3] 1.4	C.1	N/A
5	TX Power Level	[3] 1.5	C.1	N/A
6	Security Manager OOB	[3] 1.7	C.3	N/A
7	Security Manager TK Value	[3] 1.8	C.1	N/A
8	Peripheral Connection Interval Range	[3] 1.9	C.1	N/A
9	Service Solicitation	[3] 1.10	C.1	N/A
10	Service Data	[3] 1.11	C.1	N/A
11	Appearance	[3] 1.12	C.1	N/A
12	Public Target Address	[3] 1.13	C.1	N/A
13	Random Target Address	[3] 1.14	C.1	N/A
14	Advertising Interval	[3] 1.15	C.1	N/A
14a	Advertising Interval – Long	[3] 1.15	C.1	N/A
15	LE Bluetooth Device Address	[3] 1.16	C.1	N/A
16	LE Role	[3] 1.17	C.1	N/A
17	Uniform Resource Identifier	[3] 1.18	O	N/A
18	LE Supported features	[3] 1.19	O	N/A
19	Encrypted Data	[3] 1.23	O	N/A
20	Periodic Advertising Response Timing	[3] 1.24	O	N/A
21	Periodic Advertising with Responses	[3] 1.24	C.4	[15] LL 3/10a

C.1: Optional IF GAP 20/1 “Connectable and scannable undirected events” OR GAP 20/3 “Non-connectable and non-scannable undirected events” OR GAP 20/4 “Scannable undirected events”, otherwise Excluded.

C.2: Mandatory IF GAP 22/2 “Limited discoverable mode” OR GAP 22/3 “General discoverable mode”, otherwise Optional.

C.3: Optional IF (GAP 20/1 “Connectable and scannable undirected events” OR GAP 20/3 “Non-connectable and non-scannable undirected events” OR GAP 20/4 “Scannable undirected events”) AND GAP 27b/9 “Out of Band”, otherwise Excluded.

C.4: Mandatory IF GAP 20a/20 “Periodic Advertising Response Timing”, otherwise not defined.



2.3.3.2.4 Control Procedures

Table 21: Peripheral Link Layer Control Procedures

Prerequisite: GAP 5/3 "Peripheral"

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Connection Update procedure	[4] 2.2.2	M	N/A
2	Channel Map Update procedure	[4] 2.2.2	M	N/A
3	Encryption procedure	[4] 2.2.2	C.3	N/A
3a	LE Encryption	[4] 2.2.2	C.4	[15] LL 9/1
4	Central-initiated Feature Exchange procedure	[4] 2.2.2	M	N/A
5	Version Exchange procedure	[4] 2.2.2	M	N/A
6	Termination procedure	[4] 2.2.2	M	N/A
7	LE Ping procedure	[4] 2.2.2	O	N/A
8	Peripheral-initiated Feature Exchange procedure	[4] 2.2.2	C.1	N/A
9	Connection Parameter Request procedure	[4] 2.2.2	O	N/A
10	Data Length Update procedure	[8] 2.2.2	O	N/A
11	PHY Update procedure	[8] 2.2.2	O	N/A
12	Minimum Number Of Used Channels procedure	[8] 2.2.2	O	N/A

C.1: Mandatory IF GAP 21/9 "Connection Parameter Request procedure", otherwise Optional.

C.2: No longer used.

C.3: Mandatory IF GAP 25/6 "Authenticate signed data procedure" OR GAP 25/7 "Authenticated Pairing (LE security mode 1 level 3)" OR GAP 25/9 "LE security mode 1 level 4", otherwise Optional.

C.4: Mandatory IF GAP 21/3 "Encryption procedure", otherwise not defined.

2.3.3.3 Discovery Modes and Procedures

Table 22: Peripheral Discovery Modes and Procedures

Prerequisite: GAP 5/3 "Peripheral"

Item	Capability	Reference	Status
1	Non-discoverable mode	[4] 9.2.2, 13.1	M
2	Limited discoverable mode	[4] 9.2.3, 13.1	O
3	General discoverable mode	[4] 9.2.4, 13.1	C.1
4	Name discovery procedure	[2] 9.2.7	O

C.1: Mandatory IF NOT GAP 22/2 "Limited discoverable mode", otherwise Optional.

2.3.3.4 Connection Modes and Procedures

Table 23: Peripheral Connection Modes and Procedures

Prerequisite: GAP 5/3 “Peripheral”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Non-connectable mode	[4] 9.3.2	M	N/A
2	Directed connectable mode	[4] 9.3.3	O	N/A
3	Undirected connectable mode	[4] 9.3.4	M	N/A
4	Connection parameter update procedure	[4] 9.3.9	O	N/A
5	Terminate connection procedure	[4] 9.3.10	M	N/A
6	Connected Isochronous Stream Peripheral Establishment procedure	[10] 9.3.14	C.1	N/A
7	Connected Isochronous Stream Terminate procedure	[10] 9.3.15	C.1	N/A
7a	Connected Isochronous Stream - Peripheral	[10] 9.3.14, 9.3.15	O	[15] LL 9/32
8	Connection Subrate procedure	[11] 9.3.16	C.2	N/A
8a	Shorter Connection Intervals	[6] 4.6.50	C.4	[15] LL 9/69
9	Periodic Advertising Connection	[11] 9.5.5.1	C.3	N/A

C.1: Mandatory IF GAP 23/7a “Connected Isochronous Stream - Peripheral”, otherwise Excluded.

C.2: Optional IF CORE 2a/53 “Host Core v5.3 or later”, otherwise Excluded.

C.3: Optional IF GAP 20a/21 “Periodic Advertising with Responses”, otherwise Excluded.

C.4: Optional IF GAP 23/8 “Connection Subrate procedure”, otherwise not defined.

Table 23a: Channel Sounding Procedure Support and Roles

Prerequisite: GAP 5/3 “Peripheral” AND CORE 2a/60 “Host Core v6.0 or later”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	CS Initiator Role	[16] 9.7.1	C.1	[16] LL 1/7
2	CS Reflector Role	[16] 9.7.2	C.1	[16] LL 1/8
3	Channel Sounding procedure for GAP Peripheral	[16] 9.7	O	N/A

C.1: Mandatory to support at least one IF GAP 23a/3 “Channel Sounding procedure for GAP Peripheral”, otherwise not defined.

2.3.3.5 Bonding Modes and Procedures

Table 24: Peripheral Bonding Modes and Procedures

Prerequisite: GAP 5/3 “Peripheral”

Item	Capability	Reference	Status
1	Non-bondable mode	[2] 9.4.2	M
2	Bondable mode	[4] 9.4.3, 13.2	O



Item	Capability	Reference	Status
3	Bonding procedure	[4] 9.4.4, 13.2	C.2
4	Multiple Bonds	[4] 9.4	C.1

C.1: Optional IF GAP 24/2 “Bondable mode”, otherwise Excluded.

C.2: Mandatory IF GAP 24/2 “Bondable mode”, otherwise Excluded.

2.3.3.6 Security Aspects

Table 25: Peripheral Security Aspects Features

Prerequisite: GAP 5/3 “Peripheral”

Item	Capability	Reference	Status
1	LE security mode 1	[4] 10.2.1	O
2	LE security mode 2	[4] 10.2.2	C.17
3	Authentication procedure	[4] 10.3	O
4	Authorization procedure	[4] 10.5	O
5	Connection data signing procedure	[4] 10.4.1	C.6
6	Authenticate signed data procedure	[4] 10.4.2	C.6
7	Authenticated Pairing (LE security mode 1 level 3)	[4] 10.2.1	C.1
8	Unauthenticated Pairing (LE security mode 1 level 2)	[4] 10.2.1	C.1
9	LE security mode 1 level 4	[5] 10.2.1	C.1
10	Secure Connections Only mode	[12] 10.2.4, 14.3	C.4
11	Unauthenticated Pairing (LE security mode 1 level 2) with LE Secure Connections Pairing only	[5] 10.2.1	C.15
12	Authenticated Pairing (LE security mode 1 level 3) with LE Secure Connections Pairing only	[5] 10.2.1	C.16
13	Minimum 128-bit entropy key	[5] 10.2.1	C.5
13a	Minimum 128-bit entropy key, LE security mode 1 level 4	[5] 10.2.1	C.7
13b	Minimum 128-bit entropy key, LE security mode 1 level 3	[5] 10.2.1	C.8
13c	Minimum 128-bit entropy key, LE security mode 1 level 2	[5] 10.2.1	C.9
14	Client security checks for GATT indications and notifications	[11] 10.3.2.2	O
15	Channel Sounding Security Level 1	[16] 10.11.1	C.10, C.14
16	Channel Sounding Security Level 2	[16] 10.11.1	C.11, C.14
17	Channel Sounding Security Level 3	[16] 10.11.1	C.12, C.14
18	Channel Sounding Security Level 4	[16] 10.11.1	C.13, C.14

C.1: Optional IF GAP 25/1 “LE security mode 1”, otherwise Excluded.

C.2–C.3: No longer used.

C.4: Mandatory IF GAP 2/11 “Secure Connections Only Mode” OR GAP 35/10 “Secure Connections Only mode”, otherwise Optional IF GAP 25/9 “LE security mode 1 level 4”, otherwise Excluded.

C.5: Mandatory IF GAP 25/13a “Minimum 128-bit entropy key, LE security mode 1 level 4” OR GAP 25/13b “Minimum 128-bit entropy key, LE security mode 1 level 3” OR GAP 25/13c “Minimum 128-bit entropy key, LE security mode 1 level 2”, otherwise Excluded.



- C.6: Mandatory to support at least one IF GAP 25/2 “LE security mode 2”, otherwise Optional IF CORE 2b/62 “Host Core v6.2 or earlier”, otherwise Excluded.
- C.7: Mandatory IF GAP 25/9 “LE security mode 1 level 4”, otherwise Excluded.
- C.8: Optional IF GAP 25/12 “Authenticated Pairing (LE security mode 1 level 3) with LE Secure Connections Pairing only”, otherwise Excluded.
- C.9: Optional IF GAP 25/11 “Unauthenticated Pairing (LE security mode 1 level 2) with LE Secure Connections Pairing only”, otherwise Excluded.
- C.10: Optional IF GAP 25a/1 “CS Mode-2”, otherwise Excluded.
- C.11: Optional IF (GAP 25a/3 “CS RTT Access Address, 10 ns” OR GAP 25a/4 “CS RTT Access Address, 150 ns” OR GAP 25a/5 “CS RTT Sounding Sequence, 10 ns” OR GAP 25a/6 “CS RTT Sounding Sequence, 150 ns” OR GAP 25a/7 “CS RTT Random Payload, 10 ns” OR GAP 25a/8 “CS RTT Random Payload, 150 ns”) AND GAP 25a/1 “CS Mode-2”, otherwise Excluded.
- C.12: Optional IF (GAP 25a/3 “CS RTT Access Address, 10 ns” OR GAP 25a/5 “CS RTT Sounding Sequence, 10 ns” OR GAP 25a/7 “CS RTT Random Payload, 10 ns”) AND GAP 25a/1 “CS Mode-2”, otherwise Excluded.
- C.13: Optional IF (GAP 25a/3 “CS RTT Access Address, 10 ns” OR GAP 25a/5 “CS RTT Sounding Sequence, 10 ns” OR GAP 25a/7 “CS RTT Random Payload, 10 ns”) AND GAP 25a/1 “CS Mode-2” AND (GAP 25a/9 “Phase-based Normalized Attack Detector Metric – Sounding Sequence” OR GAP 25a/10 “Phase-based Normalized Attack Detector Metric – Random Bit Sequence”), otherwise Excluded.
- C.14: Mandatory to support at least one IF GAP 23a/3 “Channel Sounding procedure for GAP Peripheral”, otherwise Excluded.
- C.15: Optional IF GAP 25/8 “Unauthenticated Pairing (LE security mode 1 level 2)”, otherwise Excluded.
- C.16: Optional IF GAP 25/7 “Authenticated Pairing (LE security mode 1 level 3)”, otherwise Excluded.
- C.17: Optional IF CORE 2b/62 “Host Core v6.2 or earlier”, otherwise Excluded.

Table 25a: Channel Sounding Features

Prerequisite: GAP 5/3 “Peripheral” AND GAP 23a/3 “Channel Sounding procedure for GAP Peripheral”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	CS Mode-2	[16] 10.11	M	[16] LL 13/2
2	CS Mode-3	[16] 10.11	O	[16] LL 13/3
3	CS RTT Access Address, 10 ns	[16] 10.11.1	C.1	[16] LL 13/4
4	CS RTT Access Address, 150 ns	[16] 10.11.1	C.1	[16] LL 13/5
5	CS RTT Sounding Sequence, 10 ns	[16] 10.11.1	C.2	[16] LL 13/6
6	CS RTT Sounding Sequence, 150 ns	[16] 10.11.1	C.2	[16] LL 13/7
7	CS RTT Random Payload, 10 ns	[16] 10.11.1	C.3	[16] LL 13/8
8	CS RTT Random Payload, 150 ns	[16] 10.11.1	C.3	[16] LL 13/9
9	Phase-based Normalized Attack Detector Metric – Sounding Sequence	[16] 10.11.1	O	[17] CS 2/14a
10	Phase-based Normalized Attack Detector Metric – Random Bit Sequence	[16] 10.11.1	O	[17] CS 2/14b

- C.1: Mandatory to support one and only one.
- C.2: Optional to support one and only one.
- C.3: Optional to support one and only one.

Table 25b (auto-fill): Peripheral Security Levels Satisfaction*Prerequisite: GAP 5/3 "Peripheral"*

Item	Capability	Reference	Status
1	Satisfies LE security mode 1 level 2	[4] 10.2.1	C.1
2	Satisfies LE security mode 1 level 3	[4] 10.2.1	C.2
3	Satisfies LE security mode 1 level 4	[5] 10.2.1	C.3

C.1: Mandatory IF GAP 25/7 "Authenticated Pairing (LE security mode 1 level 3)" OR GAP 25/8 "Unauthenticated Pairing (LE security mode 1 level 2)" OR GAP 25/9 "LE security mode 1 level 4", otherwise Excluded.

C.2: Mandatory IF GAP 25/7 "Authenticated Pairing (LE security mode 1 level 3)" OR GAP 25/9 "LE security mode 1 level 4", otherwise Excluded.

C.3: Mandatory IF GAP 25/9 "LE security mode 1 level 4", otherwise Excluded.

2.3.3.7 Privacy Feature

Table 26: Peripheral Privacy Feature*Prerequisite: GAP 5/3 "Peripheral"*

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Privacy feature	[5] 10.7	O	N/A
2	Non-resolvable private address generation procedure	[5] 10.7, 10.8.2.1 [6] 1.3.2.2	O	N/A
3	Resolvable private address generation procedure	[5] 10.7, 10.8.2.2 [6] 1.3.2.2	C.1	N/A
4	Resolvable private address resolution procedure	[5] 10.7, 10.8.2.3 [6] 1.3.2.2	C.1	N/A
5	Controller-based privacy	[5] 10.7	O	N/A
6	LL Privacy	[5] 10.7 [6] 6	C.2	[15] LL 9/13

C.1: Mandatory IF GAP 26/1 "Privacy feature", otherwise Optional.

C.2: Mandatory IF GAP 26/1 "Privacy feature", otherwise not defined.

2.3.3.8 Generic Access Profile Characteristics

Table 27: Peripheral GAP Characteristics*Prerequisite: GAP 5/3 "Peripheral"*

Item	Capability	Reference	Status
1	Device Name	[2] 12.1	M
2	Appearance	[2] 12.2	M
3–4	No longer used	N/A	N/A
5	Peripheral Preferred Connection Parameters	[2] 12.3	C.6
6	Writable Device Name	[2] 12.1	C.4

Item	Capability	Reference	Status
7	Writable Appearance	[2] 12.2	C.5
8	No longer used	N/A	N/A
9	Central Address Resolution	[5] 12	C.7
9a	No longer used	N/A	N/A
10	Encrypted Data Key Material	[12] 12.6	C.9
10a	Encrypted Data Key Material Indications	[12] 12.6	C.2
11	LE GATT Security Levels	[12] 12.7	C.10
12	Resolvable Private Address Only	[2] 12.5	C.8

- C.1: No longer used.
- C.2: Mandatory IF GAP 4b/7 “Encrypted Data Key Material Indications”, otherwise Optional IF GAP 27/10 “Encrypted Data Key Material”, otherwise Excluded.
- C.3: No longer used.
- C.4: Mandatory IF GAP 4b/8 “Writable Device Name” OR GAP 37/6 “Writable Device Name”, otherwise Optional.
- C.5: Mandatory IF GAP 4b/9 “Writable Appearance” OR GAP 37/7 “Writable Appearance”, otherwise Optional.
- C.6: Mandatory IF GAP 4b/3 “Peripheral Preferred Connection Parameters”, otherwise Optional.
- C.7: Mandatory IF GAP 4b/4 “Central Address Resolution” OR GAP 37/3 “Central Address Resolution”, otherwise Optional IF GAP 26/6 “LL Privacy”, otherwise Excluded.
- C.8: Mandatory IF GAP 4b/5 “Resolvable Private Address Only” OR GAP 37/5 “Resolvable Private Address Only”, otherwise Optional IF GAP 26/6 “LL Privacy”, otherwise Excluded.
- C.9: Mandatory IF GAP 4b/6 “Encrypted Data Key Material”, otherwise Optional.
- C.10: Mandatory IF GAP 37/4 “LE GATT Security Levels”, otherwise Optional.

2.3.3.9 Periodic Advertising Modes and Procedures

Table 27a: Periodic Advertising Modes and Procedures

Prerequisite: GAP 5/3 “Peripheral” AND CORE 2a/51 “Host Core v5.1 or later”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Periodic Advertising Synchronization Transfer procedure	[8] 9.5.4	O	N/A
2	Periodic Advertising Synchronization Establishment procedure over an LE connection without listening for periodic advertising	[8] 9.5.3	O	N/A
3	Periodic Advertising Synchronization Establishment procedure over an LE connection with listening for periodic advertising	[8] 9.5.3	O	N/A
4	Periodic Advertising Sync Transfer - Sender	[8] 9.5.4	C.1	[15] LL 9/26

Item	Capability	Reference	Status	Inter-Layer Dependency
5	Periodic Advertising Sync Transfer - Recipient	[8] 9.5.3	C.2	[15] LL 9/27
6	Synchronizing to Periodic Advertising	[8] 9.5.3	C.3	[15] LL 11/1

- C.1: Mandatory IF GAP 27a/1 “Periodic Advertising Synchronization Transfer procedure”, otherwise not defined.
- C.2: Mandatory IF GAP 27a/2 “Periodic Advertising Synchronization Establishment procedure over an LE connection without listening for periodic advertising” OR GAP 27a/3 “Periodic Advertising Synchronization Establishment procedure over an LE connection with listening for periodic advertising”, otherwise not defined.
- C.3: Mandatory IF GAP 27a/3 “Periodic Advertising Synchronization Establishment procedure over an LE connection with listening for periodic advertising”, otherwise not defined.

2.3.3.10 SM requirements

Table 27b: SM Requirements

Prerequisite: GAP 5/3 “Peripheral”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Peripheral Role (Responder)	N/A	M	[13] SM 1/2
2	Authenticated MITM protection	[4] 10.3	C.1	N/A
3	Unauthenticated no MITM protection	[4] 10.3	C.2	N/A
4	No security requirements	[4] 10.2.1	C.3	N/A
5	LE Secure Connections	[4] 10.2.1	C.4	N/A
6	Long Term Key (LTK)	[4] 9.4.3	C.5	[13] SM 7b/1
7	Identity Resolving Key (IRK)	[4] 10.7	C.6	[13] SM 7b/2
8	Connection Signature Resolving Key (CSRK)	[4] 10.4	C.7	[13] SM 7b/3
9	Out of Band	[4] 10.4	O	[13] SM 4a/3 OR SM 4b/3
10	Peripheral Initiated Security	[4] 10.3	O	[13] SM 5/3
11	Legacy pairing	[4] 10.3	C.8	[13] SM 2a/1
12	LE Secure Connection pairing	[4] 10.3	C.4	[13] SM 2a/2

- C.1: Mandatory IF GAP 25/7 “Authenticated Pairing (LE security mode 1 level 3)” OR GAP 25/12 “Authenticated Pairing (LE security mode 1 level 3) with LE Secure Connections Pairing only” OR (GAP 25/2 “LE security mode 2” AND GAP 25/3 “Authentication procedure”), otherwise Excluded.
- C.2: Mandatory IF GAP 25/8 “Unauthenticated Pairing (LE security mode 1 level 2)” OR GAP 25/11 “Unauthenticated Pairing (LE security mode 1 level 2) with LE Secure Connections Pairing only” OR (GAP 25/2 “LE security mode 2” AND NOT GAP 25/3 “Authentication procedure”), otherwise Excluded.
- C.3: Mandatory IF GAP 25/1 “LE security mode 1” AND NOT GAP 25/8 “Unauthenticated Pairing (LE security mode 1 level 2)” AND NOT GAP 25/7 “Authenticated Pairing (LE security mode 1 level 3)” AND NOT GAP 25/9 “LE security mode 1 level 4”, otherwise Optional IF GAP 25/1 “LE security mode 1”, otherwise Excluded.
- C.4: Mandatory IF GAP 25/9 “LE security mode 1 level 4” OR GAP 25/11 “Unauthenticated Pairing (LE security mode 1 level 2) with LE Secure Connections Pairing only” OR GAP 25/12 “Authenticated Pairing (LE security mode 1 level 3) with LE Secure Connections Pairing only”, otherwise not defined.

- C.5: Mandatory IF GAP 24/2 “Bondable mode”, otherwise not defined.
- C.6: Mandatory IF GAP 26/3 “Resolvable private address generation procedure”, otherwise not defined.
- C.7: Mandatory IF GAP 25/6 “Authenticate signed data procedure”, otherwise not defined.
- C.8: Mandatory IF GAP 25/2 “LE security mode 2” OR GAP 25/7 “Authenticated Pairing (LE security mode 1 level 3)” OR GAP 25/8 “Unauthenticated Pairing (LE security mode 1 level 2)”, otherwise not defined.

2.3.3.11 L2CAP requirements

Table 27c (auto-fill): L2CAP Requirements

Prerequisite: GAP 5/3 “Peripheral”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Detect insufficient authentication	[4] 10.3	C.1	[14] L2CAP 4/1
2	Detect insufficient authorization	[4] 10.5	C.2	[14] L2CAP 4/2
3	Detect insufficient encryption	[4] 2.2.2	C.3	[14] L2CAP 4/3

- C.1: Mandatory IF GAP 25/3 “Authentication procedure”, otherwise not defined.
- C.2: Mandatory IF GAP 25/4 “Authorization procedure”, otherwise not defined.
- C.3: Mandatory IF GAP 21/3 “Encryption procedure”, otherwise not defined.

2.3.4 Central

2.3.4.1 Physical Layer

Table 28: Central Physical Layer

Prerequisite: GAP 5/4 “Central”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	LE Transmitter	[2] 2.2.2	M	[20] RFPHY 0/1
2	LE Receiver	[2] 2.2.2	M	[20] RFPHY 0/2
3	LE 2M PHY	[2] 2.2.2	O	[20] RFPHY 1/4

2.3.4.2 Link Layer Features

2.3.4.2.1 Link Layer States

Table 29: Central Link Layer States

Prerequisite: GAP 5/4 “Central”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Standby State	[2] 2.2.2	M	N/A
2	Scanning State	[2] 2.2.2	M	[15] LL 1/2

Item	Capability	Reference	Status	Inter-Layer Dependency
3	Initiating State	[2] 2.2.2	M	[15] LL 1/3
4	Connection State (Central Role)	[2] 2.2.2	M	[15] LL 1/5

2.3.4.2.2 Scanning Types

Table 30: Central Link Layer Scanning Types

Prerequisite: GAP 5/4 “Central”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Passive Scanning	[2] 2.2.2	C.1	[15] LL 4/1
2	Active Scanning	[2] 2.2.2	C.1	[15] LL 4/3

C.1: Mandatory to support at least one.

Table 30a: Central Link Layer Scanning Data Types

Prerequisite: GAP 5/4 “Central”

Item	Capability	Reference	Status
1	Service UUID	[3] 1.1	O
2	Local Name	[3] 1.2	O
3	Flags	[3] 1.3	O
4	Manufacturer Specific Data	[3] 1.4	O
5	TX Power Level	[3] 1.5	O
6	Security Manager OOB	[3] 1.7	O
7	Security Manager TK Value	[3] 1.8	O
8	Peripheral Connection Interval Range	[3] 1.9	O
9	Service Solicitation	[3] 1.10	O
10	Service Data	[3] 1.11	O
11	Appearance	[3] 1.12	O
12	Public Target Address	[3] 1.13	O
13	Random Target Address	[3] 1.14	O
14	Advertising Interval	[3] 1.15	O
14a	Advertising Interval – Long	[3] 1.15	O
15	LE Bluetooth Device Address	[3] 1.16	O
16	LE Role	[3] 1.17	O
17	Uniform Resource Identifier	[3] 1.18	O
18	LE Supported features	[3] 1.19	O
19	Encrypted Data	[3] 1.23	O
20	Periodic Advertising Response Timing	[3] 1.24	O

2.3.4.3 Control Procedures

Table 31: Central Link Layer Control Procedures

Prerequisite: GAP 5/4 “Central”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Connection Update procedure	[2] 2.2.2	M	N/A
2	Channel Map Update procedure	[2] 2.2.2	M	N/A
3	Encryption procedure	[2] 2.2.2	C.3	N/A
3a	LE Encryption	[4] 2.2.2	C.4	[15] LL 9/1
4	Central-initiated Feature Exchange procedure	[2] 2.2.2	M	N/A
5	Version Exchange procedure	[2] 2.2.2	M	N/A
6	Termination procedure	[2] 2.2.2	M	N/A
7	LE Ping procedure	[4] 2.2.2	O	N/A
8	Peripheral-initiated Feature Exchange procedure	[4] 2.2.2	C.1	N/A
9	Connection Parameter Request procedure	[4] 2.2.2	O	N/A
10	Data Length Update procedure	[8] 2.2.2	O	N/A
11	PHY Update procedure	[8] 2.2.2	O	N/A
12	Minimum Number Of Used Channels procedure	[8] 2.2.2	O	N/A

C.1: Mandatory IF GAP 31/9 “Connection Parameter Request procedure”, otherwise Optional.

C.2: No longer used.

C.3: Mandatory IF GAP 35/6 “Authenticate signed data procedure” OR GAP 35/7 “Authenticated Pairing (LE security mode 1 level 3)” OR GAP 35/9 “LE security mode 1 level 4”, otherwise Optional.

C.4: Mandatory IF GAP 31/3 “Encryption procedure”, otherwise not defined.

2.3.4.4 Discovery Modes and Procedures

Table 32: Central Discovery Modes and Procedures

Prerequisite: GAP 5/4 “Central”

Item	Capability	Reference	Status
1	Limited Discovery procedure	[4] 9.2.5	O
2	General Discovery procedure	[4] 9.2.6	M
3	Name Discovery procedure	[4] 9.2.7	O

2.3.4.5 Connection Modes and Procedures

Table 33: Central Connection Modes and Procedures

Prerequisite: GAP 5/4 “Central”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Auto connection establishment procedure	[2] 9.3.5	O	N/A
2	General connection establishment procedure	[4] 9.3.6	O	N/A
3	Selective connection establishment procedure	[2] 9.3.7	O	N/A
4	Direct connection establishment procedure	[2] 9.3.8	M	N/A
5	Connection parameter update procedure	[2] 9.3.9	M	N/A
6	Terminate connection procedure	[2] 9.3.10	M	N/A
7	Connected Isochronous Stream Central Establishment procedure	[10] 9.3.13	C.1	N/A
8	Connected Isochronous Stream Terminate procedure	[10] 9.3.15	C.1	N/A
8a	Connected Isochronous Stream - Central	[10] 9.3.13, 9.3.15	O	[15] LL 9/31
9	Connection Subrate procedure	[11] 9.3.16	C.2	N/A
9a	Shorter Connection Intervals	[6] 4.6.50	C.4	[15] LL 9/69
10	Periodic Advertising Connection procedure	[12] 9.3.17	O	N/A
11	Scanning for Periodic Advertising with Responses	[12] 9.3.17	C.3	[15] LL 4/8a

C.1: Mandatory IF GAP 33/8a “Connected Isochronous Stream - Central”, otherwise Excluded.

C.2: Optional IF CORE 2a/53 “Host Core v5.3 or later”, otherwise Excluded.

C.3: Mandatory IF GAP 33/10 “Periodic Advertising Connection procedure”, otherwise not defined.

C.4: Optional IF GAP 33/9 “Connection Subrate procedure”, otherwise not defined.

Table 33a: Channel Sounding Procedure Support and Roles

Prerequisite: GAP 5/4 “Central” AND CORE 2a/60 “Host Core v6.0 or later”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	CS Initiator Role	[16] 9.7.1	C.1	[16] LL 1/7
2	CS Reflector Role	[16] 9.7.1	C.1	[16] LL 1/8
3	Channel Sounding procedure for GAP Central	[16] 9.7	O	N/A

C.1: Mandatory to support at least one IF GAP 33a/3 “Channel Sounding procedure for GAP Central”, otherwise not defined.

2.3.4.6 Bonding Modes and Procedures

Table 34: Central Bonding Modes and Procedures

Prerequisite: GAP 5/4 “Central”

Item	Capability	Reference	Status
1	Non-bondable mode	[4] 9.4.2, 13.2	M
2	Bondable mode	[4] 9.4.3, 13.2	O
3	Bonding procedure	[4] 9.4.4, 13.2	C.1

C.1: Mandatory IF GAP 34/2 “Bondable mode”, otherwise Excluded.

2.3.4.7 Security Aspects

Table 35: Central Security Features

Prerequisite: GAP 5/4 “Central”

Item	Capability	Reference	Status
1	LE security mode 1	[2] 10.2.1	O
2	LE security mode 2	[2] 10.2.2	C.15
3	Authentication procedure	[2] 10.3	O
4	Authorization procedure	[2] 10.5	O
5	Connection data signing procedure	[2] 10.4.1	C.15
6	Authenticate signed data procedure	[2] 10.4.3	C.15
7	Authenticated Pairing (LE security mode 1 level 3)	[2] 10.2.1	C.1
8	Unauthenticated Pairing (LE security mode 1 level 2)	[2] 10.2.1	C.1
9	LE security mode 1 level 4	[5] 10.2.1	C.1
10	Secure Connections Only mode	[12] 10.2.4, 14.3	C.3
11	Unauthenticated Pairing (LE security mode 1 level 2) with LE Secure Connections Pairing only	[5] 10.2.1	C.13
12	Authenticated Pairing (LE security mode 1 level 3) with LE Secure Connections Pairing only	[5] 10.2.1	C.14
13	Minimum 128-bit entropy key	[5] 10.2.1	C.4
13a	Minimum 128-bit entropy key, LE security mode 1 level 4	[5] 10.2.1	C.5
13b	Minimum 128-bit entropy key, LE security mode 1 level 3	[5] 10.2.1	C.6
13c	Minimum 128-bit entropy key, LE security mode 1 level 2	[5] 10.2.1	C.7
14	Encrypted Advertising Data Procedure	[12] 10.10	O
15	Client security checks for GATT indications and notifications	[11] 10.3.2.2	O
16	Channel Sounding Security Level 1	[16] 10.11.1	C.8, C.12
17	Channel Sounding Security Level 2	[16] 10.11.1	C.9, C.12
18	Channel Sounding Security Level 3	[16] 10.11.1	C.10, C.12
19	Channel Sounding Security Level 4	[16] 10.11.1	C.11, C.12

- C.1: Optional IF GAP 35/1 “LE security mode 1”, otherwise Excluded.
- C.2: No longer used.
- C.3: Mandatory IF GAP 2/11 “Secure Connections Only Mode” OR GAP 25/10 “Secure Connections Only mode”, otherwise Optional IF GAP 35/9 “LE security mode 1 level 4”, otherwise Excluded.
- C.4: Mandatory IF GAP 35/13a “Minimum 128-bit entropy key, LE security mode 1 level 4” OR GAP 35/13b “Minimum 128-bit entropy key, LE security mode 1 level 3” OR GAP 35/13c “Minimum 128-bit entropy key, LE security mode 1 level 2”, otherwise Excluded.
- C.5: Mandatory IF GAP 35/9 “LE security mode 1 level 4”, otherwise Excluded.
- C.6: Optional IF GAP 35/12 “Authenticated Pairing (LE security mode 1 level 3) with LE Secure Connections Pairing only”, otherwise Excluded.
- C.7: Optional IF GAP 35/11 “Unauthenticated Pairing (LE security mode 1 level 2) with LE Secure Connections Pairing only”, otherwise Excluded.
- C.8: Optional IF GAP 35a/1 “CS Mode-2”, otherwise Excluded.
- C.9: Optional IF (GAP 35a/3 “CS RTT Access Address, 10 ns” OR GAP 35a/4 “CS RTT Access Address, 150 ns” OR GAP 35a/5 “CS RTT Sounding Sequence, 10 ns” OR GAP 35a/6 “CS RTT Sounding Sequence, 150 ns” OR GAP 35a/7 “CS RTT Random Payload, 10 ns” OR GAP 35a/8 “CS RTT Random Payload, 150 ns”) AND GAP 35a/1 “CS Mode-2”, otherwise Excluded.
- C.10: Optional IF (GAP 35a/3 “CS RTT Access Address, 10 ns” OR GAP 35a/5 “CS RTT Sounding Sequence, 10 ns” OR GAP 35a/7 “CS RTT Random Payload, 10 ns”) AND GAP 35a/1 “CS Mode-2”, otherwise Excluded.
- C.11: Optional IF (GAP 35a/3 “CS RTT Access Address, 10 ns” OR GAP 35a/5 “CS RTT Sounding Sequence, 10 ns” OR GAP 35a/7 “CS RTT Random Payload, 10 ns”) AND GAP 35a/1 “CS Mode-2” AND (GAP 35a/9 “Phase-based Normalized Attack Detector Metric – Sounding Sequence” OR GAP 35a/10 “Phase-based Normalized Attack Detector Metric – Random Bit Sequence”), otherwise Excluded.
- C.12: Mandatory to support at least one IF GAP 33a/3 “Channel Sounding procedure for GAP Central”, otherwise Excluded.
- C.13: Optional IF GAP 35/8 “Unauthenticated Pairing (LE security mode 1 level 2)”, otherwise Excluded.
- C.14: Optional IF GAP 35/7 “Authenticated Pairing (LE security mode 1 level 3)”, otherwise Excluded.
- C.15: Optional IF CORE 2b/62 “Host Core v6.2 or earlier”, otherwise Excluded.

Table 35a: Channel Sounding Features

Prerequisite: GAP 5/4 “Central” AND GAP 33a/3 “Channel Sounding procedure for GAP Central”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	CS Mode-2	[16] 10.11	M	[16] LL 13/2
2	CS Mode-3	[16] 10.11	O	[16] LL 13/3
3	CS RTT Access Address, 10 ns	[16] 10.11.1	C.1	[16] LL 13/4
4	CS RTT Access Address, 150 ns	[16] 10.11.1	C.1	[16] LL 13/5
5	CS RTT Sounding Sequence, 10 ns	[16] 10.11.1	C.2	[16] LL 13/6
6	CS RTT Sounding Sequence, 150 ns	[16] 10.11.1	C.2	[16] LL 13/7
7	CS RTT Random Payload, 10 ns	[16] 10.11.1	C.3	[16] LL 13/8
8	CS RTT Random Payload, 150 ns	[16] 10.11.1	C.3	[16] LL 13/9

Item	Capability	Reference	Status	Inter-Layer Dependency
9	Phase-based Normalized Attack Detector Metric – Sounding Sequence	[16] 10.11.1	O	[17] CS 2/14a
10	Phase-based Normalized Attack Detector Metric – Random Bit Sequence	[16] 10.11.1	O	[17] CS 2/14b

- C.1: Mandatory to support one and only one.
C.2: Optional to support one and only one.
C.3: Optional to support one and only one.

Table 35b (auto-fill): Central Security Levels Satisfaction*Prerequisite: GAP 5/4 “Central”*

Item	Capability	Reference	Status
1	Satisfies LE security mode 1 level 2	[4] 10.2.1	C.1
2	Satisfies LE security mode 1 level 3	[4] 10.2.1	C.2
3	Satisfies LE security mode 1 level 4	[5] 10.2.1	C.3

- C.1: Mandatory IF GAP 35/7 “Authenticated Pairing (LE security mode 1 level 3)” OR GAP 35/8 “Unauthenticated Pairing (LE security mode 1 level 2)” OR GAP 35/9 “LE security mode 1 level 4”, otherwise Excluded.
C.2: Mandatory IF GAP 35/7 “Authenticated Pairing (LE security mode 1 level 3)” OR GAP 35/9 “LE security mode 1 level 4”, otherwise Excluded.
C.3: Mandatory IF GAP 35/9 “LE security mode 1 level 4”, otherwise Excluded.

2.3.4.8 Privacy Feature

Table 36: Central Privacy Feature*Prerequisite: GAP 5/4 “Central”*

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Privacy feature	[5] 10.7	O	N/A
2	Non-resolvable private address generation procedure	[5] 10.7, 10.8.2.1 [6] 1.3.2.2	O	N/A
3	Resolvable private address resolution procedure	[5] 10.7, 10.8.2.3 [6] 1.3.2.2	C.1	N/A
4	No longer used	N/A	N/A	N/A
5	Resolvable private address generation procedure	[5] 10.7, 10.8.2.2 [6] 1.3.2.3	C.1	N/A
6	Controller-based privacy	[5] 10.7	O	N/A
7	LL Privacy	[5] 10.7 [6] 6	C.2	[15] LL 9/13

- C.1: Mandatory IF GAP 36/1 “Privacy feature”, otherwise Optional.
C.2: Mandatory IF GAP 36/1 “Privacy feature”, otherwise not defined.



2.3.4.9 Generic Access Profile Characteristics

Table 37: Central GAP Characteristics

Prerequisite: GAP 5/4 “Central”

Item	Capability	Reference	Status
1	Device Name	[2] 12.1	M
2	Appearance	[2] 12.2	M
3	Central Address Resolution	[5] 12.4	C.5
3a	No longer used	N/A	N/A
4	LE GATT Security Levels	[12] 12.7	C.6
5	Resolvable Private Address Only	[2] 12.5	C.2
6	Writable Device Name	[2] 12.1	C.3
7	Writable Appearance	[2] 12.2	C.4

C.1: No longer used.

C.2: Mandatory IF GAP 4b/5 “Resolvable Private Address Only” OR GAP 27/12 “Resolvable Private Address Only”, otherwise Optional IF GAP 36/6 “Controller-based privacy”, otherwise Excluded.

C.3: Mandatory IF GAP 4b/8 “Writable Device Name” OR GAP 27/6 “Writable Device Name”, otherwise Optional.

C.4: Mandatory IF GAP 4b/9 “Writable Appearance” OR GAP 27/7 “Writable Appearance”, otherwise Optional.

C.5: Mandatory IF GAP 4b/4 “Central Address Resolution” OR GAP 27/9 “Central Address Resolution” OR GAP 36/6 “Controller-based privacy”, otherwise Excluded.

C.6: Mandatory IF GAP 27/11 “LE GATT Security Levels”, otherwise Optional.

2.3.4.10 Periodic Advertising Modes and Procedures

Table 37a: Periodic Advertising Modes and Procedures

Prerequisite: GAP 5/4 “Central” AND CORE 2a/51 “Host Core v5.1 or later”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Periodic Advertising Synchronization Transfer procedure	[8] 9.5.4	O	N/A
2	Periodic Advertising Synchronization Establishment procedure over an LE connection without listening for periodic advertising	[8] 9.5.3	O	N/A
3	Periodic Advertising Synchronization Establishment procedure over an LE connection with listening for periodic advertising	[8] 9.5.3	O	N/A
4	Periodic Advertising Sync Transfer - Sender	[8] 9.5.4	C.1	[15] LL 9/26
5	Periodic Advertising Sync Transfer - Recipient	[8] 9.5.3	C.2	[15] LL 9/27
6	Synchronizing to Periodic Advertising	[8] 9.5.3	C.3	[15] LL 11/1

- C.1: Mandatory IF GAP 37a/1 “Periodic Advertising Synchronization Transfer procedure”, otherwise not defined.
- C.2: Mandatory IF GAP 37a/2 “Periodic Advertising Synchronization Establishment procedure over an LE connection without listening for periodic advertising” OR GAP 37a/3 “Periodic Advertising Synchronization Establishment procedure over an LE connection with listening for periodic advertising”, otherwise not defined.
- C.3: Mandatory IF GAP 37a/3 “Periodic Advertising Synchronization Establishment procedure over an LE connection with listening for periodic advertising”, otherwise not defined.

2.3.4.11 SM requirements

Table 37b: SM Requirements

Prerequisite: GAP 5/4 “Central”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Central Role (Initiator)	N/A	M	[13] SM 1/1
2	Authenticated MITM protection	[4] 10.3	C.1	N/A
3	Unauthenticated no MITM protection	[4] 10.3	C.2	N/A
4	No security requirements	[4] 10.2.1	C.3	N/A
5	LE Secure Connections	[4] 10.2.1	C.4	N/A
6	Long Term Key (LTK)	[4] 9.4.3	C.5	[13] SM 7a/1
7	Identity Resolving Key (IRK)	[4] 10.7	C.6	[13] SM 7a/2
8	Connection Signature Resolving Key (CSRK)	[4] 10.4	C.7	[13] SM 7a/3
9	Out of Band	[4] 10.4	O	[13] SM 4a/3 OR SM 4b/3
10	Legacy pairing	[4] 10.3	C.8	[13] SM 2a/1
11	LE Secure Connection pairing	[4] 10.3	C.4	[13] SM 2a/2

- C.1: Mandatory IF GAP 35/7 “Authenticated Pairing (LE security mode 1 level 3)” OR GAP 35/12 “Authenticated Pairing (LE security mode 1 level 3) with LE Secure Connections Pairing only” OR (GAP 35/2 “LE security mode 2” AND GAP 35/3 “Authentication procedure”), otherwise Excluded.
- C.2: Mandatory IF GAP 35/8 “Unauthenticated Pairing (LE security mode 1 level 2)” OR GAP 35/11 “Unauthenticated Pairing (LE security mode 1 level 2) with LE Secure Connections Pairing only” OR (GAP 35/2 “LE security mode 2” AND NOT GAP 35/3 “Authentication procedure”), otherwise Excluded.
- C.3: Mandatory IF GAP 35/1 “LE security mode 1” AND NOT GAP 35/8 “Unauthenticated Pairing (LE security mode 1 level 2)” AND NOT GAP 35/7 “Authenticated Pairing (LE security mode 1 level 3)” AND NOT GAP 35/9 “LE security mode 1 level 4”, otherwise Optional IF GAP 35/1 “LE security mode 1”, otherwise Excluded.
- C.4: Mandatory IF GAP 35/9 “LE security mode 1 level 4” OR GAP 35/11 “Unauthenticated Pairing (LE security mode 1 level 2) with LE Secure Connections Pairing only” OR GAP 35/12 “Authenticated Pairing (LE security mode 1 level 3) with LE Secure Connections Pairing only”, otherwise not defined.
- C.5: Mandatory IF GAP 34/2 “Bondable mode”, otherwise not defined.
- C.6: Mandatory IF GAP 36/5 “Resolvable private address generation procedure”, otherwise not defined.

- C.7: Mandatory IF GAP 35/6 “Authenticate signed data procedure”, otherwise not defined.
- C.8: Mandatory IF GAP 35/2 “LE security mode 2” OR GAP 35/7 “Authenticated Pairing (LE security mode 1 level 3)” OR GAP 35/8 “Unauthenticated Pairing (LE security mode 1 level 2)”, otherwise not defined.

2.3.4.12 L2CAP requirements

Table 37c (auto-fill): L2CAP Requirements

Prerequisite: GAP 5/4 “Central”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	Detect insufficient authentication	[2] 10.3	C.1	[14] L2CAP 4/1
2	Detect insufficient authorization	[2] 10.5	C.2	[14] L2CAP 4/2
3	Detect insufficient encryption	[2] 2.2.2	C.3	[14] L2CAP 4/3

- C.1: Mandatory IF GAP 35/3 “Authentication procedure”, otherwise not defined.
- C.2: Mandatory IF GAP 35/4 “Authorization procedure”, otherwise not defined.
- C.3: Mandatory IF GAP 31/3 “Encryption procedure”, otherwise not defined.

2.4 BR/EDR/LE Capability Statement

Tables 38–40: No longer used

2.4.1 Central

2.4.1.1 Security Aspects

Table 41: Central BR/EDR/LE Security Aspects

Prerequisite: GAP 0b/1 “GAP BR/EDR Host” AND GAP 5/4 “Central”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	No longer used	N/A	N/A	N/A
2	Cross Transport Key Derivation Supported	[4] 14.1	C.1	[13] SM 8a/1
2a	Derivation of BR/EDR Link Key from LE LTK	[4] 14.1	C.2	[13] SM 8a/3
2b	Derivation of LE LTK from BR/EDR Link Key	[4] 14.1	C.3	[13] SM 8a/2

- C.1: Mandatory IF GAP 41/2a “Derivation of BR/EDR Link Key from LE LTK” AND GAP 41/2b “Derivation of LE LTK from BR/EDR Link Key”, otherwise not defined.
- C.2: Optional IF GAP 35/9 “LE security mode 1 level 4”, otherwise not defined.
- C.3: Optional IF GAP 2/7a “Security mode 4, level 4”, otherwise not defined.

2.4.1.2 Simultaneous Transports

Table 44: Central Simultaneous BR/EDR and LE Transports

Prerequisite: GAP 0b/1 “GAP BR/EDR Host” AND GAP 5/4 “Central”

Item	Capability	Reference	Status
1	Simultaneous BR/EDR and LE Transports – BR/EDR Peripheral to the same device	[4] 13.1.1	O
2	Simultaneous BR/EDR and LE Transports – BR/EDR Central to the same device	[4] 13.1.1	O

2.4.2 Peripheral

Table 42: No longer used

2.4.2.1 Security Aspects

Table 43: Peripheral BR/EDR/LE Security Aspects

Prerequisite: GAP 0b/1 “GAP BR/EDR Host” AND GAP 5/3 “Peripheral”

Item	Capability	Reference	Status	Inter-Layer Dependency
1	No longer used	N/A	N/A	N/A
2	Cross Transport Key Derivation Supported	[4] 14.1	C.1	[13] SM 8b/1
2a	Derivation of BR/EDR Link Key from LE LTK	[4] 14.1	C.2	[13] SM 8b/3
2b	Derivation of LE LTK from BR/EDR Link Key	[4] 14.1	C.3	[13] SM 8b/2

C.1: Mandatory IF GAP 43/2a “Derivation of BR/EDR Link Key from LE LTK” AND GAP 43/2b “Derivation of LE LTK from BR/EDR Link Key”, otherwise not defined.

C.2: Optional IF GAP 25/9 “LE security mode 1 level 4”, otherwise not defined.

C.3: Optional IF GAP 2/7a “Security mode 4, level 4”, otherwise not defined.

2.4.2.2 Simultaneous Transports

Table 45: Peripheral Simultaneous BR/EDR and LE Transports

Prerequisite: GAP 0b/1 “GAP BR/EDR Host” AND GAP 5/3 “Peripheral”

Item	Capability	Reference	Status
1	Simultaneous BR/EDR and LE Transports – BR/EDR Peripheral to the same device	[4] 13.1.1	O
2	Simultaneous BR/EDR and LE Transports – BR/EDR Central to the same device	[4] 13.1.1	O

3 Bridge mapping (informational)

Table 3.1 provides the mapping between new and old ICS items that had a part in past TCRL releases. An implementation qualified under an older TCRL release will use the bridge mapping to indicate support of the new ICS item, which is missing from the old TCRL release. The mapping can change depending on the older TCRL release. For newer TCRL releases, the bridge mapping table is not applicable.

New ICS item	Description	Mapping from Old ICS Item
GAP 0b/1	GAP BR/EDR Host	≥ TCRL pkg101: Not applicable ≤ TCRL pkg100: GAP 0/1 OR GAP 0/3
GAP 0b/2	GAP LE Host	≥ TCRL pkg101: Not applicable ≤ TCRL pkg100: GAP 0/2 OR GAP 0/3
GAP 5/1	Broadcaster	≥ TCRL pkg101: Not applicable ≤ TCRL pkg100: GAP 5/1 OR GAP 38/1
GAP 5/2	Observer	≥ TCRL pkg101: Not applicable ≤ TCRL pkg100: GAP 5/2 OR GAP 38/2
GAP 5/3	Peripheral	≥ TCRL pkg101: Not applicable ≤ TCRL pkg100: GAP 5/3 OR GAP 38/3
GAP 5/4	Central	≥ TCRL pkg101: Not applicable ≤ TCRL pkg100: GAP 5/4 OR GAP 38/4
GAP 6/3	LE 2M PHY	≥ TCRL pkg103: Not applicable < TCRL pkg103: RFPHY 1/4 < TCRL 2016-2: Not supported (< Core v5.0)
GAP 7/3a	Isochronous Broadcaster	≥ TCRL pkg103: Not applicable < TCRL pkg103: LL 9/33 < TCRL 2019-2: Not supported (< Core v5.2)
GAP 7/3b	Encrypted Broadcast Isochronous Stream	≥ TCRL pkg103: Not applicable < TCRL pkg103: LL 12/1 < TCRL 2019-2: Not supported (< Core v5.2)
GAP 7/3c	Unencrypted Broadcast Isochronous Stream	≥ TCRL pkg103: Not applicable < TCRL pkg103: LL 12/2 < TCRL 2019-2: Not supported (< Core v5.2)
GAP 8/6	LE Periodic Advertising	≥ TCRL pkg103: Not applicable < TCRL pkg103: LL 9/42 < TCRL 2019-2: Not supported (< Core v5.2)
GAP 8b/1	LE Encryption	≥ TCRL pkg103: Not applicable < TCRL pkg103: LL 9/1
GAP 11/6	LL Privacy	≥ TCRL pkg103: Not applicable < TCRL pkg103: LL 9/13 < TCRL 2017-2: Not supported (< Core v5.0)
GAP 12/3	LE 2M PHY	≥ TCRL pkg103: Not applicable < TCRL pkg103: RFPHY 1/4 < TCRL 2016-2: Not supported (< Core v5.0)
GAP 13/3	Synchronization State	≥ TCRL pkg103: Not applicable < TCRL pkg103: LL 1/3a < TCRL 2018-2: Not supported (< Core v5.1)

New ICS item	Description	Mapping from Old ICS Item
GAP 13/3a	Synchronized Receiver	≥ TCRL pkg103: Not applicable < TCRL pkg103: LL 9/34 < TCRL 2019-2: Not supported (< Core v5.2)
GAP 14b/1	LE Encryption	≥ TCRL pkg103: Not applicable < TCRL pkg103: LL 9/1
GAP 17/6	LL Privacy	≥ TCRL pkg103: Not applicable < TCRL pkg103: LL 9/13 < TCRL 2017-2: Not supported (< Core v5.0)
GAP 18/3	LE 2M PHY	≥ TCRL pkg103: Not applicable < TCRL pkg103: RFPHY 1/4 < TCRL 2016-2: Not supported (< Core v5.0)
GAP 20/9	LE Periodic Advertising	≥ TCRL pkg103: Not applicable < TCRL pkg103: LL 9/42 < TCRL 2019-2: Not supported (< Core v5.2)
GAP 21/3a	LE Encryption	≥ TCRL pkg103: Not applicable < TCRL pkg103: LL 9/1
GAP 23/8a	Shorter Connection Intervals	≥ TCRL pkg103: Not applicable < TCRL pkg103: LL 9/69 < TCRL p101: Not supported (< Core v6.1)
GAP 27b/11	Legacy pairing	≥ TCRL p101: Not applicable ≤ TCRL p100: GAP 25/2 OR GAP 25/7 OR GAP 25/8
GAP 27b/12	LE Secure Connection pairing	≥ TCRL p101: Not applicable ≤ TCRL p100: GAP 25/9 OR GAP 25/11 OR GAP 25/12
GAP 28/3	LE 2M PHY	≥ TCRL pkg103: Not applicable < TCRL pkg103: RFPHY 1/4 < TCRL 2016-2: Not supported (< Core v5.0)
GAP 31/3a	LE Encryption	≥ TCRL pkg103: Not applicable < TCRL pkg103: LL 9/1
GAP 33/9a	Shorter Connection Intervals	≥ TCRL pkg103: Not applicable < TCRL pkg103: LL 9/69 < TCRL p101: Not supported (< Core v6.1)
GAP 36/7	LL Privacy	≥ TCRL pkg103: Not applicable < TCRL pkg103: LL 9/13 < TCRL 2017-2: Not supported (< Core v5.0)
GAP 37b/10	Legacy pairing	≥ TCRL p101: Not applicable ≤ TCRL p100: GAP 35/2 OR GAP 35/7 OR GAP 35/8
GAP 37b/11	LE Secure Connection pairing	≥ TCRL p101: Not applicable ≤ TCRL p100: GAP 35/9 OR GAP 35/11 OR GAP 35/12

Table 3.1: Bridge mapping (informational)

4 References

- [1] Specification of the Bluetooth System, Volume 3, Part C (Generic Access Profile), Version 2.1 or later
- [2] Specification of the Bluetooth System, Volume 3, Part C, Version 4.0 or later
- [3] Core Specification Supplement (CSS), Part A, Current Version
- [4] Specification of the Bluetooth System, Volume 3, Part C, Version 4.1 or later
- [5] Specification of the Bluetooth System, Volume 3, Part C, Version 4.2 or later
- [6] Specification of the Bluetooth System, Volume 6, Part B (Link Layer Specification)
- [7] Specification of the Bluetooth System, Volume 3, Part C, Version 5.0 or later
- [8] Specification of the Bluetooth System, Volume 3, Part C, Version 5.1 or later
- [9] Core Erratum 11838 Key Size Updates
- [10] Specification of the Bluetooth System, Volume 3, Part C, Version 5.2
- [11] Specification of the Bluetooth System, Volume 3, Part C, Version 5.3 or later
- [12] Specification of the Bluetooth System, Volume 3, Part C, Version 5.4 or later
- [13] ICS Proforma for Security Manager (SM)
- [14] ICS Proforma for Logical Link Control and Adaptation Protocol (L2CAP)
- [15] ICS Proforma for Link Layer (LL)
- [16] Specification of the Bluetooth System, Volume 3, Part C, Version 6.0 or later
- [17] ICS Proforma for Channel Sounding (CS)
- [18] ICS Proforma for Link Manager Protocol (LMP)
- [19] ICS Proforma for Baseband (BB)
- [20] ICS Proforma for Radio Physical Layer (RFPHY)

5 Revision history and acknowledgments

Revision History

Publication Number	Revision Number	Date	Comments
	D10R00	2004-03-10	Re-partitioned to match Main Specification Volume/Part partitioning.
	D10r01	2004-03-11	Editorial changes.
	D12r02	2004-03-23	Editorial changes. Changed reference and document numbering to D12 to reflect applicable Bluetooth version.
	D12r03	2004-03-25	Editorial changes.
10	1.2.2	2004-03-29	Changed document number and revision number to conform to legacy system. Added Disclaimer and Copyright Notice.
11	1.2.3	2005-01-13	Release after review.
	1.2.4r0	2005-09-20	Changed cover page to refer 1.2/2.0/2.0+EDR
12	1.2.4	2005-11-09	Prepare for publication.
	2.1.E.0r0	2006-11-29	Updates to Table 2 and Table 3 for Simple Pairing
	2.1.E.0r1	2006-12-14	Changed document number, updates to Table 2 status and footnotes
13	2.1.E.0	2006-12-28	Prepare for publication.
	2.1.E.1r0	2008-02	TSE 2279: Table 2 C1 and C2 TSE 2283: Table 2, Note 3. TSE 2289: Table 3: C1 change
14	2.1.E.1	2008-04-29	Publication version.
	2.1.E.2r0-1	2008-10-08/29	TSE 2638, TSE 2631, TSE 2494; Add rows to Table 2.
15	2.1.E.2	2008-12-12	Prepare for publication.
	2.1.E.2a	2009-04-21	Update conditionals to reflect the addition of Core Specification 3.0/3.0+HS
16	2.1.E.3	2009-08-12	TSE 2649: Change Table 2 Footnote C.7 TSE 2979: Table 2 Footnote C.4 updated.
17	4.0.0d4 d12	2010-06-09 – 2010-07-01	Document merge between GAP ICS 2.1.E.3 and LE specific GAP ICS called 0.9d3 dated 2010-06-09 References to Volume 3 Part C versions 2.0 or later [1] separated from references to Volume 3 Part C versions 4.0 or later [2]. TSE3788 “Pairable” changed to “Bondable” in table 1 Updated BR/EDR/LE ICS to align with the latest errata in Tokyo v13 Updated BR/EDR/LE ICS with review comment resolution Updated BR/EDR/LE ICS with review comment resolution SUM ICS references added to 0/x- conditions Change in C.1, table 22

Publication Number	Revision Number	Date	Comments
			Table 38, informative note removed – created more problems than it solved 0/3 added as a prerequisite in section 1.4 BR/EDR/LE Central and Peripheral prerequisite added to relevant ICS sub-sections of section 1.4 LE Capability Statement. 0/3 is no longer a prerequisite in section 1.4. Comment resolutions to the addition of the BR/EDR/LE Central and Peripheral prerequisites. Corrections, where prerequisites were transferred to conditions in tables 18-24, 28-37 Corrected confusion around multiple C.1 in table 34 Update contributors list
	4.0.1r0-r3	2010-10-09 – 2011-03-09	TSE 3289: Changed IF 2/6...to IF 2/7... TSE 3849: Table 22: Footnote C1: TSE 3848: Table 20/C.3: Change M to O TSE 3788: Table 1/6 and 1/7: rename TSE 3862: Add Tables 8A and 20A TSE 4090: Table 20, footnote C.3 (same change as TSE 3848) TSE 4116: Table 25, Add item 7 Input MS review comments: TSE 4116 (was made only to test spec) TSE 4244: Delete Annex A TSE 4245: Add pre-requisite “Prerequisite: GAP 5/3” to the following tables 18, 19, 20, 20A, 22, 23, 24 Add prerequisite 5/4 from tables 27 to 38 Input SL’s comments: TSE 3849: fix footnote, fix Rev. His. TSE 4305: Add prerequisite: “GAP 5/3 or GAP 38/3” to Tables: 18, 19, 20, 20A, 21, 22, 23, 24, 25, 26 & 27 ; Add prerequisite: “GAP 5/4 or GAP 38/4” to Tables: 28, 29, 30, 31, 32, 33, 34, 35, 36 & 37
18	4.0.1	2011-07-20	Prepare for publication. Add Reference section in place of Section 1 text.
	4.0.2r0	2011-11-21	TSE 4560 Table 27: Two new rows TSE 3865: Same as 3955—TPG only? TSE 4330: Change prerequisites for 1.4, Tables 6 – 11, and Tables 12-17 TSE 4451: Change Table 27 C.2 to refer to correct table TSE 4561: Table 2 References and Note 3.
	4.0.2r1	2012-01-31	TSE 4330: Update Prerequisite for Table 8
19	4.0.2	2012-03-30	Changed wording in §1.1.1. Prepare for publication

Publication Number	Revision Number	Date	Comments
	4.0.3r0	2012-05-16	TSE 4568 Table 24: add row 4 and footnote C.3 TSE 4573 Table 25, add row 8 and footnote C.1; Table 35, change status from C.1 to O, add rows 7 and 8; modify footnote C.1 TSE 4740: Change Table 2/3 and Table 2/10 TSE 4741: Add 27/8 and 36/4 TSE 4751: Table 5, Table 38: Change titles, add notes. Table 38: Change O to C.1 and add conditional footnote.
	4.0.3r1	2012-06-11	Editorial updates for TSE 4741 Table 0a introduced for CSA3 declaration and requirements. C.2 updated in Table 27 to address errata 4202 requirements.
20	4.0.3	2012-07-24	Prepare for publication.
	4.0.4r0	2012-10-10	TSE 4966: Update to conditionals in Table 17 and addition of Item 4. TSE 4873: Added conditional to Table 8 A and Table 20A.
	4.0.4r1	2012-11-29	Per BQRB review: Added [3] Core Specification Supplement (CSS) v2, Part A Add section reference to [3] in table 8A and table 20A
	4.0.4r2	2012-12-05	TSE 5033: Correction to Table 20A conditionals to remove Connected Directed Event and Add Scannable Undirected Event.
21	4.0.4	2012-11-29	Prepare for Publication
	4.0.5r1	2012-12-21	Connectionless Broadcast Change Request
	4.0.5r2	2013-01-02	Connectionless Broadcast Review: Table 1 revised C.4 conditional Table 4, revised C.1 conditional
	4.0.5r3	2013-01-03	Connectionless Broadcast Review: Table 1/9 synchronizable mode edit to conditional C.4.
	4.0.5r4	2013-01-22	Connectionless Broadcast Review (Jason & Magnus) Added "...or later" after CSA4 conditionals Update to References Section, added CSA3 and CSA4 cross-references
	4.0.5r5	2013-01-24	Connectionless Broadcast Review (Jason, Alicia, Meagan) Edited for consistent language and syntax for conditionals.
22	4.0.5	2013-02-12	Prepare for Publication
	4.0.6r1	2013-02-13	Editorial error in Table 17. C.1 Conditional corrected to read 17/1 (Privacy Feature). C.1 and C.3 edited for clarity. Approved by BTI & BQRB
23	4.0.6	2013-02-19	Prepare for Publication

Publication Number	Revision Number	Date	Comments
	4.0.7r1	2013-05-30	TSE 5063: •Updated title of section 1.4 to “LE Only Capability Statement” •Removed conditionals from Table 19, already covered in the prerequisite. All items changed to Mandatory. •Removed conditionals from Table 20, already covered in the prerequisite. Item 1 and 4 changed to Mandatory, Item 2 and 3 as optional. •Updated conditionals for Table 22, removed “AND (20/1 OR 20/3 OR 20/4) from C.1, and updated parenthesis and language in C.2 and C.3. •Removed C.1 and C.2 from Table 23, updated C.3 to be C.1. Item 1 status changed to C.1, items 2 and 4 changed to optional, and items 3 and 5 updated to Mandatory. TSE 5091: Updated Table 20A item 6 status to C.3, added “C.2: Mandatory if 22/2 or 22/3 is supported, otherwise Optional” C.2 had been included in an earlier version and was still needed, former C.2 became C.3. TSE 5100: Updated C.4 in Table 2 to remove “SUM ICS 31/5” because the item no longer exists.
	4.0.7r2	2013-06-04	Fixed the TSE reference number in the Change History. Table 0a – changed Device to Version Configuration to match the Table title. Added the ICS item description in parenthesis to conditionals where it wasn't yet indicated for consistency and clarity: Tables 1-3, 20A, 22-25, 30, 32-36. Table 2: Further review of TSE 5100 showed there was a missing ICS item that needed adding due to the Sum ICS re-shuffle: SUM ICS 31/11 (Core Specification 4.0 + HS). Updated C.4 with this item. Table 3 conditional C.1 had 2 references to GAP 3/1 it is an obvious mistake that one should say 3/2. In Tables that had been updated for the pre-requisites affected by previous TSE's 4330 and 4305 consistent with changes in TSE 5063 changed the pre-requisites that stated either Optional or Mandatory to Support based on the support of the Table's pre-requisites to simply “M” or “O”: Tables 18, 28, 29, 30, 31, 34, 36, and 37. Simplified conditionals by removing the pre-requisite items from the conditionals leaving only the dependencies in Table 30 item C.1 and Table 36 items C.1 and C.2. Misc. editorial changes.
24	4.0.7	2013-07-02	Prepare for Publication
	4.0.8rT	2013-08-01	Template Conversion

Publication Number	Revision Number	Date	Comments
	4.0.8rTr4	2013-09-24	Template Conversion Comment Resolution
	4.1.0r01	2013-09-24	BR/EDR Secure Connections CR
	4.1.0r02	2013-09-25	Low Duty Cycle Directed Advertising CR
	4.1.0r03	2013-09-25	LE Privacy 1.1 CR
	4.1.0r04	2013-09-26	TSE 5288: Revised conditional statement C.3 in Table 1.
	4.1.0r05	2013-10-04	LE Dual Mode Topology CR
	4.1.0r06	2013-10-09	LE Ping CR
	4.1.0r07	2013-10-14	LE Link Layer Topology CR
	4.1.0r13	2013-10-31	Fixed C.1 in Table 11
	4.1.0.r14	2013-11-10	Added new item 3 in Table 0a to allow mandate CSA.3 centric changes for GAP Authentication and Lot Bond, Private Address Changes, Connection Parameters Changes and Dual Mode Addressing Changes absorbed in Core v4.1. Introduced to allow GAP.TS TCMT to remove SUM ICS references.
25	4.1.0	2013-12-03	Prepare for Publication
	4.1.1r00	2014-01-23	TSE 5477: Corrected Reference for 44/1, 44/2, and 45/1. Corrected Prerequisite for Table 45, from GAP 38/4 to GAP 38/3. TSE 5463: Updated Table 36, C.1.
	4.1.1r01	2014-04-04	TSE 5579: Added 4.1 and 4.1 + HS references to conditionals and updated from otherwise Optional to otherwise Excluded for all conditionals in Table 39, Table 40, and Table 42.
	4.1.1r02	2014-04-04	TSE 5561: Updated Table 0a C.3.
26	4.1.1	2014-07-07	TCRL 2014-1 Publication
	4.1.2r00	2014-10-17	TSE 5652: Added C.2 to Table 8A. Updated 8A/3 from M to C.2. TSE 5765: Table 26, C.2, Corrected item reference for Privacy Feature v1.1 to be 26/1a instead of 26/2. TSE 5781: Updated Table 25 C.2 to include 31/10 and 31/10a. TSE 5944: Removed 20/2a, updated to Item no longer used, Removed C.3.
	4.1.2r01	2014-10-30	TSE 5633: Updated status of 23/4 from C.2 to C.1.
	4.2.0r00	2014-11-14	Integrated Section 1.3 of Core_Enhanced_Privacy_1_2.TS.CR.R05 & Section 5 of Core_LE_Secure_Connections.TS.CR.R16
	4.2.0r01	2014-11-21	Integrated comments from Rasmus, Jason, and Mayank, and added Privacy CR changes.
	4.2.0r02	2014-11-24	Updated Table 11 after further review from Jason.
	4.2.0r04	2014-11-25	BTI Rejected TSE 5781. Changes from that TSE undone and conditionals updated. Updated 0a Conditionals
27	4.2.0	2014-12-03	Prepare for TCRL 2014-2 publication

Publication Number	Revision Number	Date	Comments
	4.2.1r00	2015-05-08	TSE 6259: Corrected typos in C.4 of Table 21 TSE 6130: Deleted tables 39, 40, and 42.
	4.2.1r01	2015-05-18	Reinstated tables 39, 40, and 42. Implemented changes from TSE 6130 by removing SUM ICS references to 4.1 or later in those tables and extending prerequisite statements.
	4.2.1r02	2015-06-05	Deleted Section 1.2 (Global Statement of Conformance) per current ICS template standards.
	4.2.1r03	2015-06-08	Adjusted section numbering following deletion of Section 1.2 at 4.2.1r02.
	4.2.1r04	2015-06-22	Integrated changes from Core Specification Supplement v6. Advertising URI: Added items to tables 8A and 20A. Efficient Non-Connectable Advertising: Revised C.2 in Table 8A.
	4.2.1r05	2015-06-23	Revised CSSv6 changes to account for corresponding updates to SUM ICS.
28	4.2.1	2015-07-14	Prepared for TCRL 2015-1 publication
	4.2.2r00	2015-10-09	TSE 6485: Split item 41/2 into two items and 43/2 into two items. TSE 6169 & 6323: Rewrote Tables 11, 17, 26, 27, 36, 37 and corresponding conditionals to resolve issues with Privacy feature.
29	4.2.2	2015-12-22	Prepared for TCRL 2015-2 publication.
	5.0.0r00	2016-10-03	Issue 7732: Added new item support for Bluetooth Core Specification v5.0 and new conditional C.5 to Table 0a. Added two new tables 11a and 17a for Periodic Advertising Modes and Procedures. Added new reference for Bluetooth Core Specification v.5.0 to References section.
	5.0.0r01	2016-10-13	TSE 7297: Updated conditional C.3 for Table 27. TSE 7058: Updated conditionals in Tables 24 (C.1), 33 (C.1), and 34 (C.2).
	5.0.0r02	2016-11-08	Issue 7872: Corrected reference in 0a/5 from [1] to [11].
	5.0.0r03	2016-11-10	Issue 7803: Added two new items 8/3 and 8/4 and conditional C.1 to Table 8. Added three items 20/5, 20/6, and 20/7 and conditional C.3 to Table 20. Modified items 20/1 and 20/3. Updated conditionals for Table 20A. Issue 7884: Global edit. Added support in conditionals and prerequisites for Core Spec version 5.0.
	5.0.0r04	2016-11-16	Updated to current template. Removed unnecessary parentheses and replaced with quotation marks. Simplified the “or later” issue in Tables 39, 40, and 42 by revising the Conditionals to exclude anything other than Core Spec v4.0 or 4.0+HS and added the informative note.

Publication Number	Revision Number	Date	Comments
	5.0.0r05	2016-11-16	Updated references and conditionals for Core Specification Supplement (CSS) v7.
	5.0.0r06	2016-11-17	Simplified conditionals in Tables 39, 40 and 42 by adding a prerequisite requirement for 4.0 support.
30	5.0.0	2016-12-13	Prepared for TCRL 2016-2 publication
	5.0.1r00	2017-02-16	TSE 7816: Added new item GAP 2/7a. Added new conditional statement, C.9. Updated conditional statement C.8. TSE 8704: Revised Table 42 prerequisite by adding "GAP 38/3 "Peripheral BR/EDR/LE" AND".
	5.0.1r01	2017-05-04	TSE 7816: Fixed cross references to 5.0 and odd hidden formatting. Made font size uniform within the tables and Change History. Removed extra row in the Change History that didn't add any material information. Enhanced the change History where it was stated that "rows were added" which might explain what a tech editor did but what someone looking at the Change History would rather know is that items 20/3, 20/4, and 20/5 were added. Updated copyright/disclaimer.
31	5.0.1	2017-07-05	Approved by BTI. Prepared for TCRL 2017-1 publication.
	5.0.2r00	2017-08-22	TSE 9678: Revised Security Aspects table note C.9.
	5.0.2r01	2017-10-13	TSE 9937: Added LL control procedures to Tables 21 and 31.
32	5.0.2	2017-12-07	Approved by BTI. Prepared for TCRL 2017-2 publication.
	5.0.3r00	2018-07-17	Incorporated Core_PAST_CLE_TEST_CR_r05: Modified conditional note C.1 for Table 17a. Added 2 new sections, both titled "Periodic Advertising Modes and Procedures," as well as Tables 27a and 37a, to sections "Peripheral" and "Central," respectively.
	5.0.3r01	2018-10-04	Drafted changed for deprecation and withdrawal. Affects 27/3-4 and 27/8 as well as 0a/1 and 0a/2.
	5.0.3r02	2018-11-12	Replaced TBD and [X] values with actual values. Added new reference for Bluetooth Core Specification version 5.1.
	5.0.3r03	2018-11-13	Updated Madrid styles – changed light grey text to black text.
	5.1.0r00	2018-11-13	Updated revision number to 5.1.0 to align with the adoption of Core Specification version 5.1.
	5.1.0r01	2018-11-16	Added entry 0a/6 for Core Specification version 5.1 and updated conditionals to include the new version.
	5.1.0r02	2018-11-19	Corrected implementation of conditionals referencing 5.1.
	5.1.0r03	2018-11-20	Added item 0a/0a for Core 4.0 and updated Table 17a/C.1 as well as the prerequisites for 27a and 37a with the new item.

Publication Number	Revision Number	Date	Comments
	5.1.0r04	2018-11-21	Marked C.5 of Table 21 and C.3 of Table 31 as no longer used (as they duplicated C.3 and C.1, respectively). Updated the status for the two items referencing those conditionals.
33	5.1.0	2018-12-07	Approved by BTI. Prepared for TCRL 2018-2 publication.
	5.1.1r00–r01	2019-04-09 – 2019-07-18	TSE 11552 (rating 2): Removed ICS items that are no longer applicable to Specifications 4.2 or later. Simplified conditionals. Updated, simplified, or removed tables throughout. Moved Revision History and Contributors tables to the end of the document. Incorporated changes associated with Key Negotiation Changes specification erratum 11838: Added new ICS entry to Table 2 (item 12) to indicate if the IUT enforces a minimum encryption key size of 56 bits.
34	5.1.1	2019-08-01	Approved by BTI. Prepared for TCRL 2019-1 publication.
	p35r00–r03	2019-08-06 – 2019-11-22	Added test groups to accommodate adoption of Core Specification v5.2 with regard to Isochronous Channels CR r20 (includes Issues 11742, 11762, 11777, 11778, 11779, 11783, 11786, 11804, 11817, 11819, 11820, 11852, 11917, 11919, 11928, 11929, 11930, 11983, 11740, 11801, 11941, 12029, 12030, 12043, 12052, 12053, 12054, 12055, 12059, 12061, 12071, 12072, 12073, 12077, 12084, 12031, 12078, 12094, 12095, 12106, 12107, 12130, 12132, 12133, 12251, 12280, and 12321). Added item 3 and note C.1 to Table 7; added items 2–5 and notes C.1 and C.2 to Table 10; added Section “Security Aspects” (1.4.1.7) and Table 11b; added items 2–4 and notes C.1 and C.2 to Table 16; added Section “Security Aspects” (1.4.2.7) and Table 17b; added items 6 and 7 and note C.1 to Table 23; added items 7 and 8 and note C.1 to Table 33; updated references section with new Core Specification. TSE 12751 (rating 1): Updated to SUM ICS 31 per TSE 12647 and made minor editorial updates, which included deleting Tables 0a, 39, 40, and 42; updating C.1 and C.2 for Table 1; updating item 12 and C.3 for Table 2; updating C.1 for Tables 7, 8, 11a, 11b, 16, 17a, 17b, and 20; updating C.2 for Tables 10, 21, and 31; and updating prerequisites for Tables 27a and 37a. Updated .X and Milan references to real numbers. Revised document numbering convention, setting last release publication of 5.1.1 as p34; added publication number column to Revision History.
35	p35	2020-01-07	Approved by BTI on 2019-12-22. Prepared for TCRL 2019-2 publication.

Publication Number	Revision Number	Date	Comments
	p36r00–r11	2020-01-23 – 2020-11-18	TSE 13341 (rating 4): Added items and conditionals to Tables 25 and 35 to accommodate allowing SM1L2 and SM1L3 to use LE Secure Connections pairing only. TSE 14862 (rating 1): Fixed references in Tables 7, 10, 11b, 16, 17b, 23, and 33 to align with GAP v5.2 spec. TSE 14950 (rating 2): Updated C.3 for Table 25 and C.2 for Table 35 to address issue with LE Security Mode 1 Level 4 being mandatory when LE Secure Connections is supported. TSE 14863 (rating 2): Updated C.1 in Tables 11b and 17b to address security mode issues. TSE 15150 (rating 4): To support new LE Audio Security Consideration requirements, updated Table 2, adding items 7b, 7c, 7d, and 13, and conditionals C.10 and C.11, and updating Status of item 12; updated Table 11b, adding items 2, 3, and 4, and conditional C.2; updated Table 17b, adding items 2, 3, and 4, and conditional C.2; updated Table 35, Capability text of items 11 and 12 to add "LE" and "Pairing"; updated Table 41 by adding conditionals C.1 and C.2 and updating status of items 2a and 2b, respectively; updated Table 43 by adding conditionals C.1 and C.2 and updating status of items 2a and 2b, respectively. TSE 15762 (rating 4): To address adding Minimum 128 Bit Key Size for the LE ICS entry, updated Table 25, modifying items 11 and 12 and adding item 13 and conditional C.5, and updated Table 35, adding item 13 and conditional C.4. TSE 15447 (rating 1): Editorials to address Erratum 15353 (Vol 3), globally change "Master" to "Central" and "Slave" to "Peripheral". Consistency Checker fixes and template-related editorials.
36	p36	2020-12-22	Approved by BTI on 2020-12-03. Prepared for TCRL 2020-1 publication.
	p37r00–r07	2020-12-28 – 2021-06-10	TSE 12794 (rating 2): In Table 2, revised security mode 1 and security mode 3 item conditionals to match with Table 5.1 in the GAP section of Core Spec 4.2 and later, which shows as simply Excluded. TSE 14687 (rating 2): Updated Prerequisite and note C.1 for Table 11a and updated Prerequisite and note C.1 and added note C.2 for item 1 for Table 17a. TSE 14889 (rating 1): Updated all references to remove CSAs and clean up the existing references. References were not forward compatible in previous revision. TSE 15689 (rating 4): To address E15498, added item 14a to Tables 8A and 20A.

Publication Number	Revision Number	Date	Comments
			TSE 16115 (rating 1): Corrected capitalization and references of ICS items, aligning them with Core Spec and other referenced layers. TSE 16608 (rating 1): Fixed wording in item 17 of Tables 8A and 20A. Incorporated Enhanced_Connection_Update_TEST_CR_r17: Added a reference to the v5.3 Core release; added item 8 and note C.2 to Table 23; added item 9 and note C.2 to Table 33. Subsequently updated “Sydney” and “.x” references to real numbers. Minor template-related and consistency checker editorials.
37	p37	2021-07-13	Approved by BTI on 2021-06-27. Prepared for TCRL 2021-1 publication.
	p37ed2r00	2021-07-26	TSE 17284 (rating 1): Added “IF” to C.6 of Table 16 and performed other minor consistency checker editorials.
	p37 edition 2	2021-08-19	Approved by BTI on 2021-08-19. Prepared for edition 2 publication.
	p38r00–r02	2021-08-27 – 2021-12-28	TSE 16688 (rating 2): Changed all BB dependencies to Optional by updating C.3 and Status of item 9 and deleting C.4 in Table 1 and updating C.1 in Table 4. TSE 17496 (rating 1): Capitalization change to table numbers (8a and 20a) to make consistent and align with Launch Studio. Performed template-related fixes and consistency checker editorials. Updated the copyright page to align with v2 of the DNMD.
38	p38	2022-01-25	Approved by BTI on 2021-12-27. Prepared for TCRL 2021-2 publication.
	p38ed2 r00–r02	2022-02-01 – 2022-03-07	TSE 18025 (rating 1): Corrected references in items 11–17 of Tables 8a and 20a. TSE 18359 (rating 1): Updated “is/not supported” language in conditionals globally to align with new conventions. Simplified C.1 in Table 22. Template-related editorials.
	p38, edition 2	2022-03-07	Approved by BTI on 2022-03-07. Prepared for edition 2 publication.
	p39r00–r12	2022-09-30 – 2022-12-15	TSE 17191 (rating 2): Updated the conditionals for the Secure Connections Only Mode items (GAP 2/11, GAP 25/10, and GAP 35/10) to align with E17214 requirements to support over all supported transports. TSE 18444 (rating 4): Per E17946, added items 8a/18 and 20a/19. TSE 18547 (rating 1): Cleaned up conditionals to align with the latest ICS conventions and removed unnecessary intro text from Section 1.5.1. TSE 18669 (rating 2): Per E18668, added conditionals to 24/3 and 34/3 for Bondable mode.

Publication Number	Revision Number	Date	Comments
			TSE 20648 (rating 3): Updated 25/5 and 25/6 with conditional C.6. Updated conditional for 25/9, 25/11, and 25/12 and set C.3 to no longer used. Updated conditional for 35/9, 35/11, and 35/12 and set C.2 to no longer used. Added new Table 27b for SM Peripheral ILD requirements and new Table 37b for SM Central ILD requirements. Converted Table 41 and Table 43 to contain an ILD column, and removed conditionals. TSE 22131 (rating 1): Corrected reference for CSS. TSE 22228 (rating 4): Per E22185, added new items 11a/4 and 17a/3 and associated conditionals. Core v5.4 CRs: EAD (from CR Encrypted_Advertising_Data.Test .CR.13): Added a new reference for Core v5.4. Added 20a/18, 25/14, 27/10, 30/3 with conditional C.2, and 35/14. EAD (from CR Encrypted_Advertising_Data.Test .CR.14): Added 8a/19 to address E22205. Incorporated Test Issue 22239 for EAD, with r02 CR from comment 963971. Added items 8a/20, 14a/20, and 30a/20. Resolved TBD references per Clive's email conversion list. SLC (from CR Security_Level_Characteristics.Test.CR_r07): Added 27/11 and 37/4 to cover LE GATT Security Levels related to Core v5.4 release. PAwR (Periodic_Advertising_with_Responses_TEST_CR_r22): Added item 11a/3 and associated C.3 and 20a/20 and associated C.4.
39	p39	2023-02-07	Approved by BTI on 2022-12-28. Prepared for TCRL 2022-2 publication.
	p40r00	2023-04-16	TSE 22294 (rating 2): Added new 25/14 and related conditional C.7 and new 35/15 and related conditional C.5. TSE 22563 (rating 3): Added new 11/4.
40	p40	2023-06-29	Approved by BTI on 2023-06-05. Prepared for TCRL 2023-1 publication.
	p41r00–r07	2023-08-07 – 2023-11-14	TSE 18350 (rating 2): Added Link Layer ILDs to Tables 8 and 20. TSE 23143 (rating 4): Per E20385, added new 27/10a and related conditional C.2. TSE 23338 (rating 2): Added new items 2/14, 27b/9, 37b/9, 41/2 (with updated status for 41/2a and 41/2b and new conditionals C.1–C.3), and 43/2 (with updated status for 43/2a and 43/2b and new conditionals C.1–C.3). TSE 23525 (rating 2): Removed C.7 and updated the status of 25/14 to Optional. Removed C.5 and updated the status of 35/15 to Optional. Added the GATT ICS to the References section.

Publication Number	Revision Number	Date	Comments
			TSE 24070 (rating 1): Replaced SUM ICS references with CORE ICS references. Updated Table 0 conditionals C.1–C.3 and added C.4, affecting 0/1, 0/2, and 0/3; updated Table 7 conditional C.1, affecting 7/3; updated Table 8 conditional C.1, affecting 8/3 and 8/4; updated Table 10 conditional C.2, affecting 10/3; updated Table 11a prerequisite; updated Table 16 conditional C.1, affecting 16/2; updated Table 17a prerequisite; updated Table 20 conditional C.1, affecting 20/5, 20/6, and 20/7; updated Table 21 conditional C.1, affecting 21/8; updated Table 23 conditional C.2, affecting 23/8; updated Table 27a prerequisite; updated Table 31 conditional C.2, affecting 31/11 and 31/12; updated Table 33 conditional C.2, affecting 33/9; and updated Table 37a prerequisite. TSE 24220 (rating 2): Updated to align ILDs toward L2CAP. Added an “Auto-fill tables” informational section. Added Table 4a to cover L2CAP ILDs. Updated 21/3 status to a conditional from L2CAP. Added Table 27c to cover L2CAP ILDs. Updated 31/3 status to a conditional from L2CAP. Added Table 37c to cover L2CAP ILDs. Added a reference to the L2CAP ICS to the References section.
41	p41	2024-07-01	Approved by BTI on 2024-05-22. Prepared for TCRL 2024-1 publication.
	p42r00–r14	2024-06-24 – 2024-07-31	TSE 22966 (rating 2): Per E18082, updated Table 1 conditional C.1. TSE 23081 (rating 2): Added items 13a–13d for Table 2, updated Table 2 conditional C.11, and added Table 2 conditionals C.12–C.15. Added items 13a–13c for Table 25, updated Table 25 conditional C.5, and added Table 25 conditionals C.7–C.9. Added items 13a–13c for Table 35, updated Table 35 conditional C.4, and added Table 35 conditionals C.5–C.7. TSE 24466 (rating 2): Added Items 11/5, 17/5, 26/5, and 36/6. TSE 24837 (rating 2): Added Item 27b/10. TSE 24878 (rating 2): Per E17874, added item 5 for Table 8 and item 8 for Table 20 and updated conditional C.1 for Tables 8 and 20. TSE 25249 (rating 4): Per E24891, added Section 1.4.6 and Table 4b. In Table 26, added an ILD column, Item 26/6, and conditional C.1. In Table 27, added Item 27/12 and conditional C.3. In Table 37, added Items 37/5 – 37/7 and conditional C.2.

Publication Number	Revision Number	Date	Comments
			TSE 25552 (rating 2): Added Inter-Layer Dependency column to Tables 7, 11a, 13, 14, 17a, 19, 20a, 23, 27, 27a, 29, 30, 33, 37, and 37a. Updated the Capability column for Tables 7, 13, 14, 19, 29, and 30. Updated the Status column for Tables 8a, 11a, 17a, 27a, 37, and 37a. Added conditional C.1 to Table 7. Deleted conditional C.1 from Table 8a. Updated conditionals C.2–C.4 for Table 11a. Added Table 11c. Updated item 3, added items 4–6, and updated conditionals C.1–C.3 for Table 17a. Added item 21 and updated conditionals C.3 and C.4 for Table 20a. Added items 7a and 9 and conditional C.3 for Table 23. Added item 9a and updated conditional C.1 for Table 27. Added items 4–6 and updated conditionals C.1–C.3 for Table 27a. Added items 8a, 10, and 11 and conditional C.3 and updated conditionals C.1 and C.2 for Table 33. Added item 3a and updated conditional C.1 for Table 37. Added items 4–6 and updated conditionals C.1–C.3 for Table 37a. Incorporated CR CS_Test_CR_r16-jorg (which includes Test Issues 23205, 23293, 23331, 23332, 23361, 23362, 23363, 23364, 23365, 23378, 23379, 23381, 23382, 23384, 23404, 23419, 23422, 23424, 23425, 23500, 23501, 23502, 23503, 23504, 23506, 23594, 23693, 23694, 23696, 23701, 23706, 23711, 23732, 23736, 23737, 23738, 23776, 23842, 23923, 23993, 24023, 24033, 24043, 24049, 24133, 24135, 24137, 24138, 24139, 24141, 24142, 24143, 24146, 24147, 24149, 24150, 24151, 24153, 24177, 24181, 24231, 24232, 24330, 24331, 24332, 24410, 24411, 24418, 24419, 24478, 24483, 24515, 24531, 24599, 24601, 24602, 24614, 24618, 24619, 24621, 24623, 24624, 24625, 24627, 24630, 24639, 24645, 24646, 24655, 24656, 24657, 24659, 24660, 24669, 24681, 24717, 24769, 24776, 24789, 24808, 24809, 24838, 24844, 24850, 24867, 24868, 24893, 24894, 24895, 25028, 25029, 25040, 25042, 25053, 25055, 25111, 25112, 25120, 25139, 25140, 25141, 25142, 25143, 25148, 25149, 25150, 25157, 25166, 25209, 25240, 25278, 25282, 25299, 25428, 25443, 25479, 25498, 25511, 25512, 25525, 25585, 25617, 25632). To account for the Channel Sounding feature in Core Specification v6.0, added Tables 23a, 25a, 33a, and 35a. In Table 25, added Items 25/15 – 25/18 and C.10 – C.13. In Table 35, added Items 35/16 – 35/19 and C.8 – C.11. Updated the references list. Incorporated approved Test Issues 25302 and 25788.
42	p42	2024-09-04	Approved by BTI on 2024-08-14. Prepared for TCRL 2024-2 publication.

Publication Number	Revision Number	Date	Comments
	p42ed2r00 – r04	2024-09-13 – 2024-10-03	TSE 26148 (rating 1): Updated the table titles and prerequisites for Tables 23a, 25a, 33a, and 35a and added a GAP Peripheral row in Tables 23a and 33a, with conditionals revised as necessary. TSE 26166 (rating 1): Corrected C.1 for Table 20. TSE 26362 (rating 1): Corrected the references for 25/7, 25/8, 25/9, 25/11, and 25/12 and added appropriate conditionals for 25/11 and 25/12. Corrected the references for 27b/4 and 27b/5 and fixed C.3 verbiage. Corrected the references for 35/7, 35/8, 35/9, 35/11, and 35/12 and added appropriate conditionals for 35/11 and 35/12. Corrected the references for 37b/4 and 37b/5 and fixed C.3 verbiage.
	p42 edition 2	2024-10-24	Approved by BTI on 2024-10-16. Prepared for edition 2 publication.
	p43r00	2024-10-28	TSE 26035 (rating 2): Corrected the prerequisite for Table 37c.
43	p43	2025-02-18	Approved by BTI on 2024-12-26. Prepared for TCRL 2025-1 publication.
	p44r00–r06	2025-01-29 – 2025-03-27	TSE 18571 (rating 2): To accommodate ES-18819 and ES-19323, updated the status of 1/6 with new conditional C.4, set 1/8 to “no longer used”, and changed the status of 1/9 to “optional”; added new Table 4c. TSE 26034 (rating 2): In Table 4b, corrected the references for 4b/3 and 4b/4, updated C.1 and added C.2–C.7, replacing optional statuses with associated new conditionals. For Table 27, removed ILD column, corrected reference for 27/5, set 27/9a and C.1 to “no longer used”, updated C.2, and added C.4–C.10. For Table 37, removed ILD column, set 37/3a and C.1 to “no longer used”, and updated C.2 and added C.3–C.6. TSE 26582 (rating 3): Added new conditionals C.15 and C.16 to Table 25 and updated the status for 25/11 and 25/12; added new conditionals C.13 and C.14 to Table 35 and updated the status of 35/11 and 35/12. TSE 26641 (rating 2): Added a reference to the Channel Sounding ICS. Revised C.10–C.13 of Table 25 and added new C.14, updating the statuses of 25/15–25/18. Added new 25a/9. Revised C.8–C.11 of Table 35 and added new C.12, updating the statuses of 35/16–35/19. Added new 35a/9. TSE 26642 (rating 1): Corrected Table 25a C.2 and C.3 and Table 35a C.2 and C.3 from “Mandatory” to “Optional”. TSE 27042 (rating 1): Corrected table title, capability names, and conditional wording for Table 0 (affects 0/1, 0/2, 0/3).
44	p44	2025-05-06	Approved by BTI on 2025-04-16. Prepared for TCRL 2025-2 publication.

Publication Number	Revision Number	Date	Comments
	p45r00–r06	2025-07-14 – 2025-09-05	TSE 26830 (rating 2): Added references to the ICS document for BB. Added Table 4d and Table 4e to cover LMP and BB requirements, respectively. Updated conditionals and statuses throughout the ICS to align with those changes. TSE 27259 (rating 2): Set Table 0 and Table 38 to “No longer used” and added new Table 0b. Updated all affected prerequisites throughout the ICS. Removed headings that only encompassed “No longer used” material. Removed the Note from Table 5. Set 41/1 and 43/1 to “No longer used”. Added a new “Bridge mapping (informational)” section. TSE 27903 (rating 1): Updated to align with SM ICS edits. Corrected ILDs for 11c/1, 27b/2–27b/5 and 27b/9 and 27b/10, 37b/2–37b/5, and 37b/9; updated Capability names for 27b/6–27b/8 and 37b/6–37b/8; added new items 27b/11 and 27b/12 and associated new conditional C.8; added new items 37b/10 and 37b/11 and associated conditional C.8; and added rows to the Bridge Mapping table to align.
45	p45	2025-11-04	Approved by BTI on 2025-10-05. Prepared for TCRL pkg101 publication.
	p46r00–r12	2025-11-21 – 2026-02-23	TSE 28156 (rating 2): Added new Tables 2a, 25b, and 35b. TSE 28340 (rating 1): To accommodate changes needed for ES-18901, added a conditional to Table 25 and updated the status of 25/2 and added a conditional to Table 35 and updated the status of 35/2. TSE 28545 (rating 1): To accommodate changes needed for the deprecation of Core v4.2, updated the prerequisites for Tables 11a and 17a, removed C.2 from Table 21 and set 21/11 and 21/12 to Optional, and removed C.2 from Table 31 and set 31/11 and 31/12 to Optional.

Publication Number	Revision Number	Date	Comments
			TSE 28562 (rating 2): Added new Tables 8b and 14b to new Control Procedures subsections. Added ILD column to Tables 6, 11, 12, 17, 18, 21, 28, 31, 36. Added new items and associated conditionals as follows: 6/3; 7/3a–7/3c with new C.2–C.4; 8/6; 11/6 with new C.3; 12/3; 13/3, 13/3a with new C.1, C.2; 17/6 with new C.3; 18/3; 20/9; 21/3a with new C.4; 23/8a with new C.4; C.2 added to Table 26 to accommodate change of 26/6 from Optional; 28/3; 31/3a with new C.4; 33/9a with new C.4; and 36/7 with new C.2. Added the following GAP ICS items to the Bridge Mapping table: 6/3, 7/3a, 7/3b, 7/3c, 8/6, 8b/1, 11/6, 12/3, 13/3, 13/3a, 14b/1, 17/6, 18/3, 20/9, 21/3a, 23/8a, 28/3, 31/3a, 33/9a, and 36/7. Updated Capability descriptions of 6/1, 6/2, 12/1, 12/2, 18/1, and 18/2 to include “LE”. Also changed 21/13 and 31/13 (originally added from the CR in TSE 28094) to 21/3a and 31/3a, respectively. Added the RFPHY ICS to the References section. TSE 28786 (rating 1): To accommodate the removal of Data Signing, updated 25:C.6 and corrected the status of GAP 35/5 and GAP 35/6 from Optional to a conditional.
46	p46	2026-05-05	Approved by BTI on 2026-04-07. Prepared for TCRL pkg103 publication.

Acknowledgments

Name	Company
Elisabeth Domínguez Cañizares	AT4 wireless
Noemí Pérez Dans	AT4 wireless
Elisa Rincón	AT4 wireless
Nathan Burns	Bluetooth SIG, Inc.
Gene Chang	Bluetooth SIG, Inc.
Jeff Drake	Bluetooth SIG, Inc.
Alicia Courtney	Broadcom
Norbert Grunert	Broadcom
Chaojing Sun	Broadcom
Mayank Batra	CSR
Chris Church	CSR
Magnus Sommansson	CSR
James Dent	Nokia
Jonathan Tanner	Nokia
Brian A. Redding	Qualcomm