

HID Over GATT Profile (HOGP)

Bluetooth® Test Suite

- **Revision:** HOGP.TS.p11
- **Revision Date:** 2024-07-01
- **Prepared By:** BTI
- **Published during TCRL:** TCRL.2024-1



This document, regardless of its title or content, is not a Bluetooth Specification as defined in the Bluetooth Patent/Copyright License Agreement (“PCLA”) and Bluetooth Trademark License Agreement. Use of this document by members of Bluetooth SIG is governed by the membership and other related agreements between Bluetooth SIG Inc. (“Bluetooth SIG”) and its members, including the PCLA and other agreements posted on Bluetooth SIG’s website located at www.bluetooth.com.

THIS DOCUMENT IS PROVIDED “AS IS” AND BLUETOOTH SIG, ITS MEMBERS, AND THEIR AFFILIATES MAKE NO REPRESENTATIONS OR WARRANTIES AND DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, TITLE, NON-INFRINGEMENT, FITNESS FOR ANY PARTICULAR PURPOSE, THAT THE CONTENT OF THIS DOCUMENT IS FREE OF ERRORS.

TO THE EXTENT NOT PROHIBITED BY LAW, BLUETOOTH SIG, ITS MEMBERS, AND THEIR AFFILIATES DISCLAIM ALL LIABILITY ARISING OUT OF OR RELATING TO USE OF THIS DOCUMENT AND ANY INFORMATION CONTAINED IN THIS DOCUMENT, INCLUDING LOST REVENUE, PROFITS, DATA OR PROGRAMS, OR BUSINESS INTERRUPTION, OR FOR SPECIAL, INDIRECT, CONSEQUENTIAL, INCIDENTAL OR PUNITIVE DAMAGES, HOWEVER CAUSED AND REGARDLESS OF THE THEORY OF LIABILITY, AND EVEN IF BLUETOOTH SIG, ITS MEMBERS, OR THEIR AFFILIATES HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

This document is proprietary to Bluetooth SIG. This document may contain or cover subject matter that is intellectual property of Bluetooth SIG and its members. The furnishing of this document does not grant any license to any intellectual property of Bluetooth SIG or its members.

This document is subject to change without notice.

Copyright © 2011–2024 by Bluetooth SIG, Inc. The Bluetooth word mark and logos are owned by Bluetooth SIG, Inc. Other third-party brands and names are the property of their respective owners.

Contents

1	Scope	6
2	References, definitions, and abbreviations	7
2.1	References	7
2.2	Definitions	7
2.3	Acronyms and abbreviations	7
3	Test Suite Structure (TSS)	8
3.1	Overview	8
3.2	Test Strategy	8
3.2.1	HID over GATT Profile HID Host Testing Configuration	9
3.2.2	HID over GATT Profile HID Device Testing Configuration	10
3.2.3	Test database requirements	10
3.3	Test groups	10
4	Test cases (TC)	11
4.1	Introduction	11
4.1.1	Test case identification conventions	11
4.1.2	Conformance	12
4.1.3	Pass/Fail verdict conventions	12
4.2	Setup preambles	12
4.2.1	ATT Bearer on LE Transport	12
4.2.2	HID Device: Initiate Undirected Connectable mode before Notification	13
4.2.3	HID Host: Initiate Connection when ready to receive Notifications	13
4.3	Generic GATT Integrated Tests	15
	HOGP/RH/CGGIT/SER/BV-01-C [Service GGIT - HID Service - RH]	15
	HOGP/BH/CGGIT/SER/BV-01-C [Service GGIT - HID Service - BH]	15
	HOGP/RH/CGGIT/SER/BV-02-C [Service GGIT - Battery Service - RH]	15
	HOGP/BH/CGGIT/SER/BV-02-C [Service GGIT - Battery Service - BH]	15
	HOGP/RH/CGGIT/SER/BV-03-C [Service GGIT - Device Information Service - RH]	15
	HOGP/BH/CGGIT/SER/BV-03-C [Service GGIT - Device Information Service - BH]	15
	HOGP/RH/CGGIT/CHA/BV-01-C [Characteristic GGIT - Report Map - RH]	15
	HOGP/RH/CGGIT/CHA/BV-02-C [Characteristic GGIT - HID Information - RH]	15
	HOGP/RH/CGGIT/CHA/BV-03-C [Characteristic GGIT - HID Control Point]	15
	HOGP/RH/CGGIT/CHA/BV-04-C [Characteristic GGIT - Protocol Mode - RH]	15
	HOGP/BH/CGGIT/CHA/BV-01-C [Characteristic GGIT - Protocol Mode - BH]	15
	HOGP/BH/CGGIT/CHA/BV-02-C [Characteristic GGIT - Boot Keyboard Input Report - BH]	16
	HOGP/BH/CGGIT/CHA/BV-03-C [Characteristic GGIT - Boot Keyboard Output Report - BH]	16
	HOGP/BH/CGGIT/CHA/BV-04-C [Characteristic GGIT - Boot Mouse Input Report - BH]	16
	HOGP/RH/CGGIT/CHA/BV-05-C [Characteristic GGIT - Battery Level - RH]	16
	HOGP/BH/CGGIT/CHA/BV-05-C [Characteristic GGIT - Battery Level - BH]	16
	HOGP/RH/CGGIT/CHA/BV-06-C [Characteristic GGIT - PnP ID - RH]	16
	HOGP/BH/CGGIT/CHA/BV-06-C [Characteristic GGIT - PnP ID - BH]	16
	HOGP/RH/CGGIT/DES/BV-01-C [Descriptor GGIT - External Report Reference for Report Map]	16
	HOGP/HD/SGGIT/SER/BV-01-C [Service GGIT - HID Service - Single Instance]	16
	HOGP/HD/SGGIT/SER/BV-02-C [Service GGIT - HID Service - Multiple Instances]	17
	HOGP/HD/SGGIT/SER/BV-03-C [Service GGIT - Battery Service]	17
	HOGP/HD/SGGIT/SER/BV-04-C [Service GGIT - Device Information Service]	17
	HOGP/HD/SGGIT/SER/BV-05-C [Service GGIT - Scan Parameters Service]	17
4.4	Discovery of Characteristics and Characteristic Descriptors	18
	HOGP/RH/HGDC/BV-03-C [Discover Report Characteristics]	18

HOGP/RH/HGDC/BV-04-C [Discover Report Characteristic Client Characteristic Configuration Descriptors]	19
HOGP/RH/HGDC/BV-05-C [Discover Report Characteristic Report Reference Characteristic Descriptors]	20
HOGP/BH/HGDC/BV-13-C [Discover Boot Mouse Input Report Client Characteristic Configuration Descriptor].....	22
4.5 Read Features	23
HOGP/RH/HGRF/BV-02-C [Read External Report Reference Characteristic Descriptors for Report Map Characteristics]	23
HOGP/RH/HGRF/BV-03-C [Read Report Characteristics – Input Report]	24
HOGP/RH/HGRF/BV-04-C [Read Report Reference Characteristic Descriptors for Report Characteristics – Input Report]	26
HOGP/RH/HGRF/BV-05-C [Read Client Characteristic Configuration Descriptors for Report Characteristics – Input Report]	28
HOGP/RH/HGRF/BV-19-C [Read Report Characteristics – Output Report]	29
HOGP/RH/HGRF/BV-06-C [Read Report Reference Characteristic Descriptors for Report Characteristics – Output Report]	31
HOGP/RH/HGRF/BV-07-C [Read Report Characteristics – Feature Report]	32
HOGP/RH/HGRF/BV-08-C [Read Report Reference Characteristic Descriptors for Report Characteristics – Feature Report].....	34
4.5.1 Read Protocol Mode Characteristics (Get Protocol Mode Command)	35
HOGP/RH/HGRF/BV-18-C [Read Protocol Mode Characteristics (Get Boot Protocol Mode Command) - RH]	35
HOGP/BH/HGRF/BV-18-C [Read Protocol Mode Characteristics (Get Boot Protocol Mode Command) - BH]	35
4.6 Write Features	37
HOGP/RH/HGWF/BV-01-C [Write Report Characteristics – Input Report]	37
HOGP/RH/HGWF/BV-02-C [Write Report Characteristics – Output Report]	39
HOGP/RH/HGWF/BV-04-C [Write Report Characteristics – Feature Report]	40
HOGP/RH/HGWF/BV-05-C [Write HID Control Point Characteristics – Suspend]	42
HOGP/RH/HGWF/BV-06-C [Write HID Control Point Characteristics – Exit Suspend]	43
HOGP/RH/HGWF/BV-07-C [Write Protocol Mode Characteristics – Set Protocol Command (Protocol Mode = Report Protocol Mode)]	44
HOGP/BH/HGWF/BV-08-C [Write Protocol Mode Characteristics – Set Protocol Command (Protocol Mode = Boot Protocol Mode)]	45
4.7 Configuration Features	47
HOGP/RH/HGCF/BV-01-C [Report Characteristic – Input Reports – enable notifications (write with 0x0001)]	47
HOGP/RH/HGCF/BV-02-C [Report Characteristic – Input Reports – disable notifications (write with 0x0000)]	48
HOGP/BH/HGCF/BV-03-C [Boot Keyboard Input Report Characteristic – enable notifications (write with 0x0001)]	49
HOGP/BH/HGCF/BV-04-C [Boot Keyboard Input Report Characteristic – disable notifications (write with 0x0000)]	51
HOGP/BH/HGCF/BV-05-C [Boot Mouse Input Report Characteristic – enable notifications (write with 0x0001)]	52
HOGP/BH/HGCF/BV-06-C [Boot Mouse Input Report Characteristic – disable notifications (write with 0x0000)]	53
4.8 Notification Features	54
HOGP/RH/HGNF/BV-01-C [Report Characteristic Configuration, receive notifications]	54
HOGP/BH/HGNF/BV-02-C [Boot Keyboard Input Report Characteristic Configuration, receive notifications]	55
HOGP/BH/HGNF/BV-03-C [Boot Mouse Input Report Characteristic Configuration, receive notifications]	56
HOGP/RH/HGNF/BI-01-C [Boot Keyboard Input Report Characteristic Configuration, ignore notifications, Report Host]	57
HOGP/BH/HGNF/BI-01-C [Report Characteristic Configuration, ignore notifications, Boot Host]	58
HOGP/RH/HGNF/BI-02-C [Boot Mouse Input Report Characteristic Configuration, ignore notifications, Report Host]	59

5	Test case mapping	61
6	Revision history and acknowledgments	65

1 Scope

This Bluetooth document contains the Test Suite Structure (TSS) and test cases to test the implementation of the Bluetooth HID over GATT Profile Specification with the objective to provide a high probability of air interface interoperability between the tested implementation and other manufacturers' Bluetooth devices.

2 References, definitions, and abbreviations

2.1 References

This document incorporates provisions from other publications by dated or undated reference. These references are cited at the appropriate places in the text, and the publications are listed hereinafter. Additional definitions and abbreviations can be found in [4].

- [1] Test Strategy and Terminology Overview
- [2] Specification of the Bluetooth System, Version 4.0 or later
- [3] ICS Proforma for HID Over GATT Profile, Version 1.0
- [4] HID over GATT Profile Specification, Version 1.0
- [5] GAP Test Suite, GAP.TS
- [6] GATT Test Suite, GATT.TS
- [7] SM Test Suite, SM.TS
- [8] HID Service Specification, Version 1.0
- [9] Battery Service Specification, Version 1.0
- [10] Device Information Service, Version 1.1
- [11] Scan Parameters Service Specification, Version 1.0
- [12] Scan Parameters Profile Specification, Version 1.0
- [13] SCPP Test Suite, SCPP.TS
- [14] HIDS Test Suite, HIDS.TS
- [15] IXIT Proforma for HID Over GATT Profile

2.2 Definitions

In this Bluetooth document, the definitions from [1] and [2] apply.

2.3 Acronyms and abbreviations

In this Bluetooth document, the definitions, acronyms, and abbreviations from [1] and [2] apply.



3 Test Suite Structure (TSS)

3.1 Overview

The HID over GATT Profile is a client of GAP and GATT. This is illustrated in [Figure 3.1](#).




Figure 3.1: HID over GATT Profile Test Model

3.2 Test Strategy

The test objectives are to verify functionality of HID over GATT within a Bluetooth Host and enable interoperability between Bluetooth Hosts on different devices. The testing approach covers mandatory and optional requirements in the specification and matches these to the support of the IUT as described in the ICS. Any defined test herein is applicable to the IUT if the ICS logical expression defined in the Test Case Mapping Table (TCMT) evaluates to true.

The test equipment provides an implementation of the Radio Controller and the parts of the Host needed to perform the test cases defined in this Test Suite. A Lower Tester acts as the IUT's peer device and interacts with the IUT over-the-air interface. The configuration, including the IUT, needs to implement similar capabilities to communicate with the test equipment. For some test cases, it is necessary to stimulate the IUT from an Upper Tester. In practice, this could be implemented as a special test interface, a Man Machine Interface (MMI), or another interface supported by the IUT.

This Test Suite contains Valid Behavior (BV) tests complemented with Invalid Behavior (BI) tests where required. The test coverage mirrored in the Test Suite Structure is the result of a process that started with catalogued specification requirements that were logically grouped and assessed for testability enabling coverage in defined test purposes.

3.2.1 HID over GATT Profile HID Host Testing Configuration

The following configuration is recommended for testing HID over GATT Profile HID Host IUT:




Figure 3.2: HID over GATT Profile HID Host Testing Configuration

The sample database of Characteristics used by the Lower Tester is specified in each test case.

All HID over GATT Profile HID Host test cases, which use a configuration as shown in [Figure 3.2](#), contain test procedure descriptions and expected results. These in turn use example message syntax between the Upper tester and the IUT. Those example messages are generic; there is no normative specification for these messages. The normative specifications are the functional descriptions for the test procedures and the expected results.

In test cases where more than one alternative method of performing the test case exists, a HID Host IUT performs the test case once for each supported alternative method.

3.2.2 HID over GATT Profile HID Device Testing Configuration

The following configuration is recommended for testing HID over GATT Profile HID Device IUT:




Figure 3.3: HID over GATT Profile HID Device Testing Configuration

In test cases where more than one alternative method of performing the test case exists, a HID Device IUT performs the test case once for each supported alternative method.

3.2.3 Test database requirements

The following requirements apply to the set of databases used by the Lower Tester for testing of GATT Client functionality:

- The Lower Tester includes multiple instantiations of the HID Service, including all defined characteristics.

3.3 Test groups

The following test groups have been defined:

- Generic GATT Integrated Tests
- Discovery of Characteristics and Characteristic Descriptors
- Read Features
- Write Features
- Configuration Features
- Notification Features

4 Test cases (TC)

4.1 Introduction

4.1.1 Test case identification conventions

Test cases are assigned unique identifiers per the conventions in [1]. The convention used here is:

<spec abbreviation>/<IUT role>/<class>/<feat>/<func>/<subfunc>/<cap>/<xx>-<nn>-<y>.

Additionally, testing of this specification includes tests from the GATT Test Suite [6] referred to as Generic GATT Integrated Tests (GGIT); when used, the test cases in GGIT are referred to through a TCID string using the following convention:

<spec abbreviation>/<IUT role>/<GGIT test group>/< GGIT class >/<xx>-<nn>-<y>.

Identifier Abbreviation	Spec Identifier <spec abbreviation>
HOGP	HID over GATT Profile
Identifier Abbreviation	Role Identifier <IUT role>
BH	HID over GATT Profile Boot Host Role
HD	HID over GATT Profile HID Device Role
RH	HID over GATT Profile Report Host Role
Identifier Abbreviation	Reference Identifier <GGIT test group>
CGGIT	Client Generic GATT Integrated Tests
SGGIT	Server Generic GATT Integrated Tests
Identifier Abbreviation	Reference Identifier <GGIT class>
CHA	Characteristic
DES	Descriptor
SER	Service
Identifier Abbreviation	Class identifier <class>
HGCF	HID over GATT Profile Configuration Features
HGDC	HID over GATT Profile Discovery of Characteristics and Characteristic Descriptors
HGDR	HID over GATT Profile Related Services Discovery
HGDS	HID over GATT Profile Discovery of Services
HGNF	HID over GATT Profile Notification Features
HGRF	HID over GATT Profile Read Features
HGWF	HID over GATT Profile Write Features

Table 4.1: HOGP TC feature naming conventions

Note: The term HID Host is used throughout this document to refer to a GATT Client which implements the HID over GATT Profile; there are two variations of the HID Host Role; the Report Host and the Boot Host. Where Report Host is used, it refers only the Report Host Role as defined in the HID over GATT Profile. Where Boot Host is used, it refers only to the Boot Host Role as defined in the HID over GATT Profile. Where HID Host is used, it refers equally to either the Report Host Role or the Boot Host Role.

4.1.2 Conformance

When conformance is claimed for a particular specification, all capabilities are to be supported in the specified manner. The mandatory tests from this Test Suite depend on the capabilities to which conformance is claimed.

The Bluetooth Qualification Program may employ tests to verify implementation robustness. The level of implementation robustness that is verified varies from one specification to another and may be revised for cause based on interoperability issues found in the market.

Such tests may verify:

- That claimed capabilities may be used in any order and any number of repetitions not excluded by the specification
- That capabilities enabled by the implementations are sustained over durations expected by the use case
- That the implementation gracefully handles any quantity of data expected by the use case
- That in cases where more than one valid interpretation of the specification exists, the implementation complies with at least one interpretation and gracefully handles other interpretations
- That the implementation is immune to attempted security exploits

A single execution of each of the required tests is required to constitute a Pass verdict. However, it is noted that to provide a foundation for interoperability, it is necessary that a qualified implementation consistently and repeatedly pass any of the applicable tests.

In any case, where a member finds an issue with the test plan generated by the Bluetooth SIG qualification tool, with the test case as described in the Test Suite, or with the test system utilized, the member is required to notify the responsible party via an erratum request such that the issue may be addressed.

4.1.3 Pass/Fail verdict conventions

Each test case has an Expected Outcome section. The IUT is granted the Pass verdict when all the detailed pass criteria conditions within the Expected Outcome section are met.

The convention in this Test Suite is that, unless there is a specific set of fail conditions outlined in the test case, the IUT fails the test case as soon as one of the pass criteria conditions cannot be met. If this occurs, the outcome of the test is a Fail verdict.

4.2 Setup preambles

The procedures defined in this section are used to achieve specific conditions on the IUT and the test equipment within the tests defined in this document. The preambles here are commonly used to establish initial conditions.

4.2.1 ATT Bearer on LE Transport

Preamble procedure:

1. Establish an LE transport connection between the IUT and the Lower Tester.
2. Establish an L2CAP channel 0x0004 between the IUT and the Lower Tester over that LE transport.

4.2.2 HID Device: Initiate Undirected Connectable mode before Notification

This is a setup procedure for the HID Device to enter the Undirected Connectable mode and accept connection from a HID Host.

- Reference
 - [2] GAP 9.3.4
- Initial Condition
 - A preamble procedure defined in paragraph 4.2.1 is used to setup the LE transport and L2CAP channel. The HID Device (IUT) and the Lower Tester (HID Host) have bonded following GAP procedures.
 - The HID Device is disconnected.
 - The HID Device has been configured to accept commands from the Upper Tester to generate HID Reports.
- Preamble Procedure
 1. The Lower Tester waits for the IUT to send ADV_IND packets (GAP Undirected Connectable Mode).
 2. After receipt of either advertising packet, the Lower Tester sends CONNECT_REQ and an empty packet to the HID Device IUT.




Figure 4.1: Setup preamble for HID Device: Initiate Undirected Connectable mode before Notification

4.2.3 HID Host: Initiate Connection when ready to receive Notifications

This is a setup procedure for the HID Host to initiate connection to a HID Device.

- Reference
 - [2] GAP 9.3.4
- Initial Condition
 - A preamble procedure defined in paragraph 4.2.1 is used to setup the LE transport and L2CAP channel. The HID Host (IUT) and the Lower Tester (HID Device) have bonded following GAP procedures.

- The HID Host is disconnected.
- The HID Host has been configured to accept commands from the Upper Tester to request and receive Reports.
- Preamble Procedure
 1. The Upper Tester commands the HID Host IUT to initiate a connection.
 2. The Lower Tester sends ADV_IND packets (GAP Undirected Connectable Mode) to the HID Host IUT.
 3. The Lower Tester waits for responses from the HID Host IUT.
 4. The HID Host IUT sends a CONNECT_REQ and an empty packet to the Lower Tester.




Figure 4.2: Setup preamble for HID Host: Initiate Connection when ready to receive Notifications

4.3 Generic GATT Integrated Tests

Execute the Generic GATT Integrated Tests defined in Section 6.3, Server test procedures (SGGIT), and Section 6.4, Client test procedures (CGGIT), in [6] using Table 4.2 and Table 4.3 below as input:

TCID	Service / Characteristic / Descriptor	Reference	Properties	Value Length (Octets)	Service Type
HOGP/RH/CGGIT/SER/BV-01-C [Service GGIT - HID Service - RH]	HID Service - RH	[4] 4.5.1	-	-	Primary Service
HOGP/BH/CGGIT/SER/BV-01-C [Service GGIT - HID Service - BH]	HID Service - BH	[4] 4.3.1	-	-	Primary Service
HOGP/RH/CGGIT/SER/BV-02-C [Service GGIT - Battery Service - RH]	Battery Service - RH	[4] 4.5.3	-	-	Primary Service
HOGP/BH/CGGIT/SER/BV-02-C [Service GGIT - Battery Service - BH]	Battery Service - BH	[4] 4.5.3	-	-	Primary Service
HOGP/RH/CGGIT/SER/BV-03-C [Service GGIT – Device Information Service - RH]	Device Information Service - RH	[4] 4.5.2	-	-	Primary Service
HOGP/BH/CGGIT/SER/BV-03-C [Service GGIT – Device Information Service - BH]	Device Information Service – BH	[4] 4.5.2	-	-	Primary Service
HOGP/RH/CGGIT/CHA/BV-01-C [Characteristic GGIT - Report Map - RH]	Report Map Characteristic - RH	[4] 4.6.1.1	0x02 (Read)	Variable	-
HOGP/RH/CGGIT/CHA/BV-02-C [Characteristic GGIT - HID Information - RH]	HID Information Characteristic - RH	[4] 4.6.1.4, [8] 2.10	0x02 (Read)	4	-
HOGP/RH/CGGIT/CHA/BV-03-C [Characteristic GGIT - HID Control Point]	HID Control Point Characteristic	[4] 4.6.1.3	0x04 (Write Without Response)	Skip	-
HOGP/RH/CGGIT/CHA/BV-04-C [Characteristic GGIT - Protocol Mode - RH]	Protocol Mode Characteristic - RH	[4] 4.6.1.5	0x06 (Read, Write Without Response)	Skip	-
HOGP/BH/CGGIT/CHA/BV-01-C [Characteristic GGIT - Protocol Mode - BH]	Protocol Mode Characteristic - BH	[4] 4.6.1.5	0x06 (Read, Write Without Response)	Skip	-

TCID	Service / Characteristic / Descriptor	Reference	Properties	Value Length (Octets)	Service Type
HOGP/BH/CGGIT/CHA/BV-02-C [Characteristic GGIT - Boot Keyboard Input Report - BH]	Boot Keyboard Input Report Characteristic - BH	[4] 4.4.1.2	0x1A (Read, Write, Notify)	Variable	-
HOGP/BH/CGGIT/CHA/BV-03-C [Characteristic GGIT - Boot Keyboard Output Report - BH]	Boot Keyboard Output Report Characteristic - BH	[4] 4.4.1.3	0x0E (Read, Write, Write Without Response)	Variable	-
HOGP/BH/CGGIT/CHA/BV-04-C [Characteristic GGIT - Boot Mouse Input Report - BH]	Boot Mouse Input Report - BH	[4] 4.4.1.4	0x0A (Read, Write)	Variable	-
HOGP/RH/CGGIT/CHA/BV-05-C [Characteristic GGIT - Battery Level - RH]	Battery Level Characteristic - RH	[4] 4.6.3.1	0x12 (Read, Notify)	1	-
HOGP/BH/CGGIT/CHA/BV-05-C [Characteristic GGIT - Battery Level - BH]	Battery Level Characteristic - BH	[4] 4.4.3.1	0x12 (Read, Notify)	1	-
HOGP/RH/CGGIT/CHA/BV-06-C [Characteristic GGIT - PnP ID - RH]	PnP ID Characteristic - RH	[4] 4.5.2, 4.6.2.1	0x02 (Read)	7	-
HOGP/BH/CGGIT/CHA/BV-06-C [Characteristic GGIT - PnP ID - BH]	PnP ID Characteristic - BH	[4] 4.5.2, 4.6.2.1	0x02 (Read)	7	-
HOGP/RH/CGGIT/DES/BV-01-C [Descriptor GGIT - External Report Reference for Report Map]	External Report Reference Characteristic Descriptors for Report Map Characteristic	[4] 4.6.1.1	0x02 (Read)	Skip	-

Table 4.2: Input for the GGIT Client test procedure

TCID	Service / Characteristic / Descriptor	Reference	Properties	Value Length (Octets)	Service Type
HOGP/HD/SGGIT/SER/BV-01-C [Service GGIT - HID Service – Single Instance]	HID Service – Single Instance	[4] 3.1	-	-	Primary Service, Unique



TCID	Service / Characteristic / Descriptor	Reference	Properties	Value Length (Octets)	Service Type
HOGP/HD/SGGIT/SER/BV-02-C [Service GGIT - HID Service – Multiple Instances]	HID Service – Multiple Instances	[4] 2.5, 3.1	-	-	Primary Service, Multiple
HOGP/HD/SGGIT/SER/BV-03-C [Service GGIT – Battery Service]	Battery Service	[4] 3.2	-	-	Primary Service
HOGP/HD/SGGIT/SER/BV-04-C [Service GGIT – Device Information Service]	Device Information Service	[4] 3.3	-	-	Primary Service, Unique
HOGP/HD/SGGIT/SER/BV-05-C [Service GGIT – Scan Parameters Service]	Scan Parameters Service	[4] 3.4	-	-	Primary Service, Unique

Table 4.3: Input for the GGIT Server test procedure

4.4 Discovery of Characteristics and Characteristic Descriptors

The procedures defined in this Test Group verify discovery of the Characteristics and Characteristic Descriptors defined in the HID Service Specification [8], the Battery Service Specification [9] and the Device Information Service Specification [10] by a HID Host IUT, a Report Host IUT and a Boot Host IUT.

HOGP/RH/HGDC/BV-03-C [Discover Report Characteristics]


- Test Purpose

Verify that all Report characteristic can be discovered by a Report Host IUT.
- Reference


[4] 4.6.1.2
- Initial Condition
 - Establish an ATT Bearer connection between the Lower Tester and the IUT as defined in Section 4.2.1.
 - The IUT and Lower Tester have bonded following GAP procedures.
 - The Lower Tester has two instances of the HID Service [8].
 - The IUT has executed HOGP/RH/CGGIT/SER/BV-01-C [Service GGIT - HID Service - RH] or HOGP/BH/CGGIT/SER/BV-01-C [Service GGIT - HID Service - BH] and has saved the handle range for each instance of the HID Service available in the Lower Tester. Each instance contains one or more instances of the Report characteristic.
- Test Procedure

The Upper Tester issues a command to the IUT to discover characteristics using the handle ranges returned in the initial condition. There are two alternatives:

 1. Execute the GATT Discover All Characteristics of a Service sub-procedure once for each HID Service instance, with the handle ranges specified in initial conditions.



- Execute the GATT Discover Characteristics by UUID sub-procedure once for each HID Service instance, with the characteristic UUID set to «Report» with the database specified in [8].



- Expected Outcome

Pass verdict

The IUT sends correctly formatted *ATT_Read_By_Type_Requests* to the Lower Tester.

The IUT receives the *ATT_Read_By_Type_Responses* from the Lower Tester and reports the attribute handle-value pair for each discovered Report characteristic discovered to the Upper Tester.

Each attribute handle-value pair returned matches a Report characteristic attribute handle-value pair implemented in the Lower Tester.

HOGP/RH/HGDC/BV-04-C [Discover Report Characteristic Client Characteristic Configuration Descriptors]

- Test Purpose

Verify that the Client Characteristic Configuration characteristic descriptors for all Report characteristics can be discovered by a Report Host IUT.

- Reference

[4] 4.6.1.2

- Initial Condition


- Establish an ATT Bearer connection between the Lower Tester and the IUT as defined in Section 4.2.1.
- The IUT and Lower Tester have bonded following GAP procedures.
- The Lower Tester has two instances of the HID Service [8].
- The IUT has executed HOGP/RH/HGDC/BV-03-C [Discover Report Characteristics] and has saved the handle range for each instance of the HID Service and the handles for each instance of the Report characteristic available in the Lower Tester. At least one HID Service instance has at

least one instance of the Report characteristic, and each instance of the Report characteristic may have one and only one Client Characteristic Configuration Descriptor.

- Test Procedure

The Upper Tester issues a command to the IUT to Discover All Characteristic Descriptors using the handle ranges returned after running [HOGP/RH/HGDC/BV-03-C \[Discover Report Characteristics\]](#) above.

The IUT executes one pass of the GATT Discover all Characteristics Descriptors sub-procedure for each instance of the Report characteristic, using the handle ranges specified in initial conditions.



- Expected Outcome

Pass verdict

The IUT sends *ATT_Find_Information_Requests* to the Lower Tester until all Client Characteristic Configuration Descriptors of all Report characteristics are found.

All attribute handle/UUID pairs are returned with UUID = «Client Characteristic Configuration» and matching attribute handle for each Client Characteristic Configuration characteristic descriptor of each Report characteristic implemented in the Lower Tester.

[HOGP/RH/HGDC/BV-05-C \[Discover Report Characteristic Report Reference Characteristic Descriptors\]](#)

- Test Purpose

Verify that all Report Reference characteristic descriptors for all Report characteristics can be discovered by a Report Host IUT.

- Reference


[\[4\] 4.6.1.2](#)

- Initial Condition
 - Establish an ATT Bearer connection between the Lower Tester and the IUT as defined in Section 4.2.1.
 - The IUT and Lower Tester have bonded following GAP procedures.
 - The Lower Tester has two instances of the HID Service [8].
 - The IUT has executed [HOGP/RH/HGDC/BV-03-C \[Discover Report Characteristics\]](#) and has saved the handle range for each instance of the HID Service and each instance of the Report characteristic available in the Lower Tester. At least one HID Service instance has at least one instance of the Report characteristic, and each instance of the Report characteristic has one and only one Report Reference characteristic descriptor. Each Report Reference characteristic descriptor contains a Report ID and Report Type field.

- Test Procedure

The Upper Tester issues a command to the IUT to Discover All Characteristic Descriptors using the handle ranges returned after running [HOGP/RH/HGDC/BV-03-C \[Discover Report Characteristics\]](#) above.

The IUT executes one pass of the GATT Discover all Characteristic Descriptors sub-procedure for each instance of the Report characteristic, using the handle ranges specified in initial conditions.



- Expected Outcome

Pass verdict

The IUT sends *ATT_Find_Information_Requests* to the Lower Tester until all Report Reference characteristic descriptors of all Report characteristics are found.

All attribute handle/UUID pairs are returned with UUID = «Report Reference» and matching attribute handle for each Report Reference characteristic descriptor of each Report characteristic implemented in the Lower Tester.

The Report ID and Report Type values in each Report Reference characteristic descriptor match the values implemented in the Lower Tester.

HOGP/BH/HGDC/BV-13-C [Discover Boot Mouse Input Report Client Characteristic Configuration Descriptor]

- Test Purpose

Verify that the Client Characteristic Configuration characteristic descriptor for the Boot Mouse Input Report characteristic can be discovered by a Boot Host IUT.

- Reference

[\[4\]](#) 4.4.1.4


- Initial Condition

- Establish an ATT Bearer connection between the Lower Tester and the IUT as defined in Section [4.2.1](#).
- The IUT and Lower Tester have bonded following GAP procedures.
- The Lower Tester has two instances of the HID Service [\[8\]](#). One HID Service instance has one instance of the Boot Mouse Input Report characteristic, and the instance of the Boot Mouse Input Report characteristic has one Client Characteristic Configuration Descriptor.
- The IUT may have executed [HOGP/BH/CGGIT/CHA/BV-04-C \[Characteristic GGIT - Boot Mouse Input Report - BH\]](#) and saved the handle range for the instance of the Boot Mouse Input Report characteristic available in the Lower Tester.
- If the IUT has not executed [HOGP/BH/CGGIT/CHA/BV-04-C \[Characteristic GGIT - Boot Mouse Input Report - BH\]](#), it must have executed [HOGP/BH/CGGIT/CHA/BV-06-C \[Characteristic GGIT - PnP ID - BH\]](#) or [HOGP/RH/CGGIT/CHA/BV-06-C \[Characteristic GGIT - PnP ID - RH\]](#) and saved the handle range for the instance of the Boot Mouse Input Report characteristic available in the Lower Tester.

- Test Procedure

The Upper Tester issues a command to the IUT to Discover All Characteristic Descriptors using the handle range returned in the initial condition.

The IUT executes one pass of the GATT Discover all Characteristic Descriptors sub-procedure for each HID Service instance, using the handle range specified in initial conditions.



- Expected Outcome

Pass verdict

The IUT sends *ATT_Find_Information_Requests* to the Lower Tester until the Client Characteristic Configuration Descriptor of the Boot Mouse Input Report characteristics is found.

One attribute handle/UUID pair is returned with UUID = «Client Characteristic Configuration» and matching attribute handle for the Client Characteristic Configuration characteristic descriptor of the Boot Mouse Input Report characteristic implemented in the Lower Tester.

4.5 Read Features

The procedures defined in this test group verify IUT implementation of the Read Features defined in the HID over GATT Profile Specification [4] by a HID Host IUT, a Report Host IUT, and a Boot Host IUT.

HOGP/RH/HGRF/BV-02-C [Read External Report Reference Characteristic Descriptors for Report Map Characteristics]

- Test Purpose

Verify that all External Report Reference characteristic descriptors for all Report Map characteristics can be read by a Report Host IUT.

- Reference

[4] 4.7

[8] 2.6.3.1

- Initial Condition

- Establish an ATT Bearer connection between the Lower Tester and the IUT as defined in Section 4.2.1.
- The IUT and Lower Tester have bonded following GAP procedures.
- The Lower Tester has two instances of the HID Service [8] and one non-HID Service instance with a characteristic whose value is described within the Report Map characteristic value. Each




HID Service instance contains a single instance of the Report Map characteristic. One instance of the Report Map characteristic descriptor contains one instance of the External Report Reference characteristic descriptor. Each characteristic UUID contained within the External Report Reference characteristic descriptors matches a non-HID Service characteristic UUID.

- The IUT has executed [HOGP/RH/CGGIT/CHA/BV-01-C \[Characteristic GGIT - Report Map - RH\]](#) and has saved the attribute handle for each instance of the Report Map characteristic available in the Lower Tester.
- The IUT has executed [HOGP/RH/CGGIT/DES/BV-01-C \[Descriptor GGIT - External Report Reference for Report Map\]](#) and has saved the attribute handle for each instance of the External Report Reference characteristic descriptor available in the Lower Tester.
- Test Procedure

The Upper Tester issues a command to the IUT to read characteristic descriptors.

Execute the GATT Read Characteristic Descriptors sub-procedure once for each handle for the External Report Reference characteristic descriptor specified in initial conditions.



- Expected Outcome

Pass verdict

The IUT sends correctly formatted *ATT_Read_Request* commands to the Lower Tester containing the handle values specified by the Upper Tester.

The IUT receives correctly formatted *ATT_Read_Reponses* to the Upper Tester for each instance of the External Report Reference characteristic descriptor.

The complete characteristic descriptors reported to the Upper Tester match the values implemented in the Lower Tester.

[HOGP/RH/HGRF/BV-03-C \[Read Report Characteristics – Input Report\]](#)


- Test Purpose

Verify that all Report characteristics with a Report Type of Input Report can be read by a Report Host IUT.


- Reference
 - [\[4\]](#) 4.8
 - [\[8\]](#) 2.5.2
- Initial Condition
 - Establish an ATT Bearer connection between the Lower Tester and the IUT as defined in Section [4.2.1](#).
 - ATT_MTU has been exchanged between the IUT and Lower Tester
 - The IUT and Lower Tester have bonded following GAP procedures.
 - The Lower Tester has two instances of the HID Service [\[8\]](#). Each HID Service instance contains one instance of the Report characteristic with a single instance of the Report Reference characteristic descriptor. The HID Report is an Input Report as described via the Report Reference characteristic descriptor.
 - The IUT has executed [HOGP/RH/HGDC/BV-03-C \[Discover Report Characteristics\]](#) and has saved the attribute handle for each instance of the Report characteristic available in the Lower Tester.
 - The IUT has executed [HOGP/RH/HGDC/BV-05-C \[Discover Report Characteristic Report Reference Characteristic Descriptors\]](#) and has saved the attribute handle for each instance of the Report Reference characteristic descriptor available in the Lower Tester.
- Test Procedure

The Upper Tester issues a command to the IUT to read characteristics. There are two alternatives:

1. If the length of the Report characteristic value is less than ATT_MTU, execute the GATT Read Characteristic Value sub-procedure once for each Report characteristic, with the handle for the Report characteristic specified in initial conditions.



2. If the length of the Report characteristic value is greater than ATT_MTU, execute the GATT Read Long Characteristic Value sub-procedure once for each Report characteristic, with the handle for the Report characteristic specified in initial conditions.



- Expected Outcome

Pass verdict

The IUT sends correctly formatted *ATT_Read_Blob_Request* commands to the Lower Tester containing the handle specified by the Upper Tester.

Note: The first request may be an *ATT_Read_Request*; in that case the Lower Tester replies with an *ATT_Read_Response*, and, if the characteristic value length is greater than ATT_MTU, the IUT detects that the characteristic value is long, and continue with *ATT_Read_Blob_Requests*.

The *ATT_Read_Blob_Request* specifies the handle of the characteristic value to be read and the offset value of the first octet to be read. The offset for the first request is 0x0000; subsequent offset values are sequential values of Nx(ATT_MTU-1). The IUT detects the end of the long characteristic value in either of two ways:

- ALT2: Detect the size of the last part attribute value is less than [ATT_MTU-1].
- ALT3: Detect an error response of Invalid Offset, indicating that it has read the complete characteristic value.

Each complete Report characteristic value reported to the Upper Tester matches the value implemented in the Lower Tester.

HOGP/RH/HGRF/BV-04-C [Read Report Reference Characteristic Descriptors for Report Characteristics – Input Report]

- Test Purpose

Verify that all Report Reference characteristic descriptors for all Report characteristics of Report Type: Input Report can be read by a Report Host IUT.

- Reference

[4] 4.8

[8] 2.5.3.2


- Initial Condition

- Establish an ATT Bearer connection between the Lower Tester and the IUT as defined in Section 4.2.1.
- The IUT and Lower Tester have bonded following GAP procedures.
- The Lower Tester has two instances of the HID Service [8]. Each HID Service instance contains one instance of the Report characteristic. Each instance of the Report characteristic contains one and only one instance of the Report Reference characteristic descriptor. Each Report Reference characteristic descriptor contains the value for Report Type which defines an Input Report.
- The IUT has executed HOGP/RH/HGRF/BV-03-C [Read Report Characteristics – Input Report] and has saved the attribute handle for each instance of the Report characteristic and each instance of the Report Reference characteristic descriptor available in the Lower Tester.

- Test Procedure

The Upper Tester issues a command to the IUT to read characteristic descriptors.

Execute the GATT Read Characteristic Descriptors sub-procedure once for each instance of the Report Reference characteristic descriptor specified in initial conditions.



- Expected Outcome

Pass verdict

The IUT sends correctly formatted **ATT_Read_Request** commands to the Lower Tester containing the handle values specified by the Upper Tester.

The IUT receives correctly formatted **ATT_Read_Reponses** to the Upper Tester for each instance of the Report Reference characteristic descriptor.

The Report Type field of each Report Reference characteristic descriptor reported to the Upper Tester matches the value for Report Type=Input Report, and matches the values implemented in the Lower Tester.

HOGP/RH/HGRF/BV-05-C [Read Client Characteristic Configuration Descriptors for Report Characteristics – Input Report]

- Test Purpose

Verify that all Client Characteristic Configuration characteristic descriptors for all Report characteristics of Report Type: Input Report can be read by a Report Host IUT.

- Reference

[\[4\]](#) 4.8

[\[8\]](#) 2.5.3.1


- Initial Condition

- Establish an ATT Bearer connection between the Lower Tester and the IUT as defined in Section [4.2.1](#).
- The IUT and Lower Tester have bonded following GAP procedures.
- The Lower Tester has two instances of the HID Service [\[8\]](#). Each HID Service instance contains one instance of the Report characteristic. Each instance of the Report characteristic contains one and only one instance of the Client Characteristic Configuration characteristic descriptor.
- The IUT has executed [HOGP/RH/HGDC/BV-03-C \[Discover Report Characteristics\]](#) and has saved the attribute handle for each instance of the Report characteristic available in the Lower Tester.
- The IUT has executed [HOGP/RH/HGDC/BV-04-C \[Discover Report Characteristic Client Characteristic Configuration Descriptors\]](#) and has saved the attribute handle for each instance of the Client Characteristic Configuration characteristic descriptor for the Report characteristics available in the Lower Tester.
- The IUT has executed [HOGP/RH/HGDC/BV-05-C \[Discover Report Characteristic Report Reference Characteristic Descriptors\]](#) and has saved the attribute handle for each instance of the Report Reference characteristic descriptor where the Report Type defined in the Report Reference characteristic descriptor is an Input Report available in the Lower Tester.

- Test Procedure

The Upper Tester issues a command to the IUT to read characteristic descriptors.

Execute the GATT Read Characteristic Descriptors sub-procedure once for each instance of the Report characteristic whose Report Reference characteristic descriptor defines an Input Report as specified in initial conditions.



- Expected Outcome

Pass verdict

The IUT sends correctly formatted *ATT_Read_Request* commands to the Lower Tester containing the attribute handle values specified by the Upper Tester.

The IUT receives correctly formatted *ATT_Read_Reponses* to the Upper Tester for each instance of the Client Characteristic Configuration characteristic descriptor.

The attribute value field of each Client Characteristic Configuration characteristic descriptor reported to the Upper Tester matches the values implemented in the Lower Tester.

HOGP/RH/HGRF/BV-19-C [Read Report Characteristics – Output Report]

- Test Purpose

Verify that all Report characteristics with a Report Type of Output Report can be read by a Report Host IUT.

- Reference

[4] 4.8

[8] 2.5.2

- Initial Condition


- Establish an ATT Bearer connection between the Lower Tester and the IUT as defined in Section 4.2.1.
- ATT_MTU has been exchanged between the IUT and Lower Tester.
- The IUT and Lower Tester have bonded following GAP procedures.
- The Lower Tester has two instances of the HID Service [8]. At least one HID Service instance contains at least one instance of the Report characteristic with a single instance of the Report Reference characteristic descriptor. The HID Report is an Output Report as described via the Report Reference characteristic descriptor.
- The IUT has executed HOGP/RH/HGDC/BV-03-C [Discover Report Characteristics] and has saved the attribute handle for each instance of the Report characteristic available in the Lower Tester.

- The IUT has executed [HOGP/RH/HGDC/BV-04-C \[Discover Report Characteristic Client Characteristic Configuration Descriptors\]](#) and has saved the attribute handle for each instance of the Report Reference characteristic descriptor available in the Lower Tester.


- Test Procedure

The Upper Tester issues a command to the IUT to read characteristics. There are two alternatives:

1. If the length of the HID Report characteristic value is less than ATT_MTU, execute the GATT Read Characteristic Value sub-procedure once for each Report characteristic, with the handles for the Report characteristic specified in initial conditions.



2. If the length of the HID Report characteristic value is greater than ATT_MTU, execute the GATT Read Long Characteristic Value sub-procedure once for each Report characteristic, with the handle for the Report characteristic specified in initial conditions.



- Expected Outcome

Pass verdict

The IUT sends correctly formatted ATT_Read_Blob_Request commands to the Lower Tester containing the handle specified by the Upper Tester.

Note: The first request may be an ATT_Read_Request; in that case the Lower Tester replies with an ATT_Read_Response, and, if the characteristic value length is greater than ATT_MTU, the IUT detects that the characteristic value is long, and continue with ATT_Read_Blob_Requests.

The ATT_Read_Blob_Request specifies the handle of the characteristic value to be read and the offset value of the first octet to be read. The offset for the first request is 0x0000; subsequent offset values are sequential values of Nx(ATT_MTU-1). The IUT detects the end of the long characteristic value in either of two ways:

- ALT2: Detect the size of the last part attribute value is less than [ATT_MTU-1].
- ALT3: Detect an error response of Invalid Offset, indicating that it has read the complete characteristic value.

Each complete Report characteristic value reported to the Upper Tester matches the value implemented in the Lower Tester.

HOGP/RH/HGRF/BV-06-C [Read Report Reference Characteristic Descriptors for Report Characteristics – Output Report]

- Test Purpose

Verify that all Report Reference characteristic descriptors for all Report characteristics of Report Type: Output Report can be read by a Report Host IUT.

- Reference

[4] 4.8

[8] 2.5.3.2


- Initial Condition

- Establish an ATT Bearer connection between the Lower Tester and the IUT as defined in Section 4.2.1.
- The IUT and Lower Tester have bonded following GAP procedures.
- The Lower Tester has two instances of the HID Service [8]. Each HID Service instance contains one instance of the Report characteristic. Each instance of the Report characteristic contains one and only one instance of the Report Reference characteristic descriptor. Each Report Reference characteristic descriptor contains the value for Report Type which defines an Output Report.
- The IUT has executed HOGP/RH/HGRF/BV-19-C [Read Report Characteristics – Output Report] and has saved the attribute handle for each instance of the Report characteristic and each instance of the Report Reference characteristic descriptor available in the Lower Tester.

- Test Procedure

The Upper Tester issues a command to the IUT to read characteristic descriptors.

Execute the GATT Read Characteristic Descriptors sub-procedure once for each instance of the Report Reference characteristic descriptor specified in initial conditions.



- Expected Outcome

Pass verdict

The IUT sends correctly formatted *ATT_Read_Request* commands to the Lower Tester containing the handle values specified by the Upper Tester.

The IUT receives correctly formatted *ATT_Read_Reponses* to the Upper Tester for each instance of the Report Reference characteristic descriptor.

The Report Type field of each Report Reference characteristic descriptor reported to the Upper Tester matches the value for Report Type= Output Report, and matches the values implemented in the Lower Tester.

HOGP/RH/HGRF/BV-07-C [Read Report Characteristics – Feature Report]

- Test Purpose

Verify that all Report characteristics with a Report Type of Feature Report can be read by a Report Host IUT.

- Reference

[4] 4.8

[8] 2.5.2


- Initial Condition

- Establish an ATT Bearer connection between the Lower Tester and the IUT as defined in Section 4.2.1.
- ATT_MTU has been exchanged between the IUT and Lower Tester.
- The IUT and Lower Tester have bonded following GAP procedures.
- The Lower Tester has two instances of the HID Service [8]. Each HID Service instance contains one instance of the Report characteristic, each with a single instance of the Report Reference characteristic descriptor. Each Report characteristic is a Feature Report as defined by the Report Reference characteristic descriptor.


- The IUT has executed [HOGP/RH/HGDC/BV-03-C \[Discover Report Characteristics\]](#) and has saved the attribute handle for each instance of the Report characteristic available in the Lower Tester.
 - The IUT has executed [HOGP/RH/HGDC/BV-04-C \[Discover Report Characteristic Client Characteristic Configuration Descriptors\]](#) and has saved the attribute handle for each instance of the Report Reference characteristic descriptor available in the Lower Tester.
- Test Procedure

The Upper Tester issues a command to the IUT to read characteristics. There are two alternatives:

1. If the length of the HID Report characteristic value is less than ATT_MTU, execute the GATT Read Characteristic Value sub-procedure once for each Report characteristic, with the handle for the Report characteristic specified in initial conditions.



2. If the length of the HID Report characteristic value is greater than ATT_MTU, execute the GATT Read Long Characteristic Value sub-procedure once for each Report characteristic, with the handle for the Report characteristic specified in initial conditions.



- Expected Outcome

Pass verdict

The IUT sends correctly formatted ATT_Read_Blob_Request commands to the Lower Tester containing the handle specified by the Upper Tester.

Note: The first request may be an ATT_Read_Request; in that case the Lower Tester replies with an ATT_Read_Response, and if the characteristic value length is greater than ATT_MTU, the IUT detects that the characteristic value is long, and continue with ATT_Read_Blob_Requests.

The ATT_Read_Blob_Request specifies the handle of the characteristic value to be read and the offset value of the first octet to be read. The offset for the first request is 0x0000; subsequent offset values are sequential values of Nx(ATT_MTU-1). The IUT detects the end of the long characteristic value in either of two ways:

- ALT2: Detect the size of the last part attribute value is less than [ATT_MTU-1].
- ALT3: Detect an error response of Invalid Offset, indicating that it has read the complete characteristic value.

Each complete Report characteristic value reported to the Upper Tester matches the value implemented in the Lower Tester.

HOGP/RH/HGRF/BV-08-C [Read Report Reference Characteristic Descriptors for Report Characteristics – Feature Report]

- Test Purpose

Verify that all Report Reference characteristic descriptors for all Report characteristics of Report Type: Feature Report can be read by a Report Host IUT.

- Reference

[4] 4.8

[8] 2.5.3.2


- Initial Condition

- Establish an ATT Bearer connection between the Lower Tester and the IUT as defined in Section 4.2.1.
- The IUT and Lower Tester have bonded following GAP procedures.
- The Lower Tester has two instances of the HID Service [8]. Each HID Service instance contains one instance of the Report characteristic. Each instance of the Report characteristic contains one and only one instance of the Report Reference characteristic descriptor. Each Report Reference characteristic descriptor contains the value for Report Type which defines a Feature Report.
- The IUT has executed HOGP/RH/HGRF/BV-07-C [Read Report Characteristics – Feature Report] and has saved the attribute handle for each instance of the Report characteristic and each instance of the Report Reference characteristic descriptor available in the Lower Tester.

- Test Procedure

The Upper Tester issues a command to the IUT to read characteristic descriptors.

Execute the GATT Read Characteristic Descriptors sub-procedure once for each instance of the Report Reference characteristic descriptor specified in initial conditions.



- Expected Outcome

Pass verdict

The IUT sends correctly formatted *ATT_Read_Request* commands to the Lower Tester containing the handle values specified by the Upper Tester.

The IUT receives correctly formatted *ATT_Read_Reponses* to the Upper Tester for each instance of the Report Reference characteristic descriptor.

The Report Type field of each Report Reference characteristic descriptor reported to the Upper Tester matches the value for Report Type= Feature Report, and matches the values implemented in the Lower Tester.

4.5.1 Read Protocol Mode Characteristics (Get Protocol Mode Command)

- Test Purpose

Verify that all Protocol Mode characteristics can be read by a HID Host IUT.

- Test Case Configuration

Test Case
HOGP/RH/HGRF/BV-18-C [Read Protocol Mode Characteristics (Get Boot Protocol Mode Command) - RH]
HOGP/BH/HGRF/BV-18-C [Read Protocol Mode Characteristics (Get Boot Protocol Mode Command) - BH]

Table 4.4: Read Protocol Mode Characteristics (Get Protocol Mode Command) test cases

- Reference

[4] 4.11

[8] 2.4.1

- Initial Condition


- Establish an ATT Bearer connection between the Lower Tester and the IUT as defined in Section 4.2.1.
- The IUT and Lower Tester have bonded following GAP procedures.




- The Lower Tester has two instances of the HID Service [8]. Each instance contains a single instance of the Protocol Mode characteristic.
 - The Report Host IUT has executed either [HOGP/RH/CGGIT/CHA/BV-04-C \[Characteristic GGIT - Protocol Mode - RH\]](#) or [HOGP/BH/CGGIT/CHA/BV-01-C \[Characteristic GGIT - Protocol Mode - BH\]](#) and has saved the attribute handle for each instance of the Protocol Mode characteristic available in the Lower Tester. The Boot Host IUT may have executed either [HOGP/RH/CGGIT/CHA/BV-04-C \[Characteristic GGIT - Protocol Mode - RH\]](#) or [HOGP/BH/CGGIT/CHA/BV-01-C \[Characteristic GGIT - Protocol Mode - BH\]](#) and saved the attribute handle for each instance of the Protocol Mode characteristic available in the Lower Tester.
 - If the Boot Host IUT has executed neither [HOGP/RH/CGGIT/CHA/BV-04-C \[Characteristic GGIT - Protocol Mode - RH\]](#) nor [HOGP/BH/CGGIT/CHA/BV-01-C \[Characteristic GGIT - Protocol Mode - BH\]](#), it must have executed either [HOGP/RH/CGGIT/SER/BV-01-C \[Service GGIT - HID Service - RH\]](#) or [HOGP/BH/CGGIT/SER/BV-01-C \[Service GGIT - HID Service - BH\]](#) and have saved the handle range for all HID Service instances available in the Lower Tester.
- Test Procedure

The Upper Tester issues a command to the IUT to read characteristics, there are two alternatives:

1. Execute the GATT Read Characteristic Value sub-procedure once for each instance of the Protocol Mode characteristic, with the handles specified in initial conditions.



2. If the Boot Host IUT has not executed [HOGP/RH/CGGIT/CHA/BV-04-C \[Characteristic GGIT - Protocol Mode - RH\]](#) nor [HOGP/BH/CGGIT/CHA/BV-01-C \[Characteristic GGIT - Protocol Mode - BH\]](#), execute the GATT Read Using Characteristic UUID sub-procedure once for each HID Service instance, with the characteristic UUID set to «Protocol Mode», with the HID Service handle ranges saved as specified in initial conditions.



- Expected Outcome

Pass verdict

1. The IUT sends correctly formatted *ATT_Read_Requests* to the Lower Tester, containing the attribute handle values specified by the Upper Tester and receives correctly formatted *ATT_Read_Responses* from the Lower Tester containing the values of all Protocol Mode characteristics. The IUT reports all received Protocol Mode characteristic values to the Upper Tester.

Or:

2. The Boot Host IUT sends correctly formatted *ATT_Read_By_Type_Requests* to the Lower Tester containing the characteristic UUID values specified by the Upper Tester and receives correctly formatted *ATT_Read_By_Type_Responses* containing the values of all Protocol Mode characteristics. The IUT reports all received Protocol Mode characteristic values to the Upper Tester.

Each complete Protocol Mode characteristic value reported to the Upper Tester matches the values implemented in the Lower Tester for the Protocol Mode field.

4.6 Write Features

The procedures defined in this test group verify IUT implementation of the Write Features defined in the HID over GATT Profile Specification [4] by a HID Host IUT, a Report Host IUT, and a Boot Host IUT.

HOGP/RH/HGWF/BV-01-C [Write Report Characteristics – Input Report]

- Test Purpose

Verify that all Report characteristics with a Report Type of Input Report can be written by a Report Host IUT.

- Reference

[4] 4.8


[8] 2.5.1

- Initial Condition
 - Establish an ATT Bearer connection between the Lower Tester and the IUT as defined in Section 4.2.1.
 - The IUT and Lower Tester have bonded following GAP procedures.
 - The Lower Tester has two instances of the HID Service [8]. Each instance of the HID Service contains at least one instance of the Report characteristic and a single instance of the Report Reference characteristic descriptor within each Report characteristic definition. Each Report Reference characteristic descriptor has the Report Type value field set to the value for Input Report as defined in the HID Service.
 - The IUT has executed [HOGP/RH/HGDC/BV-03-C \[Discover Report Characteristics\]](#) and saved the attribute handles for all Report characteristics available in the Lower Tester. The IUT has also executed [HOGP/RH/HGDC/BV-05-C \[Discover Report Characteristic Report Reference Characteristic Descriptors\]](#) and has saved the attribute handles for all Report Reference characteristic descriptors available in the Lower Tester whose Report Type field is set to the value for Input Report.
 - The contents of the Input Report Data have been declared via IXIT and whose length is small enough to fit in a single transaction (i.e., $\leq [\text{ATT_MTU}-3]$).

- Test Procedure

The Upper Tester issues a command to the IUT to write characteristics.

Execute the GATT Write Characteristic Value sub-procedure once for each Report characteristic of Input Report Type with the handles specified in initial conditions and the value declared for Input Report contents via IXIT.



- Expected Outcome

Pass verdict

The IUT sends correctly formatted *ATT_Write_Requests* to the Lower Tester using the attribute handle specified by the Upper Tester and the values declared via IXIT for Input Report Data.

The Lower Tester confirms the written Report characteristic values match the values sent to the IUT by the Upper Tester.

HOGP/RH/HGWF/BV-02-C [Write Report Characteristics – Output Report]

- Test Purpose

Verify that all Report characteristics with a Report Type of Output Report can be written by a Report Host IUT.

- Reference

[\[4\]](#) 4.8

[\[8\]](#) 2.5.1

- Initial Condition

- Establish an ATT Bearer connection between the Lower Tester and the IUT as defined in Section [4.2.1](#).
- The IUT and Lower Tester have bonded following GAP procedures.
- The Lower Tester has two instances of the HID Service [\[8\]](#). Each instance of the HID Service contains at least one instance of the Report characteristic and a single instance of the Report Reference characteristic descriptor within each Report characteristic definition. Each Report Reference characteristic descriptor has the Report Type value field set to the value for Output Report as defined in the HID Service.
- The IUT has executed [HOGP/RH/HGDC/BV-03-C \[Discover Report Characteristics\]](#) and saved the attribute handles for all Report characteristics available in the Lower Tester. The IUT has also executed [HOGP/RH/HGDC/BV-05-C \[Discover Report Characteristic Report Reference Characteristic Descriptors\]](#) and has saved the attribute handles for all Report Reference characteristic descriptors available in the Lower Tester whose Report Type field is set to the value for Output Report
- The contents of all Output Report Data have been declared via IXIT and whose length is small enough to fit in a single transaction (i.e., $\leq [\text{ATT_MTU}-3]$).

- Test Procedure

The Upper Tester issues a command to the IUT to write characteristics.

There are two alternatives:

1. Execute the GATT Write Characteristic Value sub-procedure once for each Report characteristic of Output Report Type, with the handles specified in initial conditions and the value declared for Output Report contents via IXIT.

Or

2. Execute the GATT Write Without Response sub-procedure once for each Report characteristic of Output Report Type, with the handles specified in initial conditions and the value declared for Output Report contents via IXIT.




Figure 4.3: Alternative 1: Upper Tester Sends WriteRequest – ATT_Write_Request




Figure 4.4: Alternative 2: Upper Tester Sends WriteRequest – ATT_Write_Command

- Expected Outcome

Pass verdict

The IUT sends correctly formatted write requests (either *ATT_Write_Requests* or *ATT_Write_Commands*) to the Lower Tester using the handles specified by the Upper Tester and the values declared via IXIT for Output Report Data.

The Lower Tester confirms the written Report characteristic values match the values sent to the IUT by the Upper Tester.

HOGP/RH/HGWF/BV-04-C [Write Report Characteristics – Feature Report]

- Test Purpose

Verify that all Report characteristics with a Report Type of Feature Report can be written by a Report Host IUT.

- Reference

[4] 4.8

[8] 2.5.1


- Initial Condition

- Establish an ATT Bearer connection between the Lower Tester and the IUT as defined in Section 4.2.1.
- The IUT and Lower Tester have bonded following GAP procedures.
- The Lower Tester has two instances of the HID Service [8]. Each instance of the HID Service contains one instance of the Report characteristic and a single instance of the Report Reference characteristic descriptor within each Report characteristic definition. Each Report Reference characteristic descriptor has the Report Type value field set to the value for Feature Report as defined in the HID Service.
- The IUT has executed [HOGP/RH/HGDC/BV-03-C \[Discover Report Characteristics\]](#) and saved the attribute handles for all Report characteristics available in the Lower Tester. The IUT has also executed [HOGP/RH/HGDC/BV-05-C \[Discover Report Characteristic Report Reference Characteristic Descriptors\]](#) and has saved the attribute handles for all Report Reference characteristic descriptors available in the Lower Tester whose Report Type field is set to the value for Feature Report.
- The contents of the Feature Report Data have been declared via IXIT and whose length is small enough to fit in a single transaction (i.e. $\leq [\text{ATT_MTU}-3]$).

- Test Procedure

The Upper Tester issues a command to the IUT to write characteristics.

Execute the GATT Write Characteristic Value sub-procedure once for each Report characteristic of Feature Report Type with the handles specified in initial conditions and the value declared for Feature Report contents via IXIT.



- Expected Outcome

Pass verdict

The IUT sends correctly formatted *ATT_Write_Requests* to the Lower Tester using the attribute handle specified by the Upper Tester and the values declared via IXIT for Feature Report Data.

The Lower Tester confirms the written Report characteristic values match the values sent to the IUT by the Upper Tester.

HOGP/RH/HGWF/BV-05-C [Write HID Control Point Characteristics – Suspend]

- Test Purpose

Verify that all HID Control Point characteristics can be written with the Suspend command by a Report Host IUT.

- Reference

[4] 4.9

[8] 2.11.2


- Initial Condition

- Establish an ATT Bearer connection between the Lower Tester and the IUT as defined in Section 4.2.1.
- The IUT and Lower Tester have bonded following GAP procedures.
- The Lower Tester has two instances of the HID Service [8]. Each HID Service instance contains a single instance of the HID Control Point characteristic.
- The IUT has executed HOGP/RH/CGGIT/CHA/BV-03-C [Characteristic GGIT - HID Control Point] and has saved the attribute handle of all HID Control Point characteristics available in the Lower Tester.

- Test Procedure

The Upper Tester commands the IUT to write.

Execute the GATT Write Without Response sub-procedure once for each HID Service instance, using the handles returned after running HOGP/RH/CGGIT/CHA/BV-03-C [Characteristic GGIT - HID Control Point], and the value 0x0000 which corresponds to the Suspend command.



- Expected Outcome

Pass verdict

The IUT sends correctly formatted *ATT_Write_Commands* to the Lower Tester using the handles specified by the Upper Tester and the value 0x0000 which corresponds to the Suspend command.

The Lower Tester confirms all HID Control Point characteristic values are written and the values match the values sent by the Upper Tester to the IUT.

HOGP/RH/HGWF/BV-06-C [Write HID Control Point Characteristics – Exit Suspend]

- Test Purpose

Verify that all HID Control Point characteristics can be written with the Exit Suspend command by a Report Host IUT.

- Reference

[4] 4.9

[8] 2.11.2


- Initial Condition

- Establish an ATT Bearer connection between the Lower Tester and the IUT as defined in Section 4.2.1.
- The Lower Tester has two instances of the HID Service [8]. Each instance contains a single instance of the HID Control Point characteristic.
- The IUT has executed [HOGP/RH/CGGIT/CHA/BV-03-C \[Characteristic GGIT - HID Control Point\]](#) and has saved the attribute handles of all HID Control Point characteristics available in the Lower Tester.

- Test Procedure

The Upper Tester commands the IUT to write characteristics.

Execute the GATT Write Without Response sub-procedure once for each instance of the HID Service, with the handles using the handles returned after running [HOGP/RH/CGGIT/CHA/BV-03-C \[Characteristic GGIT - HID Control Point\]](#), and the value for the Exit Suspend command (0x0001).



- Expected Outcome

Pass verdict

The IUT sends correctly formatted *ATT_Write_Commands* to the Lower Tester using the handles specified by the Upper Tester and the value 0x0001 which corresponds to the Exit Suspend command.

The Lower Tester confirms all HID Control Point characteristic values are written and the values match the values sent by the Upper Tester to the IUT.

HOGP/RH/HGWF/BV-07-C [Write Protocol Mode Characteristics – Set Protocol Command (Protocol Mode = Report Protocol Mode)]

- Test Purpose

Verify that all Protocol Mode characteristics can be written with the Set Protocol command (Set Report Protocol Mode) by a Report Host IUT.

- Reference

[4] 4.11

[8] 2.4.1


- Initial Condition

- Establish an ATT Bearer connection between the Lower Tester and the IUT as defined in Section 4.2.1.
- The IUT and Lower Tester have bonded following GAP procedures.
- The Lower Tester has two instances of the HID Service [8]. Each HID Service instance contains a single instance of the Protocol Mode characteristic.
- The Report Host IUT has executed HOGP/RH/CGGIT/CHA/BV-04-C [Characteristic GGIT - Protocol Mode - RH] or HOGP/BH/CGGIT/CHA/BV-01-C [Characteristic GGIT - Protocol Mode - BH] and has saved the attribute handle of all Protocol Mode characteristics available in the Lower Tester.

- Test Procedure

The Upper Tester commands the IUT to write characteristics using the handles returned in the initial condition and the value 0x0001.

Execute the GATT Write Without Response sub-procedure once for each HID Service instance, with the handles specified in initial conditions, and the value 0x0001 which corresponds to the Set Protocol (Set Report Protocol Mode) command.



- Expected Outcome

Pass verdict

The IUT sends correctly formatted *ATT_Write_Commands* to the Lower Tester using the handles specified by the Upper Tester and the value 0x0001 which corresponds to the Set Protocol (Set Report Protocol Mode) command.

The Lower Tester confirms all Protocol Mode characteristic values are written and the values match the values sent by the Upper Tester to the IUT.

HOGP/BH/HGWF/BV-08-C [Write Protocol Mode Characteristics – Set Protocol Command (Protocol Mode = Boot Protocol Mode)]

- Test Purpose

Verify that all Protocol Mode characteristics for HID Services supporting Boot Protocol Mode can be written with the Set Protocol command (Set Boot Protocol Mode) by a Boot Host IUT.

- Reference

[4] 4.11

[8] 2.4.1

- Initial Condition


- Establish an ATT Bearer connection between the Lower Tester and the IUT as defined in Section 4.2.1.
- The IUT and Lower Tester have bonded following GAP procedures.
- The Lower Tester has two instances of the HID Service [8]. Each HID Service instance contains a single instance of the Protocol Mode characteristic.
- The IUT may have executed HOGP/BH/CGGIT/CHA/BV-01-C [Characteristic GGIT - Protocol Mode - BH] or HOGP/RH/CGGIT/CHA/BV-04-C [Characteristic GGIT - Protocol Mode - RH] and saved the attribute handle of all Protocol Mode characteristics available in the Lower Tester.
- If the IUT has not executed HOGP/BH/CGGIT/CHA/BV-01-C [Characteristic GGIT - Protocol Mode - BH] or HOGP/RH/CGGIT/CHA/BV-04-C [Characteristic GGIT - Protocol Mode - RH], it must have executed HOGP/BH/HGRF/BV-18-C [Read Protocol Mode Characteristics (Get Boot Protocol Mode Command) - BH] or HOGP/RH/HGRF/BV-18-C [Read Protocol Mode

[Characteristics \(Get Boot Protocol Mode Command\) - RH](#)] and saved the handles for all instances of the Protocol Mode characteristic available in the Lower Tester.


- Test Procedure

The Upper Tester commands the IUT to write characteristics, there are two alternatives:

1. If the IUT has executed [HOGP/BH/CGGIT/CHA/BV-01-C \[Characteristic GGIT - Protocol Mode - BH\]](#) or [HOGP/RH/CGGIT/CHA/BV-04-C \[Characteristic GGIT - Protocol Mode - RH\]](#), execute the GATT Write Without Response sub-procedure once for each instance of the Protocol Mode characteristic using the handles returned in the initial condition, and using the value 0x0000 which corresponds to the Set Protocol (Set Boot Protocol Mode) command.



2. If the IUT has executed [HOGP/BH/HGRF/BV-18-C \[Read Protocol Mode Characteristics \(Get Boot Protocol Mode Command\) - BH\]](#) or [HOGP/RH/HGRF/BV-18-C \[Read Protocol Mode Characteristics \(Get Boot Protocol Mode Command\) - RH\]](#), execute the GATT Write Without Response sub-procedure once for each instance of the Protocol Mode characteristic, with the Protocol Mode handles saved as specified in initial conditions, and the value 0x0000 which corresponds to the Set Protocol (Set Boot Protocol Mode) command.



- Expected Outcome

Pass verdict

The IUT sends correctly formatted *ATT_Write_Commands* to the Lower Tester using the handles specified by the Upper Tester and the value 0x0000 which corresponds to the Set Protocol (Set Boot Protocol Mode) command.

The Lower Tester confirms all Protocol Mode characteristic values are written and the values match the values sent by the Upper Tester to the IUT.

4.7 Configuration Features

The procedures defined in this test group verify IUT implementation of the Configuration Features defined in the HID over GATT Profile Specification [4] by a Report Host IUT or a Boot Host IUT.

HOGP/RH/HGCF/BV-01-C [Report Characteristic – Input Reports – enable notifications (write with 0x0001)]

- Test Purpose


Verify that all Client Characteristic Configuration characteristic descriptors for all Report characteristics of Report Type: Input Report can be written with the value 0x0001 by a Report Host IUT.
- Reference

[4] 4.8

[8] 2.5.3.1
- Initial Condition
 - Establish an ATT Bearer connection between the Lower Tester and the IUT as defined in Section 4.2.1.
 - The IUT and Lower Tester have bonded following GAP procedures.
 - The Lower Tester has two instances of the HID Service [8]. Each instance of the HID Service contains at least one instance of the Report characteristic with one and only one instance of the Client Characteristic Configuration characteristic descriptor.
 - The IUT has executed HOGP/RH/HGDC/BV-04-C [Discover Report Characteristic Client Characteristic Configuration Descriptors] and saved the attribute handle for the Client Characteristic Configuration characteristic descriptor for each instance of the Report characteristic available in the Lower Tester.
- Test Procedure

The Upper Tester commands the IUT to enable notifications for each Report characteristic using the handles returned after running HOGP/RH/HGDC/BV-04-C [Discover Report Characteristic Client Characteristic Configuration Descriptors].

The IUT sends an *ATT_Write_Request* with the value 0x0001 to the Lower Tester to each of the handles specified in initial conditions.



- Expected Outcome

Pass verdict

The IUT sends correctly formatted *ATT_Write_Requests* to the Lower Tester using the handles specified by the Upper Tester and the value 0x0001.

The IUT receives a correctly formatted *ATT_Write_Response* from the Lower Tester and sends the *WriteResponse* to the Upper Tester.

HOGP/RH/HGCF/BV-02-C [Report Characteristic – Input Reports – disable notifications (write with 0x0000)]

- Test Purpose

Verify that all Client Characteristic Configuration characteristic descriptors for all Report characteristics of Report Type: Input Report can be written with the value 0x0000 by a Report Host IUT.

- Reference


[4] 4.8

[8] 2.5.3.1

- Initial Condition

- Establish an ATT Bearer connection between the Lower Tester and the IUT as defined in Section 4.2.1.
- The IUT and Lower Tester have bonded following GAP procedures.
- The Lower Tester has two instances of the HID Service [8]. Each instance of the HID Service contains at least one instance of the Report characteristic with one and only one instance of the Client Characteristic Configuration characteristic descriptor.
- The IUT has executed HOGP/RH/HGDC/BV-04-C [Discover Report Characteristic Client Characteristic Configuration Descriptors] and saved the attribute handle for the Client Characteristic Configuration characteristic descriptor for each instance of the Report characteristic available in the Lower Tester.

- The Upper Tester commands the IUT to enable notifications for each Report characteristic using the handles returned after running [HOGP/RH/HGDC/BV-04-C \[Discover Report Characteristic Client Characteristic Configuration Descriptors\]](#). The IUT sends an *ATT_Write_Request* with the value 0x0001 to the Lower Tester to each of the handles specified in initial conditions as in [HOGP/RH/HGCF/BV-01-C \[Report Characteristic – Input Reports – enable notifications \(write with 0x0001\)\]](#).
- Test Procedure
 1. The Upper Tester commands the IUT to disable notifications for each Report characteristic using the handles returned after running [HOGP/RH/HGDC/BV-04-C \[Discover Report Characteristic Client Characteristic Configuration Descriptors\]](#).
 2. The IUT sends an *ATT_Write_Request* with the value 0x0000 to the Lower Tester to each of the handles specified in initial conditions.



- Expected Outcome

Pass verdict

The IUT sends correctly formatted *ATT_Write_Requests* to the Lower Tester using the handles specified by the Upper Tester. The IUT successfully disables notification by writing the value 0x0000 to the Client Characteristic Configuration characteristic descriptors for all Report characteristics of Report Type: Input Report.

The IUT receives a correctly formatted *ATT_Write_Response* from the Lower Tester and sends the *WriteResponse* to the Upper Tester.

HOGP/BH/HGCF/BV-03-C [Boot Keyboard Input Report Characteristic – enable notifications (write with 0x0001)]

- Test Purpose

Verify that the Client Characteristic Configuration characteristic descriptor for the Boot Keyboard Input Report characteristic can be written with the value 0x0001 by a Boot Host IUT.

- Reference

[4] 4.12

[8] 2.7.3.1


- Initial Condition

- Establish an ATT Bearer connection between the Lower Tester and the IUT as defined in Section 4.2.1.
- The IUT and Lower Tester have bonded following GAP procedures.
- The Lower Tester has two instances of the HID Service [8]. One instance of the HID Service contains one instance of the Boot Keyboard Input Report characteristic with one instance of the Client Characteristic Configuration characteristic descriptor.
- The IUT may have executed [HOGP/BH/CGGIT/CHA/BV-02-C \[Characteristic GGIT - Boot Keyboard Input Report - BH\]](#) and saved the attribute handle for the Client Characteristic Configuration characteristic descriptor for the instance of the Boot Keyboard Input Report characteristic available in the Lower Tester.

- Test Procedure

The Upper Tester commands the IUT to enable notifications for each Report characteristic using the handle returned after running [HOGP/BH/CGGIT/CHA/BV-02-C \[Characteristic GGIT - Boot Keyboard Input Report - BH\]](#) above.

The IUT sends an *ATT_Write_Request* with the value 0x0001 to the Lower Tester of the handle specified in initial conditions.



- Expected Outcome

Pass verdict

The IUT sends a correctly formatted *ATT_Write_Request* to the Lower Tester using the handle specified by the Upper Tester and the value 0x0001.

The IUT receives a correctly formatted *ATT_Write_Response* from the Lower Tester and sends the *WriteResponse* to the Upper Tester.

HOGP/BH/HGCF/BV-04-C [Boot Keyboard Input Report Characteristic – disable notifications (write with 0x0000)]

- Test Purpose

Verify that the Client Characteristic Configuration characteristic descriptor for the Boot Keyboard Input Report characteristic can be written with the value 0x0000 by a Boot Host IUT.

- Reference

[4] 4.12

[8] 2.7.3.1


- Initial Condition

- Establish an ATT Bearer connection between the Lower Tester and the IUT as defined in Section 4.2.1.
- The IUT and Lower Tester have bonded following GAP procedures.
- The Lower Tester has two instances of the HID Service [8]. One instance of the HID Service contains one instance of the Boot Keyboard Input Report characteristic with one instance of the Client Characteristic Configuration characteristic descriptor.
- The IUT may have executed [HOGP/BH/CGGIT/CHA/BV-02-C \[Characteristic GGIT - Boot Keyboard Input Report - BH\]](#) and saved the attribute handle for the Client Characteristic Configuration characteristic descriptor for the instance of the Boot Keyboard Input Report characteristic available in the Lower Tester.

- Test Procedure

The Upper Tester commands the IUT to enable notifications for each Report characteristic using the handle returned after running [HOGP/BH/CGGIT/CHA/BV-02-C \[Characteristic GGIT - Boot Keyboard Input Report - BH\]](#) above.

The IUT sends an *ATT_Write_Request* with the value 0x0000 to the Lower Tester to the handles specified in initial conditions.



- Expected Outcome

Pass verdict

The IUT sends a correctly formatted *ATT_Write_Request* to the Lower Tester using the handles specified by the Upper Tester and the value 0x0000.

The IUT receives a correctly formatted *ATT_Write_Response* from the Lower Tester and sends the *WriteResponse* to the Upper Tester.

HOGP/BH/HGCF/BV-05-C [Boot Mouse Input Report Characteristic – enable notifications (write with 0x0001)]

- Test Purpose

Verify that all Client Characteristic Configuration characteristic descriptors for the Boot Mouse Input Report characteristic can be written with the value 0x0001 by a Boot Host IUT.

- Reference

[4] 4.14

[8] 2.9.3.1


- Initial Condition

- Establish an ATT Bearer connection between the Lower Tester and the IUT as defined in Section 4.2.1.
- The IUT and Lower Tester have bonded following GAP procedures.
- The Lower Tester has two instances of the HID Service [8]. One instance of the HID Service contains one instance of the Boot Mouse Input Report characteristic with one instance of the Client Characteristic Configuration characteristic descriptor.
- The IUT may have executed HOGP/BH/HGDC/BV-13-C [Discover Boot Mouse Input Report Client Characteristic Configuration Descriptor] and saved the attribute handles for the Client Characteristic Configuration characteristic descriptor for the instance of the Boot Mouse Input Report characteristic available in the Lower Tester.
- If the IUT has not executed HOGP/BH/HGDC/BV-13-C [Discover Boot Mouse Input Report Client Characteristic Configuration Descriptor] it must have executed HOGP/BH/CGGIT/CHA/BV-04-C [Characteristic GGIT - Boot Mouse Input Report - BH] and saved the attribute handle for the Client Characteristic Configuration characteristic descriptor for the instance of the Boot Mouse Input Report characteristic available in the Lower Tester.

- Test Procedure

The Upper Tester commands the IUT to enable notifications for each Report characteristic using the handles returned after running HOGP/BH/HGDC/BV-13-C [Discover Boot Mouse Input Report Client Characteristic Configuration Descriptor] or HOGP/BH/CGGIT/CHA/BV-04-C [Characteristic GGIT - Boot Mouse Input Report - BH] above.

The IUT sends an *ATT_Write_Request* with the value 0x0001 to the Lower Tester to the handle specified in initial conditions.



- Expected Outcome

Pass verdict

The IUT sends a correctly formatted *ATT_Write_Request* to the Lower Tester using the handles specified by the Upper Tester and the value 0x0001.

The IUT receives a correctly formatted *ATT_Write_Response* from the Lower Tester and sends the *WriteResponse* to the Upper Tester.

HOGP/BH/HGCF/BV-06-C [Boot Mouse Input Report Characteristic – disable notifications (write with 0x0000)]

- Test Purpose

Verify that the Client Characteristic Configuration characteristic descriptor for the Boot Mouse Input Report characteristic can be written with the value 0x0000 by a Boot Host IUT.

- Reference

[4] 4.14

[8] 2.9.3.1

- Initial Condition


- Establish an ATT Bearer connection between the Lower Tester and the IUT as defined in Section 4.2.1.
- The IUT and Lower Tester have bonded following GAP procedures.
- The Lower Tester has two instances of the HID Service [8]. One instance of the HID Service contains one instance of the Boot Mouse Input Report characteristic with one instance of the Client Characteristic Configuration characteristic descriptor.
- The IUT may have executed [HOGP/BH/HGDC/BV-13-C \[Discover Boot Mouse Input Report Client Characteristic Configuration Descriptor\]](#) and saved the attribute handle for the Client Characteristic Configuration characteristic descriptor for the instance of the Boot Mouse Input Report characteristic available in the Lower Tester.
- If the IUT has not executed [HOGP/BH/HGDC/BV-13-C \[Discover Boot Mouse Input Report Client Characteristic Configuration Descriptor\]](#) it must have executed [HOGP/BH/CGGIT/CHA/BV-04-C](#)

[[Characteristic GGIT - Boot Mouse Input Report - BH](#)] and saved the attribute handles for the Client Characteristic Configuration characteristic descriptors for the instance of the Boot Mouse Input Report characteristic available in the Lower Tester.

- Test Procedure

The Upper Tester commands the IUT to enable notifications for each Report characteristic using the handle returned after running [HOGP/BH/HGDC/BV-13-C \[Discover Boot Mouse Input Report Client Characteristic Configuration Descriptor\]](#) or [HOGP/BH/CGGIT/CHA/BV-04-C \[Characteristic GGIT - Boot Mouse Input Report - BH\]](#) above.

The IUT sends an *ATT_Write_Request* with the value 0x0000 to the Lower Tester to the handle specified in initial conditions.



- Expected Outcome

Pass verdict

The IUT sends a correctly formatted *ATT_Write_Request* to the Lower Tester using the handle specified by the Upper Tester and the value 0x0000.

The IUT receives a correctly formatted *ATT_Write_Response* from the Lower Tester and sends the *WriteResponse* to the Upper Tester.

4.8 Notification Features

The procedures defined in this test group verify IUT implementation of the Notification Features defined in the HID over GATT Profile Specification [\[4\]](#) by a Report Host IUT and a Boot Host IUT.

[HOGP/RH/HGNF/BV-01-C \[Report Characteristic Configuration, receive notifications\]](#)

- Test Purpose

Verify that, when the Client Characteristic Configuration characteristic descriptor is configured for notification, a Report Host IUT can successfully receive notifications for Report characteristics.

- Reference

[\[4\]](#) 4.8




[\[8\] 2.5.3.1](#)

- Initial Condition
 - Establish an ATT Bearer connection between the Lower Tester and the IUT as defined in Section [4.2.1](#).
 - The IUT and Lower Tester have bonded following GAP procedures.
 - The Lower Tester has two instances of the HID Service [\[8\]](#). Each HID Service instance contains one instance of the Report characteristic of Report Type: Input Report with a single instance of the Client Characteristic Configuration characteristic descriptor.

The IUT has executed [HOGP/RH/HGCF/BV-01-C \[Report Characteristic – Input Reports – enable notifications \(write with 0x0001\)\]](#) to configure all Report characteristics of Report Type: Input Report available in the Lower Tester for notifications.

- Test Procedure

The Lower Tester sends *ATT_Handle_Value_Notifications* containing the characteristic values for all instances of the Report characteristic of Report Type: Input Report to the IUT.



- Expected Outcome

Pass verdict

The IUT reports all received Report characteristic values to the Upper Tester.

The reported values for the Report characteristics match the ones sent by the Lower Tester.

[HOGP/BH/HGNF/BV-02-C \[Boot Keyboard Input Report Characteristic Configuration, receive notifications\]](#)

- Test Purpose

Verify that, when the Client Characteristic Configuration characteristic descriptor is configured for notification, a Boot Host IUT can successfully receive notifications for the Boot Keyboard Input Report characteristic.


- Reference

[\[4\] 4.12](#)

[\[8\] 2.7.3.1](#)

- Initial Condition
 - Establish an ATT Bearer connection between the Lower Tester and the IUT as defined in Section 4.2.1.
 - The IUT and Lower Tester have bonded following GAP procedures.
 - The Lower Tester has two instances of the HID Service [8]. One HID Service instance contains a single instance of the Boot Keyboard Input Report characteristic with a single instance of the Client Characteristic Configuration characteristic descriptor.
 - The IUT has executed [HOGP/BH/HGCF/BV-03-C \[Boot Keyboard Input Report Characteristic – enable notifications \(write with 0x0001\)\]](#) to configure the Boot Keyboard Input Report characteristic for notifications available in the Lower Tester.
- Test Procedure

The Lower Tester sends *ATT_Handle_Value_Notifications* containing the characteristic values for the Boot Keyboard Input Report characteristic to the IUT.



- Expected Outcome

Pass verdict

The IUT reports the received Boot Keyboard Input Report characteristic value to the Upper Tester.

The reported values for the Boot Keyboard Input Report characteristic match the one sent by the Lower Tester.

[HOGP/BH/HGNF/BV-03-C \[Boot Mouse Input Report Characteristic Configuration, receive notifications\]](#)

- Test Purpose

Verify that, when the Client Characteristic Configuration characteristic descriptor is configured for notification, a Boot Host IUT can successfully receive notifications for the Boot Mouse Input Report characteristic.

- Reference

[4] 4.14


[8] 2.9.3.1

- Initial Condition

- Establish an ATT Bearer connection between the Lower Tester and the IUT as defined in Section 4.2.1.
- The IUT and Lower Tester have bonded following GAP procedures.
- The Lower Tester has two instances of the HID Service [8]. One HID Service instance contains a single instance of the Boot Mouse Input Report characteristic with a single instance of the Client Characteristic Configuration characteristic descriptor.
- The IUT has executed [HOGP/BH/HGCF/BV-05-C \[Boot Mouse Input Report Characteristic – enable notifications \(write with 0x0001\)\]](#) to configure the Boot Mouse Input Report characteristic available in the Lower Tester for notifications.

- Test Procedure

The Lower Tester sends *ATT_Handle_Value_Notifications* containing the characteristic values for the Boot Mouse Input Report characteristic to the IUT.



- Expected Outcome

Pass verdict

The IUT reports the received Boot Mouse Input Report characteristic value to the Upper Tester.

The reported value for the Boot Mouse Input Report characteristic matches the one sent by the Lower Tester.

[HOGP/RH/HGNF/BI-01-C \[Boot Keyboard Input Report Characteristic Configuration, ignore notifications, Report Host\]](#)

- Test Purpose

Verify that, when the Client Characteristic Configuration characteristic descriptor is configured for notification, a Report Host IUT will ignore notifications for the Boot Keyboard Input Report characteristic.

- Reference

[4] 4.12


[8] 2.7.3.1

- Initial Condition

- Establish an ATT Bearer connection between the Lower Tester and the IUT as defined in Section 4.2.1.
- The IUT and Lower Tester have bonded following GAP procedures.
- The Lower Tester has two instances of the HID Service [8]. One HID Service instance contains a single instance of the Boot Keyboard Input Report characteristic with a single instance of the Client Characteristic Configuration characteristic descriptor.
- The Lower Tester has configured the instance of the Boot Keyboard Input Report characteristic for notifications.

- Test Procedure

The Lower Tester sends *ATT_Handle_Value_Notifications* containing the characteristic value for the Boot Keyboard Input Report characteristic to the IUT.



- Expected Outcome

Pass verdict

The IUT ignores the received Boot Keyboard Input Report characteristic value and reports no value to the Upper Tester.

HOGP/BH/HGNF/BI-01-C [Report Characteristic Configuration, ignore notifications, Boot Host]

- Test Purpose

Verify that, when the Client Characteristic Configuration characteristic descriptor is configured for notification, a Boot Host IUT will ignore all notifications for Report characteristics.

- Reference


[4] 4.8

[8] 2.5.3.1

- Initial Condition
 - Establish an ATT Bearer connection between the Lower Tester and the IUT as defined in Section 4.2.1.
 - The IUT and Lower Tester have bonded following GAP procedures.
 - The Lower Tester has two instances of the HID Service [8]. Each HID Service instance contains one instance of the Report characteristic of Report Type: Input Report, each with a single instance of the Client Characteristic Configuration characteristic descriptor.
 - The Lower Tester has configured all Report characteristics of Report Type: Input Report for notifications.

- Test Procedure

The Lower Tester sends *ATT_Handle_Value_Notifications* containing the characteristic values for all instances of the Report characteristic of Report Type: Input Report to the IUT.



- Expected Outcome

Pass verdict

The IUT ignores all received Report characteristic values from the Lower Tester and reports no values to the Upper Tester.

HOGP/RH/HGNF/BI-02-C [Boot Mouse Input Report Characteristic Configuration, ignore notifications, Report Host]

- Test Purpose

Verify that, when the Client Characteristic Configuration characteristic descriptor is configured for notification, a Report Host IUT will ignore notifications for the Boot Mouse Input Report characteristic.

- Reference

[4] 4.14

[8] 2.9.3.1


- Initial Condition

- Establish an ATT Bearer connection between the Lower Tester and the IUT as defined in Section 4.2.1.
- The IUT and Lower Tester have bonded following GAP procedures.

- The Lower Tester has two instances of the HID Service [8]. One HID Service instance contains a single instance of the Boot Keyboard Input Report characteristic with a single instance of the Client Characteristic Configuration characteristic descriptor.
- The Lower Tester has configured the instance of the Boot Mouse Input Report characteristic for notifications.

- Test Procedure

The Lower Tester sends *ATT_Handle_Value_Notifications* containing the characteristic value for the Boot Mouse Input Report characteristic to the IUT.



- Expected Outcome

Pass verdict

The IUT ignores the received Boot Mouse Input Report characteristic value and reports no value to the Upper Tester.

5 Test case mapping

The Test Case Mapping Table (TCMT) maps test cases to specific requirements in the ICS. The IUT is tested in all roles for which support is declared in the ICS document.

The columns for the TCMT are defined as follows:

Item: Contains a logical expression based on specific entries from the associated ICS document. Contains a logical expression (using the operators AND, OR, NOT as needed) based on specific entries from the applicable ICS document(s). The entries are in the form of y/x references, where y corresponds to the table number and x corresponds to the feature number as defined in the ICS document for HID Over GATT Profile (HOGP) [4].

Feature: A brief, informal description of the feature being tested.

Test Case(s): The applicable test case identifiers are required for Bluetooth Qualification if the corresponding y/x references defined in the Item column are supported.

For the purpose and structure of the ICS/IXIT, refer to [1].

Item	Feature	Test Case(s)
HOGP 1/2 AND HOGP 9/1	HID Services – RH	HOGP/RH/CGGIT/SER/BV-01-C
HOGP 1/3 AND HOGP 10/1	HID Services – BH	HOGP/BH/CGGIT/SER/BV-01-C
HOGP 1/2 AND HOGP 9/2	Battery Service – RH	HOGP/RH/CGGIT/SER/BV-02-C
HOGP 1/3 AND HOGP 10/2	Battery Service – BH	HOGP/BH/CGGIT/SER/BV-02-C
HOGP 1/2 AND HOGP 9/3	Device Information Service - RH	HOGP/RH/CGGIT/SER/BV-03-C
HOGP 1/3 AND HOGP 10/3	Device Information Service - BH	HOGP/BH/CGGIT/SER/BV-03-C
HOGP 1/2 AND HOGP 9/4	Scan Parameters Service	SCPP.TS: SCPP/CL/CGGIT/SER/BV-01-C
HOGP 3/1 AND NOT HOGP 3/2	HID Service – Single Instance	HOGP/HD/SGGIT/SER/BV-01-C
HOGP 3/1 AND HOGP 3/2	HID Service – Multiple Instances	HOGP/HD/SGGIT/SER/BV-02-C
HOGP 3/3	Battery Service	HOGP/HD/SGGIT/SER/BV-03-C
HOGP 3/4	Device Information Service	HOGP/HD/SGGIT/SER/BV-04-C
HOGP 3/5	Scan Parameters Service	HOGP/HD/SGGIT/SER/BV-05-C
HOGP 1/2 AND HOGP 9/5	Report Map Characteristics for HID Services	HOGP/RH/CGGIT/CHA/BV-01-C
HOGP 1/2 AND HOGP 9/6	External Report Reference Characteristic Descriptors for Report Map	HOGP/RH/CGGIT/DES/BV-01-C
HOGP 1/2 AND HOGP 9/7	Discover Report Characteristics for HID Services	HOGP/RH/HGDC/BV-03-C

Item	Feature	Test Case(s)
HOGP 1/2 AND HOGP 9/8	Discover Client Characteristic Configuration Descriptor for Report	HOGP/RH/HGDC/BV-04-C
HOGP 1/2 AND HOGP 9/9	Discover Report Reference Characteristic Descriptors for Report	HOGP/RH/HGDC/BV-05-C
HOGP 1/2 AND HOGP 9/10	HID Information Characteristics for HID Services	HOGP/RH/CGGIT/CHA/BV-02-C
HOGP 1/2 AND HOGP 9/11	HID Control Point Characteristics for HID Services	HOGP/RH/CGGIT/CHA/BV-03-C
HOGP 1/2 AND HOGP 9/12	Protocol Mode characteristics for HID Services – RH	HOGP/RH/CGGIT/CHA/BV-04-C
HOGP 1/3 AND HOGP 10/4 AND (HOGP 14/5 OR HOGP 14/6)	Protocol Mode characteristics for HID Services – BH	HOGP/BH/CGGIT/CHA/BV-01-C
HOGP 1/2 AND HOGP 9/13	Battery Level Characteristic for Battery Service – RH	HOGP/RH/CGGIT/CHA/BV-05-C
HOGP 1/3 AND HOGP 10/10 AND (HOGP 14/5 OR HOGP 14/6)	Battery Level Characteristic for Battery Service - BH	HOGP/BH/CGGIT/CHA/BV-05-C
HOGP 1/2 AND HOGP 9/15	PnP ID Characteristic for Device Information Service - RH	HOGP/RH/CGGIT/CHA/BV-06-C
HOGP 1/3 AND HOGP 10/12 AND (HOGP 14/5 OR HOGP 14/6)	PnP ID Characteristic for Device Information Service - BH	HOGP/BH/CGGIT/CHA/BV-06-C
HOGP 1/3 AND HOGP 10/5 AND (HOGP 14/5 OR HOGP 14/6)	Boot Keyboard Input Report Characteristics for HID Services	HOGP/BH/CGGIT/CHA/BV-02-C
HOGP 1/3 AND HOGP 10/7 AND (HOGP 14/5 OR HOGP 14/6)	Boot Keyboard Output Report Characteristics for HID Services	HOGP/BH/CGGIT/CHA/BV-03-C
HOGP 1/3 AND HOGP 10/8 AND (HOGP 14/5 OR HOGP 14/6)	Boot Mouse Input Report Characteristics for HID Services	HOGP/BH/CGGIT/CHA/BV-04-C
HOGP 1/3 AND HOGP 10/9	Discover Client Characteristic Configuration Descriptors for Boot Mouse Input Report	HOGP/BH/HGDC/BV-13-C
HOGP 1/2 AND HOGP 11/2	Read External Report Reference Characteristic Descriptors for Report Map	HOGP/RH/HGRF/BV-02-C
HOGP 1/2 AND HOGP 11/3	Read Report Characteristics: Input Report	HOGP/RH/HGRF/BV-03-C

Item	Feature	Test Case(s)
HOGP 1/2 AND HOGP 11/9	Read Report Reference Characteristic Descriptors	HOGP/RH/HGRF/BV-04-C HOGP/RH/HGRF/BV-06-C HOGP/RH/HGRF/BV-08-C
HOGP 1/2 AND HOGP 11/10	Read Client Characteristic Configuration Descriptors for Report: Input Report	HOGP/RH/HGRF/BV-05-C
HOGP 1/2 AND HOGP 11/5	Read Report Characteristics: Output Report	HOGP/RH/HGRF/BV-19-C
HOGP 1/2 AND HOGP 11/7	Read Report Characteristics: Feature Report	HOGP/RH/HGRF/BV-07-C
HOGP 1/2 AND HOGP 11/17	Read Protocol Mode Characteristics (Get Protocol Mode Command)	HOGP/RH/HGRF/BV-18-C
HOGP 1/3 AND HOGP 12/1	Read Protocol Mode Characteristics (Get Protocol Mode Command)	HOGP/BH/HGRF/BV-18-C
HOGP 1/2 AND HOGP 11/4	Write Report Characteristics: Input Report	HOGP/RH/HGWF/BV-01-C
HOGP 1/2 AND HOGP 11/6	Write Report Characteristics: Output Report	HOGP/RH/HGWF/BV-02-C
HOGP 1/2 AND HOGP 11/8	Write Report Characteristics: Feature Report	HOGP/RH/HGWF/BV-04-C
HOGP 1/2 AND HOGP 11/15	Write HID Control Point Characteristics: Suspend	HOGP/RH/HGWF/BV-05-C
HOGP 1/2 AND HOGP 11/16	Write HID Control Point Characteristics: Exit Suspend	HOGP/RH/HGWF/BV-06-C
HOGP 1/2 AND HOGP 11/18	Write Protocol Mode Characteristics: Set Report Protocol	HOGP/RH/HGWF/BV-07-C
HOGP 1/3 AND HOGP 12/2	Write Protocol Mode Characteristics: Set Boot Protocol	HOGP/BH/HGWF/BV-08-C
HOGP 1/2 AND HOGP 11/11	Report Characteristic: Input Report: Enable Notifications	HOGP/RH/HGCF/BV-01-C
HOGP 1/2 AND HOGP 11/11a	Report Characteristic: Input Report: Disable Notifications	HOGP/RH/HGCF/BV-02-C
HOGP 1/3 AND HOGP 12/6	Boot Keyboard Input Report Characteristic: Enable Notifications	HOGP/BH/HGCF/BV-03-C
HOGP 1/3 AND HOGP 12/6a	Boot Keyboard Input Report Characteristic: Disable Notifications	HOGP/BH/HGCF/BV-04-C
HOGP 1/3 AND HOGP 12/12	Boot Mouse Input Report Characteristic: Enable Notifications	HOGP/BH/HGCF/BV-05-C

Item	Feature	Test Case(s)
HOGP 1/3 AND HOGP 12/12a	Boot Mouse Input Report Characteristic: Disable Notifications	HOGP/BH/HGCF/BV-06-C
HOGP 1/2 AND HOGP 11/24	Report Characteristic: Receive Notifications	HOGP/RH/HGNF/BV-01-C
HOGP 1/3 AND HOGP 12/13	Boot Keyboard Input Report Characteristic: Receive Notifications	HOGP/BH/HGNF/BV-02-C
HOGP 1/3 AND HOGP 12/13	Boot Mouse Input Report Characteristic: Receive Notifications	HOGP/BH/HGNF/BV-03-C
HOGP 1/3	Boot Host: Ignore Report Notifications	HOGP/BH/HGNF/BI-01-C
HOGP 1/2	Report Host: Ignore Boot Keyboard Input Report Notifications	HOGP/RH/HGNF/BI-01-C
HOGP 1/2	Report Host: Ignore Boot Mouse Input Report Notifications	HOGP/RH/HGNF/BI-02-C

Table 5.1: Test case mapping

6 Revision history and acknowledgments

Revision History

Publication Number	Revision Number	Date	Comments
0	1.0.0	2011-12-27	Adopted by the Bluetooth SIG Board of Directors
	1.0.1r0	2012-05-18	TSE 4714: Value change in Test Procedure and Pass Verdict for HOGP/RH/HGWF/BV-07-I and HOGP/BH/HGWF/BV-08-I (legacy ID: TP/HGWF/RH/BV-07-C and TP/HGWF/BV-08-C). TSE 4789: TCMT update for HIDS/HD/DES/BV-03-C (legacy ID: TP/DES/BV-03-C) TSE 4727: Pass Verdict clarification for HOGP/BH/HGDC/BV-16-I, HOGP/RH/HGDC/BV-16-I (legacy ID: TP/HGDC/HH/BV-16-C) TSE 4728: TCMT update for HOGP/RH/HGCF/BV-02-I (legacy ID: TP/HGCF/RH/BV-02-C) TSE 4674: TCMT update for HOGP/RH/HGDR/BV-01-I (legacy ID: TP/HGDR/RH/BV-01-C)
1	1.0.1	2012-07-24	Prepare for publication.
	1.0.2r1	2012-09-21	TSE 4927: Change all test cases from –C to –I. TSE 4967: Added references to SCPP and HIDS, editorial changes in HOGP/BH/HGWF/BV-08-I (legacy ID: TP/HGWF/BV-08-I), and added cross-references to the TCMT.
2	1.0.2	2012-10-31	Prepare for publication
	1.0.3r00	2014-04—11	TSE 5529: Updated TCMT mapping for HOGP/HD/HGDS/BV-02-I (legacy ID: TP/HGDS/HD/BV-02-I).
3	1.0.3	2014-07-07	TCRL 2014-1 Publication
	1.0.4r00	2015-10-02	TSE 6653: Added cross-reference to HIDS.TS in HOGP (1/1 AND 4/7) in TCMT; revised HOGP (1/3 AND 12/6) and HOGP (1/3 AND 12/12) items in TCMT. TSE 6487: Removed requirement to support reading Report characteristic value for Input, Output, and Feature reports; renamed Input Report variant, and deleted Output and Feature report duplicates in TCMT.
4	1.0.4	2015-12-22	Prepared for TCRL 2015-2 publication.
	1.0.5r00	2016-05-24	Converted to new Test Case ID conventions as defined in TSTO v4.1
	1.0.5r01	2016-06-08	Corrected roles in Test Case IDs
	1.0.5r02	2016-06-12	Edited MSCs to match new Test Case IDs
	1.0.5r03	2016-06-22	Converted to current TS template
	1.0.5r04	2016-06-24	Corrected roles to match roles declared in ICS.
5	1.0.5	2016-07-13	Prepared for TCRL 2016-1 publication.

Publication Number	Revision Number	Date	Comments
	1.0.6r00	2016-10-08	TSE 7451: Introduced alternative path through HOGP/RH/HGWF/BV-02-I and deleted HOGP/RH/HGWF/BV-03-I
6	1.0.6	2016-12-13	Approved by BTI. Prepared for TCRL 2016-2 publication.
	1.0.7r00	2017-04-26	TSE 8014: Corrected TCMT mapping for HOGP/BH/HGRF/BV-11-I.
7	1.0.7	2017-06-26	Approved by BTI. Prepared for TCRL 2017-1 publication.
	1.0.8r00	2018-05-10	TSE 10618 (rating 3): Modified the initial conditions and clarified the MSC, test procedure, and pass verdict for test case HOGP/RH/HGCF/BV-02-I.
8	1.0.8	2018-06-27	Approved by BTI. Prepared for TCRL 2018-1 publication.
	p9r00–r02	2022-09-19 – 2022-11-14	TSE 19166 (rating 2): Updated the TCMT to remove an incorrect line that should be in HIDS.TS per TSE 18204. Deleted Test Case Applicable column from the TCMT. Updated the introductory text to the Test case mapping section. Performed additional template-related formatting fixes. Added a Publication Number column to the Revision History. Revised the document numbering convention, setting the last release publication of 1.0.8 as p8. Replaced Bluetooth logo in footer and updated the copyright page to align with v2 of the DNMD. Removed the numbering of single TCID headings.
9	p9	2023-02-07	Approved by BTI on 2022-12-28. Prepared for TCRL 2022-2 publication.
	p10r00	2023-05-26	TSE 23225 (rating 1): Changed TCID SCPP/CL/SPDS/BV-01-I to SCPP/CL/CGGIT/SER/BV-01-C in the TCMT to reflect the GGIT conversion done in the SCPP Test Suite. Updated formatting of the Test groups section to align the document with the latest TS template.
10	p10	2023-06-29	Approved by BTI on 2023-05-30. Prepared for TCRL 2023-1 publication.
	p11r00–r04	2023-10-24 – 2024-04-29	TSE 23227 (rating 2): Converted the following 41 test cases to GGIT: HOGP/RH/HGDS/BV-01-I – -03-I; HOGP/BH/HGDS/BV-01-I – -03-I; HOGP/HD/HGDS/BV-01-I – -02-I; HOGP/RH/HGDR/BV-01-I; HOGP/RH/HGDC/BV-01-I and -02-I, -06-I – -08-I, and -14-I – -16-I; HOGP/BH/HGDC/BV-08-I – -12-I and -14-I – -16-I; HOGP/RH/HGRF/BV-01-I and -09-I – -12-I; HOGP/BH/HGRF/BV-10-I – -17-I; and HOGP/BH/HGWF/BV-09-I – -11-I. The 24 new converted TCIDs are: HOGP/BH/CGGIT/CHA/BV-01-C – -06-C, HOGP/BH/CGGIT/SER/BV-01-C – -03-C, HOGP/HD/SGGIT/SER/BV-01-C – -05-C, HOGP/RH/CGGIT/CHA/BV-01-C – -06-C,

Publication Number	Revision Number	Date	Comments
			HOGP/RH/CGGIT/DES/BV-01-C, and HOGP/RH/CGGIT/SER/BV-01-C – -03-C. Added a Test database requirements section. Updated the test procedure and MSCs for HOGP/RH/HGDC/BV-03-I. Updated the test procedure for HOGP/RH/HGDC/BV-04-I and -05-I, HOGP/RH/HGRF/BV-03-I – -08-I and -19-I, and HOGP/RH/HGWF/BV-01-I, -02-I, and -04-I. Updated the initial condition and test procedure for HOGP/BH/HGDC/BV-13-I and HOGP/BH/HGCF/BV-04-I. Updated the initial condition, test procedure, and MSC for HOGP/RH/HGRF/BV-02-I, HOGP/RH/HGRF/BV-18-I, HOGP/BH/HGRF/BV-18-I, HOGP/RH/HGWF/BV-05-I – -07-I, HOGP/BH/HGWF/BV-08-I, and HOGP/BH/HGCF/BV-03-I, -05-I, and -06-I. Updated the TCMT accordingly. Updated the acknowledgments. TSE 23273 (rating 1): Converted -I tests to -C tests as appropriate; updated the TCMT and TCRL accordingly. TSE 23418 (rating 2): To align with updates to the HOGP spec, updated the preamble procedure for ATT Bearer on LE Transport and updated references in HID Device and HID Host preambles. Deleted legacy notation in setup preambles. TSE 25095 (rating 2): Updated the TCMT for HOGP/BH/CGGIT/CHA/BV-01-C – -06-C to replace GATT references with respective HOGP references. Performed other editorials to align the document with the latest TS template, including updates to the test groups and test case identification conventions sections.
11	p11	2024-07-01	Approved by BTI on 2024-04-21. Prepared for TCRL 2024-1 publication.

Acknowledgments

Name	Company
Dejan Berec	Bluetooth SIG, Inc.
Tiberiu Marinescu	Bluetooth SIG, Inc.
Jason Nydegger	Bluetooth SIG, Inc.
Sowmya Ramjee	Bluetooth SIG, Inc.
Chris Church	CSR
Joe Decuir	CSR
Magnus Sommansson	CSR
Miles Smith	Nordic Semiconductor