

Authorization Control Service (ACS)

Bluetooth® Implementation Conformance Statement (ICS) Proforma

- **Revision:** ACS.ICS.p2
- **Revision Date:** 2025-02-18
- **Prepared By:** Medical Devices Working Group
- **Published during TCRL:** TCRL.2025-1



This document, regardless of its title or content, is not a Bluetooth Specification as defined in the Bluetooth Patent/Copyright License Agreement (“PCLA”) and Bluetooth Trademark License Agreement. Use of this document by members of Bluetooth SIG is governed by the membership and other related agreements between Bluetooth SIG Inc. (“Bluetooth SIG”) and its members, including the PCLA and other agreements posted on Bluetooth SIG’s website located at www.bluetooth.com.

THIS DOCUMENT IS PROVIDED “AS IS” AND BLUETOOTH SIG, ITS MEMBERS, AND THEIR AFFILIATES MAKE NO REPRESENTATIONS OR WARRANTIES AND DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, TITLE, NON-INFRINGEMENT, FITNESS FOR ANY PARTICULAR PURPOSE, THAT THE CONTENT OF THIS DOCUMENT IS FREE OF ERRORS.

TO THE EXTENT NOT PROHIBITED BY LAW, BLUETOOTH SIG, ITS MEMBERS, AND THEIR AFFILIATES DISCLAIM ALL LIABILITY ARISING OUT OF OR RELATING TO USE OF THIS DOCUMENT AND ANY INFORMATION CONTAINED IN THIS DOCUMENT, INCLUDING LOST REVENUE, PROFITS, DATA OR PROGRAMS, OR BUSINESS INTERRUPTION, OR FOR SPECIAL, INDIRECT, CONSEQUENTIAL, INCIDENTAL OR PUNITIVE DAMAGES, HOWEVER CAUSED AND REGARDLESS OF THE THEORY OF LIABILITY, AND EVEN IF BLUETOOTH SIG, ITS MEMBERS, OR THEIR AFFILIATES HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

This document is proprietary to Bluetooth SIG. This document may contain or cover subject matter that is intellectual property of Bluetooth SIG and its members. The furnishing of this document does not grant any license to any intellectual property of Bluetooth SIG or its members.

This document is subject to change without notice.

Copyright © 2018–2025 by Bluetooth SIG, Inc. The Bluetooth word mark and logos are owned by Bluetooth SIG, Inc. Other third-party brands and names are the property of their respective owners.



Contents

- 1 General principles 4**
 - 1.1 Implementation Under Test (IUT) identification 4
 - 1.2 Enforcement of inter-layer dependencies 4
- 2 ICS declarations..... 5**
 - 2.1 Versions 5
 - 2.2 Transports 5
 - 2.3 Features 5
 - 2.4 Service requirements 6
 - 2.5 GATT requirements 8
 - 2.6 SDP requirements..... 8
- 3 References 9**
- 4 Revision history and acknowledgments 10**



1 General principles

1.1 Implementation Under Test (IUT) identification

Using the Bluetooth SIG qualification tool, the implementer is expected to declare details about what will be implemented.

1.2 Enforcement of inter-layer dependencies

This ICS includes one or more tables with inter-layer dependencies (ILDs). ILDs are used for specification requirements that are dependent on other supporting specifications. ILDs can refer to an individual ICS item in a separate layer (individual ILD), or it can refer to the full layer (full-layer ILD).

ILDs residing in an X2Core layer will be enforced from the Bluetooth SIG qualification tool in the following conditions, depending on where the referred ILD is residing:

Referred ILD resides in	Individual ILD	Full-layer ILD
Controller layer	Core-Complete configuration, or Referred layer is supported	N/A
Lower HCI layer	HCI is supported	N/A
Upper HCI layer	Core-Host configuration, or UHCI is supported	N/A
Host layer	Core-Host configuration, or Core-Complete configuration, or Referred layer is supported	N/A
X2Core layer	Core-Host configuration, or Core-Complete configuration, or Referred layer is supported	Core-Host configuration, or Core-Complete configuration

Table 1.1: Enforcement of an ILD within the Bluetooth SIG qualification tool

2 ICS declarations

2.1 Versions

Table 0: X.Y Versions

Item	Version	Reference	Status
1	ACS v1.0	[1]	M

Table 1: X.Y.Z Versions

Table number reserved but not yet in use.

2.2 Transports

Table 2: Transport Requirements

Item	Transport	Reference	Status
1	Service supported over BR/EDR	[1] 1.7	C.1
2	Service supported over LE	[1] 1.7	C.1

C.1: Mandatory to support at least one.

2.3 Features

Table 3: Major Features

Item	Capability	Reference	Status
1	Set Security Controls Switch	[1] 4.4.4.27.1	O
2	Descriptors	[1] 4.4.4.27.1	C.1
3	Multiple Restriction Maps	[1] 4.4.4.27.1	O
4	Resource Handle To UUID Map	[1] 4.4.4.27.1	C.1
5	Initiation of Pairing	[1] 4.4.4.27.1	O
6	OOB Key Exchange	[1] 4.4.4.27.1	O
7	ECDH Key Exchange	[1] 4.4.4.27.1	O
8	KDF Key Exchange	[1] 4.4.4.27.1	O
9	Key URI	[1] 4.4.4.27.1	O
10	Invalidate Established Security	[1] 4.4.4.27.1	O
11	ATT_MTU	[1] 4.4.4.27.1	O
12	Protected Resource Uses Write Request	[1] 4.4.4.27.1	O
13	Protected Resource Uses Read Request	[1] 4.4.4.27.1	O
14	Protected Resource Uses Notification	[1] 4.4.4.27.1	O
15	Protected Resource Uses Indication	[1] 4.4.4.27.1	O
16	Key Format AC Server Manufacturer-specific	[1] 4.4.4.27.1	O
17	Key Format AC Client Manufacturer-specific	[1] 4.4.4.27.1	O
18	Key Format AC Server Uncompressed Plain	[1] 4.4.4.27.1	O

Item	Capability	Reference	Status
19	Key Format AC Client Uncompressed Plain	[1] 4.4.4.27.1	O
20	Key Format AC Server X.509	[1] 4.4.4.27.1	O
21	Key Format AC Client X.509	[1] 4.4.4.27.1	O
22	Nonce is a Sequence Number Even-Odd	[1] 3.6.2, 4.3.2	C.2
23	Nonce is a Sequence Number Different Fixed Parts	[1] 3.6.2, 4.3.2	C.2

C.1: Mandatory to support at least one.

C.2: Mandatory to support one and only one.

Table 4: Protection Methods

Item	Capability	Reference	Status
1	Confidentiality	[1] 4.4.4.27.2	O
2	Integrity	[1] 4.4.4.27.2	O
3	Authentication	[1] 4.4.4.27.2	O
4	Authorization	[1] 4.4.4.27.2	O
5	Non-repudiation	[1] 4.4.4.27.2	O
6	Manufacturer-specific Controls Used	[1] 4.4.4.27.2	O

Table 5: Confirmation OOB Methods

Prerequisite: ACS 3/6 “OOB Key Exchange” OR ACS 3/7 “ECDH Key Exchange”

Item	Capability	Reference	Status
1	Confirmation Input OOB Number Action Used: Push	[1] 4.4.4.18.2, 4.4.4.27.6	C.1, C.2
2	Confirmation Input OOB Number Action Used: Input Numeric	[1] 4.4.4.18.2, 4.4.4.27.6	C.1, C.2
3	Confirmation Output OOB Number Action Used: Beep	[1] 4.4.4.18.2, 4.4.4.27.8	C.1, C.2
4	Confirmation Output OOB Number Action Used: Output Numeric	[1] 4.4.4.18.2, 4.4.4.27.8	C.1, C.2
5	Confirmation Static OOB Number Used	[1] 4.4.4.18.2, 4.4.4.27.4	C.1, C.2
6	No Confirmation OOB Method Used	[1] 4.4.4.18.2, 4.4.4.27.3	C.1

C.1: Mandatory to support at least one IF ACS 3/6 “OOB Key Exchange”, otherwise Optional.

C.2: Mandatory to support at least one IF ACS 3/7 “ECDH Key Exchange”, otherwise Optional.

2.4 Service requirements

Table 6: Service Requirements

Item	Capability	Reference	Status
1	Authorization Control Service	[1] 2	M
2	ACS Status	[1] 4, 4.2	M



Item	Capability	Reference	Status
3	ACS Data In	[1] 4, 4.3	C.1
4	ACS Data Out Notify	[1] 4, 4.3	C.2
5	ACS Data Out Indicate	[1] 4, 4.3	C.3
6	ACS Control Point	[1] 4, 4.4	M

- C.1: Mandatory IF ACS 3/12 “Protected Resource Uses Write Request” OR ACS 3/13 “Protected Resource Uses Read Request”, otherwise Excluded.
- C.2: Mandatory IF ACS 3/13 “Protected Resource Uses Read Request” OR ACS 3/14 “Protected Resource Uses Notification”, otherwise Excluded.
- C.3: Mandatory IF ACS 3/15 “Protected Resource Uses Indication”, otherwise Excluded.

Table 7: ACS Control Point Procedures

Item	Capability	Reference	Status
1	Get All Active Descriptors	[1] 4.4.1, 4.4.3.1	C.1
2	Get Restriction Map Descriptor	[1] 4.4.1, 4.4.3.2	C.1
3	Get Restriction Map ID List	[1] 4.4.1, 4.4.3.3	C.1
4	Activate Restriction Map	[1] 4.4.1, 4.4.3.4	C.2
5	Get Resource Handle To UUID Map	[1] 4.4.1, 4.4.3.5	C.3
6	Get Service And Characteristic UUIDs For Characteristic Resource Handle	[1] 4.4.1, 4.4.3.6	C.3
7	Get Information Security Configuration Descriptor	[1] 4.4.1, 4.4.3.7	C.1
8	Get Key Descriptor	[1] 4.4.1, 4.4.3.8	C.4
9	Get Current Key List	[1] 4.4.1, 4.4.3.9	C.4
10	Start Key Exchange	[1] 4.4.1, 4.4.3.10	C.5
11	Invalidate All Established Security	[1] 4.4.1, 4.4.3.11	C.6
12	Invalidate Key	[1] 4.4.1, 4.4.3.12	C.7
13	Abort	[1] 4.4.1, 4.4.3.13	C.8
14	Set Security Controls Switch	[1] 4.4.1, 4.4.3.14	C.9
15	Get Key URI	[1] 4.4.1, 4.4.3.15	C.10
16	Get ACS Feature	[1] 4.4.1, 4.4.3.16	M
17	Key Exchange ECDH	[1] 4.4.1, 4.4.3.17.1.1	C.11
18	Key Exchange ECDH Confirmation Code	[1] 4.4.1, 4.4.3.17.1.2	C.11
19	Key Exchange ECDH Confirmation Random Number	[1] 4.4.1, 4.4.3.17.1.3	C.11
20	Set AC Client Nonce Fixed	[1] 4.4.1, 4.4.3.18	C.14
21	Get ATT_MTU	[1] 4.4.1, 4.4.3.19	C.12
22	Initiate Pairing	[1] 4.4.1, 4.4.3.20	C.13
23	Key Exchange KDF	[1] 4.4.1, 4.4.3.17.2.1	C.5

- C.1: Mandatory IF ACS 3/2 “Descriptors”, otherwise Excluded.
- C.2: Mandatory IF ACS 3/3 “Multiple Restriction Maps”, otherwise Excluded.
- C.3: Mandatory IF ACS 3/4 “Resource Handle To UUID Map”, otherwise Excluded.
- C.4: Mandatory IF ACS 3/6 “OOB Key Exchange” OR ACS 3/7 “ECDH Key Exchange” OR ACS 3/8 “KDF Key Exchange”, otherwise Optional IF ACS 4/6 “Manufacturer-specific Controls Used”, otherwise Excluded.



- C.5: Mandatory IF ACS 3/6 “OOB Key Exchange” OR ACS 3/7 “ECDH Key Exchange” OR ACS 3/8 “KDF Key Exchange”, otherwise Excluded.
- C.6: Mandatory IF ACS 3/10 “Invalidate Established Security”, otherwise Excluded.
- C.7: Mandatory IF (ACS 3/6 “OOB Key Exchange” OR ACS 3/7 “ECDH Key Exchange” OR ACS 3/8 “KDF Key Exchange”) AND ACS 3/10 “Invalidate Established Security”, otherwise Excluded.
- C.8: Mandatory IF ACS 3/2 “Descriptors” OR ACS 3/6 “OOB Key Exchange” OR ACS 3/7 “ECDH Key Exchange” OR ACS 3/8 “KDF Key Exchange”, otherwise Optional.
- C.9: Mandatory IF ACS 3/1 “Set Security Controls Switch”, otherwise Excluded.
- C.10: Mandatory IF ACS 3/9 “Key URI”, otherwise Excluded.
- C.11: Mandatory IF ACS 3/7 “ECDH Key Exchange”, otherwise Excluded.
- C.12: Mandatory IF ACS 3/11 “ATT_MTU”, otherwise Excluded.
- C.13: Mandatory IF ACS 3/5 “Initiation of Pairing”, otherwise Excluded.
- C.14: Mandatory IF ACS 3/23 “Nonce is a Sequence Number Different Fixed Parts”, otherwise Excluded.

2.5 GATT requirements

Table 8: GATT Requirements

Item	Capability	Reference	Status	Inter-Layer Dependency
1	No longer used	N/A	N/A	N/A
1a	GATT Server over BR/EDR	[1] 1.5	C.2	[2] GATT 1a/4
1b	GATT Server over LE	[1] 1.5	C.3	[2] GATT 1a/3
2	Indications	[1] 1.6	M	[2] GATT 4/18
3	Single Notification	[1] 1.6	C.1	[2] GATT 4/17
4	Write Characteristic Value	[1] 1.6	M	[2] GATT 4/14
5	Write Long Characteristic Values	[1] 1.6	O	[2] GATT 4/15
6	Read Characteristic Descriptors	[1] 1.6	M	[2] GATT 4/19
7	Write Characteristic Descriptors	[1] 1.6	M	[2] GATT 4/21

- C.1: Mandatory IF ACS 6/4 “ACS Data Out Notify”, otherwise not defined.
- C.2: Mandatory IF ACS 2/1 “Service supported over BR/EDR”, otherwise not defined.
- C.3: Mandatory IF ACS 2/2 “Service supported over LE”, otherwise not defined.

2.6 SDP requirements

Table 9: SDP Requirements

Prerequisite: ACS 2/1 “Service supported over BR/EDR”

Item	Capability	Reference	Status
1	SDP record present for ACS	[1] 5	M
2–4	No longer used	N/A	N/A



3 References

- [1] Authorization Control Service (ACS) Specification, Version 1.0
- [2] ICS Proforma for Generic Attribute Profile (GATT)



4 Revision history and acknowledgments

Revision History

Publication Number	Revision Number	Date	Comments
0	p0	2022-09-20	Approved by BTI on 2022-08-31. ACS v1.0 adopted by the BoD on 2022-09-13. Prepared for initial publication.
	p1r00	2023-09-08	TSE 23655 (rating 2): Resolved GATT and SDP inter-layer dependencies: In Table 8, marked Item 1 as no longer used, added Items 1a and 1b, and added C.2 and C.3. In Table 9, updated the Capability value for Item 1 and marked Items 2–4 as no longer used. Updated references. Editorials to align the document with the latest ICS template, including updates to conditionals in Table 2, 3, and 5.
1	p1	2024-07-01	Approved by BTI on 2024-04-21. Prepared for TCRL 2024-1 publication.
	p2r00–r01	2024-11-04 – 2024-12-02	TSE 26094 (rating 2): In Table 5, added Items 5 and 6, updated conditionals 1 and 2, and updated the capability, reference, and status for Items 1–4.
2	p2	2025-02-18	Approved by BTI on 2024-12-23. Prepared for TCRL 2025-1 publication.

Acknowledgments

Name	Company
Jörg Brakensiek	Bluetooth SIG, Inc.
Ismail Mohamud	Bluetooth SIG, Inc.
Christoph Fischer	F. Hoffmann-La Roche AG
Nathaniel Hamming	HMT Consulting